Package 'rcontroll'

August 4, 2026

Type Package

Title Individual-Based Forest Growth Simulator 'TROLL'

Version 0.1.3

Maintainer Sylvain Schmitt <sylvain.m.schmitt@gmail.com>

URL https://github.com/sylvainschmitt/rcontroll, https://sylvainschmitt.github.io/rcontroll/

BugReports https://github.com/sylvainschmitt/rcontroll/issues

Description 'TROLL' is coded in C++ and it typically simulates hundreds of thousands of individuals over hundreds of years. The 'rcontroll' R package is a wrapper of 'TROLL'. 'rcontroll' includes functions that generate inputs for simulations and run simulations. Finally, it is possible to analyse the 'TROLL' outputs through tables, figures, and maps taking advantage of other R visualisation packages. 'rcontroll' also offers the possibility to generate a virtual LiDAR point cloud that corresponds to a snapshot of the simulated forest.

License GPL-3

LazyData TRUE

Additional_repositories https://r-lidar.r-universe.dev

Imports methods (>= 3.5.0), utils (>= 3.5.0), readr (>= 1.3.0), sys (>= 3.2), dplyr (>= 1.0.0), magrittr (>= 2.0.0), reshape2 (>= 1.3.0), ggplot2 (>= 3.2.0), viridis (>= 0.4.0), parallel (>= 3.5.0), doParallel (>= 1.0.7), doSNOW (>= 1.0.10), foreach (>= 1.4.1), iterators (>= 1.0.5), Rcpp (>= 1.0.5), gganimate (>= 1.0.0), vroom (>= 1.0.0), tidyr (>= 1.0.0), tibble (>= 3.0.0), lubridate (>= 1.6.0), terra (>= 1.5-16)

Suggests markdown, knitr, rmarkdown, testthat, covr, lidR

RoxygenNote 7.3.1

Collate 'RcppExports.R' 'TROLLv3_climatedaytime12.R' 'TROLLv3_daytimevar.R' 'TROLLv3_input.R' 'TROLLv3_output.R' 'TROLLv3_pointcloud.R' 'TROLLv3_species.R' 'zzz.R' 'TROLLversion.R' 'trollsim.R' 'load_output.R' 'troll.R'

'autogif.R' 'get_chm.trollsim.R' 'trollstack.R'
'autoplot.troll.R' 'utils-pipe.R' 'generate_climate.R'
'generate_lidar.R' 'generate_parameters.R'
'get_forest.trollsim.R' 'get_log.trollsim.R' 'load_stack.R'
'load_sim.trollsim.R' 'print.trollsim.R' 'rcontroll-package.R'
'rcontroll.R' 'stack.R' 'update_parameters.trollsim.R'

VignetteBuilder knitr

Depends R (>= 3.6)

LinkingTo Rcpp, RcppGSL

Encoding UTF-8

NeedsCompilation yes

Author Sylvain Schmitt [aut, cre] (ORCID:
<https://orcid.org/0000-0001-7759-7106>),
Guillaume Salzet [aut] (ORCID: <https://orcid.org/0000-0003-4548-5673>),
Fabian Fischer [aut] (ORCID: <https://orcid.org/0000-0003-2325-9886>),
Isabelle Maréchaux [aut] (ORCID:
<https://orcid.org/0000-0002-5401-0197>),
Jérôme Chave [aut] (ORCID: <https://orcid.org/0000-0002-7766-1347>)

Repository CRAN

Date/Publication 2026-08-04 08:40:08 UTC

Contents

rcontroll-package 3
autogif 5
autoplot,trollsim-method 6
generate_climate 7
generate_lidar 11
generate_parameters 12
get_chm 16
get_forest 16
get_log 17
load_output 18
load_sim 19
load_stack 19
option.rcontroll 20
print.trollsim 20
stack 21
troll 23
TROLL.version 25
trollCpp 25
trollsim 26
trollsim-class 28
trollstack 29
trollstack-class 30

TROLLv3_climatedaytime12 30
TROLLv3_daytimevar 31
TROLLv3_input 32
TROLLv3_output 32
TROLLv3_pointcloud 33
TROLLv3_species 33
update_parameters 34

Index **35**

`rcontroll-package` `rcontroll`*: individual-based forest growth simulator TROLL*

Description

`TROLL` is coded in C++ and it typically simulates hundreds of thousands of individuals over hundreds of years. The `rcontroll` R package is a wrapper of `TROLL`. `rcontroll` includes functions that generate inputs for simulations and run simulations. Finally, it is possible to analyse the `TROLL` outputs through tables, figures, and maps taking advantage of other R visualisation packages. `rcontroll` also offers the possibility to generate a virtual LIDAR point cloud that corresponds to a snapshot of the simulated forest.

Construction and manipulation of input files

As stated above, three types of input data are needed for a typical `TROLL` simulation: (i) climate data, (ii) plant functional traits, (iii) global model parameters. Pre-simulation functions include global parameters definition (`generate_parameters` function) and climate data generation (`generate_climate` function). `rcontroll` also includes default data for species and climate inputs for a typical French Guiana rainforest site. The purpose of the `generate_climate` function with the help of the corresponding vignette is to create `TROLL` climate inputs from ERA5-Land (Muñoz-Sabater et al. 2021), a global climatic reanalysis dataset that is freely available. The ERA5-Land climate reanalysis is available at 9 km spatial resolution and hourly temporal resolution since 1950, and daily or monthly means are available and their uncertainties reported. Therefore, `rcontroll` users only need to input the species-specific trait data to run `TROLL` simulations, irrespective of the site. `TROLL` was originally developed for tropical and subtropical forests, so certain assumptions must be critically examined when applying it outside the tropics. The input files can be used to start a `TROLL` simulation run within the `rcontroll` environment (see below), or saved so that the `TROLL` simulation can be started as a command line tool.

Simulations

The default option is to run a `TROLL` simulation using the `troll` function of the rcontroll package, which currently calls version 3.1.7 of `TROLL` using the Rcpp package (Eddelbuettel & François 2011). The output is stored in a `trollsim` R class. For multiple runs, users can rely on the `stack` function, and the output is stored in the `trollstack` class. Both `trollsim` and `trollstack` values can be accessed using object attributes in the form of simple R objects (with `@` in R). They consist of eight simulation attributes: (1) name, (2) path to saved files, (3) parameters, (4) inputs, (5) log, (6) initial and final state, (7) ecosystem output metrics, and (8) species output metrics. The initial

and final states are represented by a table with the spatial position, size and other relevant traits of all trees at the start and end of the simulation. The ecosystem and species metrics are summaries of ecosystem processes and states, such as net primary production and aboveground biomass, and they are documented at species level and aggregated over the entire stand. Simulations can be saved using a user-defined path when run and later loaded as a simple simulation (`load_output` function) or a stack of simulations (`load_stack` function).

Simulated airborne lidar scanning option

`TROLL` also has the capacity of generating point clouds from virtual aerial lidar scannings of simulated forest scenes. Within each cubic metre voxel of the simulated stand, points are generated probabilistically, with the probability depending both on the amount of light reaching the particular voxel and the amount of leaf matter intercepting light within the voxel. Extinction and interception of light are based on the Beer-Lambert law, but an effective extinction factor is used to account for differences between the near-infrared and visible light. The definition of the lidar parameters (`generate_lidar` function) is optional but allows the user to add a virtual aerial lidar scan for a time step of the `TROLL` simulation. When this option is enabled, the cloud of points from simulated aerial lidar scans are stored as LAS using the R package `lidR` (Roussel et al., 2020) as a ninth attribute of the `trollsim` and `trollstack` objects.

Manipulation of simulation outputs

`rcontroll` includes functions to manipulate simulation outputs. Simulation outputs can be retrieved directly from the `trollsim` or `trollstack`objects and summarised or plotted in the R environment with the `print`, `summary` and `autoplot` functions. The `get_chm` function allows users to retrieve canopy height models from aerial lidar point clouds. In addition, a `rcontroll` function is available to visualise TROLL simulations as an animated figure (`autogif` function).

TROLL

version 3.1.6

Author(s)

Maintainer: Sylvain Schmitt <sylvain.m.schmitt@gmail.com> (ORCID)

Authors:

- Guillaume Salzet <guillaume.salzet@inrae.fr> (ORCID)
- Fabian Fischer <fabian.fischer@univ-tlse3.fr> (ORCID)
- Isabelle Maréchaux <isabelle.mj.marechaux@gmail.com> (ORCID)
- Jérôme Chave <jerome.chave@univ-tlse3.fr> (ORCID)

See Also

Useful links:

- https://github.com/sylvainschmitt/rcontroll
- https://sylvainschmitt.github.io/rcontroll/
- Report bugs at https://github.com/sylvainschmitt/rcontroll/issues

autogif *Create an animation from a TROLL simulation*

Description

`autogif()` uses `ggplot2` and `gganimate` to render an animation from a TROLL simulation. The animation can include a vertical cut in the forest structure along the X-axis highlighting either tree species (`variables = 'species'`), either tree height relative to their maximum height (`variables = 'height_ct'`), or tree carbon acquisition with net over growth primary productivity (`variables = 'npp_gpp'`). The animation can also include a top view of the canopy representing either canopy trees height (`variables = 'height'`) or total leaf area index per pixel (`variables = 'lai'`).

Usage

```
autogif(
  name = NULL,
  path = NULL,
  variables = c("species", "height_ct", "npp_gpp", "height", "lai"),
  global,
  species,
  climate,
  daily,
  forest = NULL,
  verbose = TRUE,
  overwrite = TRUE,
  thin = NULL
)
```

Arguments

`name`	char. Model name (if NULL timestamp).
`path`	char. Path to save the simulation outputs, the default is null corresponding to a simulation in memory without saved intermediary files (based on temporary files from option.rcontroll).
`variables`	char. Variables to build as a gif among 'species', 'height_ct', 'npp_gpp', 'height', or 'lai'.
`global`	df. Global parameters (e.g. TROLLv3_input or using `generate_parameters()`).
`species`	df. Species parameters (e.g. TROLLv3_species).
`climate`	df. Climate parameters (e.g. TROLLv3_climatedaytime12).
`daily`	df. Daily variation parameters (e.g. TROLLv3_daytimevar).
`forest`	df. TROLL with forest input, if null starts from an empty grid (default NULL) (e.g. using TROLLv3_output with `get_forest()`).
`verbose`	bool. Show TROLL outputs in the console.
`overwrite`	bool. Overwrite previous outputs.
`thin`	int. Vector of integers corresponding to the iterations to be kept to reduce output size, default is NULL and corresponds to no thinning.

Value

A list of gganimate objects corresponding to chosen outputs.

See Also

autoplot,trollsim-method

Examples

```
## Not run:
data("TROLLv3_species")
data("TROLLv3_climatedaytime12")
data("TROLLv3_daytimevar")
autogif(
  name = "test", global = generate_parameters(
    cols = 100, rows = 100,
    iterperyear = 12, nbiter = 12 * 100,
    extent_visual = 10
  ),
  species = TROLLv3_species,
  climate = TROLLv3_climatedaytime12,
  daily = TROLLv3_daytimevar,
  verbose = FALSE
)

## End(Not run)
```

---

autoplot,trollsim-method

Plot TROLL simulation or stack

Description

autoplot() is a method that takes advantage of ggplot2 to plot TROLL simulations. autoplot() can plot either temporal trajectories of whole ecosystem or species metrics (what = 'temporal'), the initial or final pattern observed in the forest community (what = 'spatial' or what = 'distribution'), or lidar outputs (what = 'lidar'). Metrics includes abundances of individuals above 1cm (N), above 10cm (N10), and above 30cm (N30), aboveground biomass (AGB), basal area of individuals above 1cm (BA), and above 10cm (BA10), gross primary production (GPP), net primary production (NPP), respiration of day (Rday), night (Rnight) and stem (Rstem), and litterfall.

Usage

```
## S4 method for signature 'trollsim'
autoplot(
  object,
  what = "temporal",
```

```
  variables = NULL,
  species = NULL,
  iter = NULL
)
```

Arguments

object	TROLL simulation or stack (see troll(), stack(), trollsim() and trollstack()).
what	char. What to plot: "temporal", "spatial" "distribution", or "lidar". "temporal" is for temporal trajectories of the whole ecosystem or defined species. "spatial" is for spatial patterns in the initial or final forest. "distribution" is for metrics distribution in the initial or final forest. "lidar" is for canopy height model plot.
variables	char. Which variable(s) to plot. Only one variable is accepted when plotting "spatial".
species	char. Which species to plot. NULL indicates the whole ecosystem level. "all" can be used to use all species.
iter	char. Which iteration(s) to plot, for temporal thinning or to specify which forest to plot. "initial" or "final" can be used. NULL is converted to "final".

Value

A ggplot2 object.

See Also

autogif(), summary,trollsim-method

Examples

```
data("TROLLv3_output")
autoplot(TROLLv3_output)
```

---

generate_climate *Generate climate dataset*

Description

TROLL forest simulator relies on climate tables with half-hourly variations of a typical day and monthly variations of a typical year which are recycled through simulation days and years. Initially, TROLL climate tables were computed from the Nouraflux dataset. Variations in quantities of interests (temperatures, ...) were averaged to the target resolution (half-hour for daily variation or month for monthly variation). The purpose of climate generation functions is to compute equivalent climate tables from the ERA5 land reanalysis dataset (Muñoz-Sabater et al. 2021). With these functions, rcontroll users only need inventories and associated functional traits to run TROLL simulations. See the corresponding vignette vignette("climate", package = "rcontroll") for further details.

Usage

```
generate_climate(
  x,
  y,
  tz,
  era5land_hour,
  era5land_month,
  daytime_start = 7,
  daytime_end = 19
)
```

Arguments

x	num. Longitude in UTM. Can be obtained from the location name with nominatimlite::geo_lite_sf()
y	num. Latitude in UTM. Can be obtained from the location name with nominatimlite::geo_lite_sf().
tz	num. Time zone. Can be obtained from the coordinates with lutz::tz_lookup_coords().
era5land_hour	str. Path to ERA5 land data monthly averaged reanalysis by hour of day in netCDF. See the corresponding vignette vignette("climate", package = "rcontroll") to download corresponding data from Copernicus in R.
era5land_month	str. Path to ERA5 land data monthly averaged reanalysis in netCDF. See the corresponding vignette vignette("climate", package = "rcontroll") to download corresponding data from Copernicus in R.
daytime_start	int. Daytime starting hour to compute nigh and day variables (default 7).
daytime_end	int. Daytime ending hour to compute nigh and day variables (default 19).

Details

The TROLL forest model simulates tree growth based on ecophysiological processes, with an external climate forcing. Input climatic conditions are provided in the form of climate tables with (i) half-hourly standardised variation of a typical day, and (ii) monthly average values of a typical year, which are currently recycled through simulation. Initially, TROLL climate tables were computed from the Nouraflux dataset (Poncy et al., 1998). The variation in quantities of interest (irradiance, temperature, vapour pressure, rainfall, and wind speed) were averaged to the target resolution (half-hour for daily variation or month for monthly variation).

The purpose of the climate generation function is to compute equivalent climate tables from a global climatic reanalysis dataset. With generate_climate, rcontroll users no longer need to format complex climate input fields, but can generate them from global and carefully documented climate distributions to run TROLL simulations. The selected input climate product for this version of rcontroll is ERA5-Land (Muñoz-Sabater et al. 2021). The ERA5-Land climate reanalysis has two main advantages over other climate reanalysis products: (1) the data are at a spatial resolution of 9km and have been available at hourly temporal resolution since 1950, and (2) daily or monthly averages are available and their uncertainties are reported.

Hypotheses:

The following assumptions are made in the generation of climate data:

1. The temperature at 2m and its derivatives (d2m) from ERA5-land corresponds to air temperature measurement used as an input in TROLL;

2. We can calculate the vapour pressure deficit using the Buck equation;
3. The extraction of standardised half-hourly values of an average day and of monthly average values of a year for the climate variables of interest is based on the decomposition of the raw time series into: (i) an overall trend over the study period, (ii) seasonal or daily variation across months or hours depending on the study level, and (iii) the remaining variation;
4. Half-hourly values are not available for ERA5-land data. Spline functions are used to interpolate hourly values for downscaling to half-hourly resolution.

Quantities of interest:

TROLL *variables:*
TROLL climate tables summarise temporal variation of quantities of interest. These variations are called **seasonal pattern** and are computed from time series under the additive assumption :
$X(t) = Trend_X(t) + Seasonal_{x,Period}(t \mod p[modPeriod]) + Irregular(t)$
With :

- $Trend_X(t)$ a moving average covering one period;
- $Seasonal_{x,Period}(t \mod p[modPeriod])$ the seasonal pattern contribution at t time modulo the period;
- $Irregular(t)$ the remainder part.

The de-seasonally average of X is defined as :
$mean(X) = mean(Trend_X(t))$
These values of seasonal pattern and de-seasonally average are used to compute the climate table TROLLv3_climatedaytime12 and TROLLv3_daytimevar.

ERA5-Land variables:
There is a restricted set of variables needed to generate the TROLL climate files:

- t2m: Temperature at 2m in K
- d2m: Dew point temperature at 2m in K
- tp: Cumulative rainfall in m
- sp: Atmospheric pressure at the surface in Pa
- ssrd: Cumulative Net solar irradiation in J/m2
- u10: Zonal wind component at 10m in m/s
- v10: Meridional wind component at 10m in m/s

Calculation of variables:

The transition from ERA-Land data to TROLL data requires several transformations. The TROLL climate files correspond to seasonal components, either daily from 7am to 7pm, or monthly. The extraction of these seasonal components is possible by analysing the time series of the data. An additive decomposition of the variables allows one to obtain the pattern of interest at the original resolution (hourly or monthly). Interpolation of the pattern using spline functions of the periodic type, ensuring the boundary conditions (i.e. value at 0 am is the same as 12 pm), except for the ssrd which is not a continuous periodic function and which requires natural type spline interpolation. An evaluation of the quality of the pattern extraction is possible by measuring the standard deviation of the error to the original time series. This error can be calculated for each unit of the pattern (for each hour for example).

Wind speed:
The wind speed is the norm of the vector generated by the u10 and v10 components of the wind. We can therefore deduce that the wind speed corresponds to:
$WindSpeed = \sqrt{u10^2 + v10^2}$

Vapour pressure deficit:
The calculation of the vapour pressure deficit can be done according to three variables (`t2m`, `d2m` and `sp`) using the formula of (Buck 1981):
$VPD = e_{sat}(d2m, sp) - e_{obst}(2m, sp)$
$e_*(t2m|d2m, sp) = 611.21xf(t2m|d2m, sp)x(1)$
$(1) = 18.678 - (t2m|d2m - 273.15)/234.5x(t2m|d2m - 273.15)/(240.97 + t2m|d2m - 273.15)$
$f(t2m|d2m, sp) = 1.0007 + 10^{-7}xspx0.032 + 5.9x10^{-6}x(t2m|d2m - 273.15)^2$

Instantaneous irradiance:
The measurement of irradiance in the ERA5 data corresponds to the accumulation either at hourly or daily intervals. The instantaneous measurement can be obtained by calculating the variation of this accumulation:
$\Delta ssrd(t) = ssrd(t) - ssrd(t-1)$

Conclusion:

In conclusion, despite some discrepancies between climate input generated from local meteorological station data and the `generate_climate` function that should be investigated further, the `generate_climate` function allows `rcontroll` users to easily obtain relevant climate data for their study. The discrepancies may be partly due to the unconventional situation of the Nouraflux station, which should not be considered as the true climate.

Warning: As `TROLL` is under constant development, some of the variables presented here may not be used in the current version (v 3.1.7) and may be left over from previous versions or may be intended for future versions. Furthermore, this supplementary information corresponds to the version 3.1.7 of `TROLL` and the climate variables used by the model may change as new versions of `TROLL` are released. We plan to include future major developments of `TROLL` in `rcontroll` to keep the advances of the model accessible to the community, including the development of the `generate_climate` function. We thus invite the reader to check the corresponding updated vignette on GitHub (https://sylvainschmitt.github.io/rcontroll/articles/climate.html) according to the version of `TROLL` they are using in `rcontroll` (check with `TROLL.version()`).

References:

Buck, Arden L. (1981) New equations for computing vapor pressure and enhancement factor. Journal of Applied Meteorology and Climatology, 1981, vol. 20, no 12, p. 1527-1532.

Muñoz-Sabater, J., Dutra, E., Agustí-Panareda, A., Albergel, C., Arduini, G., Balsamo, G., … Thépaut, J. N. (2021). ERA5-Land: A state-of-the-art global reanalysis dataset for land applications. Earth System Science Data, 13(9), 4349–4383. https://doi.org/10.5194/essd-13-4349-2021

Poncy, O., Riéra, B., Larpin, D., Belbenoit, P., Jullien, M., Hoff, M., & Charles-Dominique, P. (1998). The permanent field research station "Les Nouragues" in the tropical rainforest of French Guiana: current projects and preliminary results on tree diversity, structure, and dynamics. Forest Biodiversity in North, Central and South America, and the Caribbean: Research and Monitoring., 385–410.

Value

A list with two `data.frame()`: daytimevar and climatedaytime12.

`generate_lidar` *Generate lidar parameters*

Description

`generate_lidar` generate the lidar parameters used in `TROLL` lidar simulation. All parameters have a default value from literature.

Usage

```
generate_lidar(
  mean_beam_pc = 10,
  sd_beam_pc = 5,
  klaser_pc = 0.63,
  transmittance_laser = 0.4,
  iter_pointcloud_generation = NULL
)
```

Arguments

`mean_beam_pc`	num. Mean pulse density (pulses per m2).
`sd_beam_pc`	num. Standard deviation of pulse density (per m2).
`klaser_pc`	num. laser attenuation factor.
`transmittance_laser`	num. Percentage of pulses that continue through the canopy after a hit.
`iter_pointcloud_generation`	num. Number of iteration for point cloud generation.

Value

A [data.frame)] of lidar simulation parameters.

[data.frame)]: R:data.frame)

See Also

`troll()`, `stack()`

Examples

```
generate_lidar(iter_pointcloud_generation = 3600)
```

`generate_parameters` *Generate global parameters*

Description

`generate_parameters()` generate the global parameters used in the `TROLL` simulation. All parameters have a default value used in French Guiana simulations.

Usage

```
generate_parameters(
  cols = 200,
  rows = 200,
  HEIGHT = 70,
  length_dcell = 25,
  nbiter,
  iterperyear = 12,
  NV = 1,
  NH = 1,
  nbout = 4,
  nbspp = 45,
  SWtoPPFD = 2.27,
  p_nonvert = 0.05,
  klight = 0.63,
  phi = 0.093,
  absorptance_leaves = 0.9,
  theta = 0.7,
  g1 = 3.77,
  vC = 0.021,
  DBH0 = 0.005,
  H0 = 0.95,
  CR_min = 0.3,
  CR_a = 2.13,
  CR_b = 0.63,
  CD_a = 0,
  CD_b = 0.2,
  CD0 = 0.3,
  shape_crown = 0.72,
  dens = 1,
  fallocwood = 0.35,
  falloccanopy = 0.25,
  Cseedrain = 50000,
  nbs0 = 10,
  sigma_height = 0,
  sigma_CR = 0,
  sigma_CD = 0,
  sigma_P = 0,
```

```
  sigma_N = 0,
  sigma_LMA = 0,
  sigma_wsg = 0,
  sigma_dbhmax = 0,
  corr_CR_height = 0,
  corr_N_P = 0,
  corr_N_LMA = 0,
  corr_P_LMA = 0,
  leafdem_resolution = 30,
  p_tfsecondary = 1,
  hurt_decay = 0,
  crown_gap_fraction = 0.15,
  m = 0.013,
  m1 = 0.013,
  Cair = 400,
  LL_parameterization = 1,
  LA_regulation = 2,
  sapwood = 1,
  seedsadditional = 0,
  NONRANDOM = 1,
  GPPcrown = 0,
  BASICTREEFALL = 1,
  SEEDTRADEOFF = 0,
  CROWN_MM = 0,
  OUTPUT_extended = 1,
  extent_visual = 0
)
```

Arguments

cols	num. Number of columns.
rows	num. Number of rows.
HEIGHT	num. Vertical extent of simulation.
length_dcell	num. Linear size of a dcell.
nbiter	num. Total number of timesteps.
iterperyear	num. Number of iterations per year.
NV	num. Vertical number of cells (per m).
NH	num. Horizontal number of cells (per m).
nbout	num. Number of outputs.
nbspp	num. Number of species
SWtoPPFD	num. Convert shortwave irradiance to PAR photons.
p_nonvert	num. Light incidence parameter (difference through turbid medium).
klight	num. Light attenuation in the canopy following a Beer-Lambert law.
phi	num. Quantum yield (in micromol C/micromol photon).

absorptance_leaves
: num. Absorptance of individual leaves.

theta
: num. Parameter of the Farquhar model.

g1
: num. Parameter g1 of Medlyn et al stomatal conductance model.

vC
: num. Variance of the flexion moment.

DBH0
: num. Initial diameter at breast height (m).

H0
: num. Initial height (m).

CR_min
: num. Minimum crown radius (in m).

CR_a
: num. Crown radius log intercept or Michaelis Menten initial growth.

CR_b
: num. Crown radius log slope or Michaelis Menten asymptotic CR.

CD_a
: num. Crown depth intercept (absolute value).

CD_b
: num. Crown depth slope (as fraction of tree height).

CD0
: num. Initial crown depth (in m).

shape_crown
: num. Crown shape parameter.

dens
: num. Initial leaf density (m^2/m^2).

fallocwood
: num. Fraction of biomass allocated to above ground wood (branch turnover+stem).

falloccanopy
: num. Fraction of biomass allocated to canopy (leaves + reproductive organs + twigs).

Cseedrain
: num. Constant used to scale total seed rain per hectare across species.

nbs0
: num. Number of seeds produced and dispersed by each mature tree when SEED-TRADEOFF is not defined.

sigma_height
: num. Intraspecific variation in tree height (lognormal).

sigma_CR
: num. Intraspecific variation in crown radius (lognormal).

sigma_CD
: num. Intraspecific variation in crown depth (lognormal).

sigma_P
: num. Intraspecific variation in leaf phosphorus (lognormal).

sigma_N
: num. Intraspecific variation in leaf nitrogen (lognormal).

sigma_LMA
: num. Intraspecific variation in leaf mass per area (lognormal).

sigma_wsg
: num. Intraspecific variation in wood specific gravity.

sigma_dbhmax
: num. Intraspecific variation in maximum diameter.

corr_CR_height
: num. Correlation coefficient between crown radius and tree height.

corr_N_P
: num. Correlation coefficient between leaf nitrogen and leaf phosphorus.

corr_N_LMA
: num. Correlation coefficient between leaf nitrogen and leaf mass per area

corr_P_LMA
: num. Correlation coefficient between leaf phosphorus and leaf mass per area

leafdem_resolution
: num. Resolution of leaf demography model.

p_tfsecondary
: num. Probability of secondary treefall.

hurt_decay
: num. Parameter determining how tree damages are repaired.

crown_gap_fraction
: num. Fraction of gaps in the crown.

`m` num. Minimal death rate.

`m1` num. Slope of death rate m1.

`Cair` num. Atmospheric CO2 concentration in micromol/mol.

`LL_parameterization`
num. Leaf lifespan parameterizations: Reich empirical, Kikuzawa model, and Kikuzawa model with leaf plasticity (0,1,2).

`LA_regulation` num. Dynamic LA regulation: off, 1.0, 0.75, or 0.5 (0,1,2,3).

`sapwood` num. Sapwood parameterizations: constant thickness (0.04), Fyllas percentage, Fyllas lower limit (0,1,2).

`seedsadditional`
num. Excess biomass into seeds after maturation (0,1).

`NONRANDOM` num. If _NONRANDOM >= 1, the seeds for the random number generators will be set using fixed seed in R, default for bug fixing (0,1).

`GPPcrown` num. This defines an option to compute only GPP from the topmost value of PPFD and GPP, instead of looping within the crown (0,1).

`BASICTREEFALL` num. If defined: treefall is a source of tree death (0,1).

`SEEDTRADEOFF` num. if defined: the number of seeds produced is determined by NPP allocated to reproduction and seed mass, otherwise the number of seeds is fixed (0,1).

`CROWN_MM` num. Michaelis Menten allometry for crowns instead of power law, parameters have to be changed in other input sheets accordingly (0,1).

`OUTPUT_extended`
num. extended set of ouput files (0,1).

`extent_visual` num. extent for visualization output. Unactivated when equal 0.

Value

A data frame of global parameters.

See Also

`troll()`, `stack()`, `update_parameters()`

Examples

```
generate_parameters(nbiter = 12)
```

get_chm *Extract canopy height model*

Description

get_chm() extract the canopy height model from TROLL outputs with lidar option.

Usage

```
get_chm(sim, method = "smoothed", ...)

## S4 method for signature 'trollsim'
get_chm(sim, method = "smoothed", ...)
```

Arguments

sim	trollsim.
method	char. method to extract the canopy height model from the point cloud in las, either 'filled' (replacing NA by 0) or 'smoothed' (local means, default value).
...	unused argument.

Value

data.frame()

See Also

trollsim(), troll(), stack()

get_forest *Extract forest inventory*

Description

get_forest() extract the forest inventory from TROLL outputs.

Usage

```
get_forest(sim, ...)

## S4 method for signature 'trollsim'
get_forest(sim, ...)
```

Arguments

sim	trollsim or trollstack.
...	unused argument.

Value

data.frame()

See Also

trollsim(), trollstack(), troll(), stack()

Examples

```
data("TROLLv3_output")
head(get_forest(TROLLv3_output))
```

---

get_log *Extract simulation log*

Description

get_forest() extract the simulation log TROLL outputs.

Usage

```
get_log(sim, ...)

## S4 method for signature 'trollsim'
get_log(sim, ...)
```

Arguments

sim	trollsim or trollstack.
...	unused argument.

Value

the log in the console

See Also

trollsim(), trollstack(), troll(), stack()

Examples

```
data("TROLLv3_output")
get_log(TROLLv3_output)
```

`load_output` *Load outputs from simulation*

Description

`load_output` load outputs from `TROLL` simulation files using `TROLL` simulation `name` and `path`.

Usage

```
load_output(name, path, thin = NULL)
```

Arguments

`name`	char. Name given to the model output.
`path`	char. Path where the model is saved.
`thin`	int. Vector of integers corresponding to the iterations to be kept to reduce output size, default is NULL and corresponds to no thinning.

Value

An S4 `trollsim()` class object.

See Also

`trollsim()`, `trollstack()`, `load_sim()`, `load_stack()`

Examples

```
## Not run:
load_output("test", "./")

## End(Not run)
```

load_sim *Load outputs from simulation or stack of simulations*

Description

load_sim is a method of trollsim() or trollstack() with wirtten files not in R memory to load them into R memory taking advantage of load_output() and load_stack().

Usage

```
load_sim(sim, ...)

## S4 method for signature 'trollsim'
load_sim(sim, ...)
```

Arguments

sim	trollsim or trollstack.
...	unused argument.

Value

An S4 trollsim() or trollstack() class object.

See Also

trollsim(), trollstack(), load_sim(), load_stack()

load_stack *Load outputs from a stack of simulations*

Description

load_stack load outputs from a stack of TROLL simulation files using TROLL stack of simulation name and path.

Usage

```
load_stack(name, path, thin = NULL)
```

Arguments

name	char. Name given to the stack output.
path	char. Path where the stack is saved.
thin	int. Vector of integers corresponding to the iterations to be kept to reduce output size, default is NULL and corresponds to no thinning.

Value

An S4 `trollstack()` class object.

See Also

`trollsim()`, `trollstack()`, `load_sim()`, `load_stack()`

Examples

```
## Not run:
load_stack("test", "./")

## End(Not run)
```

`option.rcontroll` *Options*

Description

`rcontroll` package global options including temporary files location and `TROLL` version.

Details

`rcontroll.tmp` char. Path to temporary files folder used by `troll()` and `stack()`.

`rcontroll.troll` char. `TROLL` version number accessible with `TROLL.version()`.

`print.trollsim` *Print a summary*

Description

`print()` prints a summary of TROLL simulation or stack of simulations outputs.

Usage

```
## S4 method for signature 'trollsim'
print(x, ...)

## S4 method for signature 'trollsim'
show(object)

## S4 method for signature 'trollsim'
summary(object, ...)
```

Arguments

x	trollsim or trollstack.
...	unused argument.
object	trollsim or trollstack.

Value

Print or show in console.

See Also

troll(), stack(), trollsim(), trollstack()

Examples

```
data("TROLLv3_output")
print(TROLLv3_output)
```

---

stack *Run a stack of* TROLL *simulations*

Description

stack() run a stack of TROLL simulation. The minimal set of input files required for a TROLL run include (i) climate data for the focal location (climate and daily), (ii) functional traits for the list of species at the focal location (species), and (iii) global parameters (global), i.e. parameters that do not depend on species identity.

Usage

```
stack(
  name = NULL,
  simulations,
  path = NULL,
  global,
  species,
  climate,
  daily,
  lidar = NULL,
  forest = NULL,
  load = TRUE,
  cores = NULL,
  verbose = TRUE,
  overwrite = TRUE,
  thin = NULL
)
```

Arguments

name	char. Stack name (if NULL the timestamp will be used).
simulations	char. Simulation names (corrsponding to simulation indexes in orresponding tables, see example below).
path	char. Path to save the stack of simulation outputs (parent folder), the default is null corresponding to a simulation in memory without saved intermediary files (based on temporary files from option.rcontroll).
global	df. Global parameters (e.g. TROLLv3_input or using generate_parameters()).
species	df. Species parameters (e.g. TROLLv3_species).
climate	df. Climate parameters (e.g. TROLLv3_climatedaytime12).
daily	df. Daily variation parameters (e.g. TROLLv3_daytimevar).
lidar	df. Lidar simulation parameters (e.g. using generate_lidar()), if null not computed (default NULL).
forest	df. TROLL with forest input, if null starts from an empty grid (default NULL) (e.g. using TROLLv3_output with get_forest()).
load	bool. TROLL outputs are loaded in R memory, if not only the path and name of the stack of simulations is kept in the resulting trollstack() object but the content can be accessed later using the load_sim() method.
cores	int. Number of cores for parallelization, if NULL available cores - 1 (default NULL). You can use parallel::detectCores() to know available cores on your machine.
verbose	bool. Show TROLL log in the console.
overwrite	bool. Overwrite previous outputs folder and files.
thin	int. Vector of integers corresponding to the iterations to be kept to reduce output size, default is NULL and corresponds to no thinning.

Value

A trollstack() object.

See Also

troll()

Examples

```
## Not run:
data("TROLLv3_species")
data("TROLLv3_climatedaytime12")
data("TROLLv3_daytimevar")
data("TROLLv3_output")
TROLLv3_input_stack <- generate_parameters(
  cols = 100, rows = 100,
  iterperyear = 12, nbiter = 12 * 1
) %>%
```

```
  mutate(simulation = list(c("seed50000", "seed500"))) %>%
  unnest(simulation)
TROLLv3_input_stack[62, 2] <- 500 # Cseedrain
stack(
  name = "teststack",
  simulations = c("seed50000", "seed500"),
  global = TROLLv3_input_stack,
  species = TROLLv3_species,
  climate = TROLLv3_climatedaytime12,
  daily = TROLLv3_daytimevar,
  load = TRUE,
  cores = 2,
  verbose = FALSE,
  thin = c(1, 5, 10)
)

## End(Not run)
```

`troll` *Run a* `TROLL` *simulation*

Description

`troll()` run a `TROLL` simulation. The minimal set of input files required for a `TROLL` run include (i) climate data for the focal location (`climate` and `daily`), (ii) functional traits for the list of species at the focal location (`species`), and (iii) global parameters (`global`), i.e. parameters that do not depend on species identity.

Usage

```
troll(
  name = NULL,
  path = NULL,
  global,
  species,
  climate,
  daily,
  lidar = NULL,
  forest = NULL,
  load = TRUE,
  verbose = TRUE,
  overwrite = TRUE,
  thin = NULL
)
```

Arguments

name	char. Model name (if NULL the timestamp will be used).
path	char. Path to save the simulation outputs, the default is null corresponding to a simulation in memory without saved intermediary files (based on temporary files from option.rcontroll).
global	df. Global parameters (e.g. TROLLv3_input or using generate_parameters()).
species	df. Species parameters (e.g. TROLLv3_species).
climate	df. Climate parameters (e.g. TROLLv3_climatedaytime12).
daily	df. Daily variation parameters (e.g. TROLLv3_daytimevar).
lidar	df. Lidar simulation parameters (e.g. using generate_lidar()), if null not computed (default NULL).
forest	df. TROLL with forest input, if null starts from an empty grid (default NULL) (e.g. using TROLLv3_output with get_forest()).
load	bool. TROLL outputs are loaded in R memory, if not only the path and name of the simulations is kept in the resulting trollsim() object but the content can be accessed later using the load_sim() method.
verbose	bool. Show TROLL log in the console.
overwrite	bool. Overwrite previous outputs folder and files.
thin	int. Vector of integers corresponding to the iterations to be kept to reduce output size, default is NULL and corresponds to no thinning.

Value

A trollsim() object.

See Also

stack()

Examples

```
data("TROLLv3_species")
data("TROLLv3_climatedaytime12")
data("TROLLv3_daytimevar")
troll(
  name = "test",
  global = generate_parameters(
    cols = 100, rows = 100,
    iterperyear = 12, nbiter = 12 * 1
  ),
  species = TROLLv3_species,
  climate = TROLLv3_climatedaytime12,
  daily = TROLLv3_daytimevar
)
```

TROLL.version — TROLL *version*

Description

TROLL.version() prints TROLL version.

Usage

```
TROLL.version()
```

Value

TROLL version in console.

See Also

option.rcontroll

Examples

```
TROLL.version()
```

trollCpp — *TROLL simulator*

Description

Wrapper of the TROLL C++ simulator with Rcpp.

Usage

```
trollCpp(
  global_file,
  climate_file,
  species_file,
  day_file,
  lidar_file,
  forest_file,
  output_file
)
```

Arguments

global_file	char. Path to the global parameters file.
climate_file	char. Path to the climate file.
species_file	char. Path to the species file.
day_file	char. Path to the daytime file.
lidar_file	char. Path to the lidar file.
forest_file	char. Path to the forest file.
output_file	char. Path to the output folder.

Value

Void with outputs files written in the defined folder.

Examples

```
## Not run:
trollCpp(global_file = "test/test_input_global.txt",
         climate_file = "test/test_input_climate.txt",
         species_file = "test/test_input_species.txt",
         day_file = "test/test_input_daily.txt",
         lidar_file = "",
         forest_file = "",
         output_file = "test")

## End(Not run)
```

---

trollsim *A* TROLL *simulations*

Description

trollsim() is an S4 class to represent a TROLL simulation. trollsim values can be accessed using object attributes in the form of simple R objects (with @). They consist of eight simulation attributes: (1) name, (2) path to saved files, (3) parameters, (4) inputs, (5) log, (6) initial and final state, (7) ecosystem output metrics, and (8) species output metrics. The initial and final states are represented by a table with the spatial position, size and other relevant traits of all trees at the start and end of the simulation. The ecosystem and species metrics are summaries of ecosystem processes and states, such as net primary production and aboveground biomass, and they are documented at species level and aggregated over the entire stand.

Usage

```
trollsim(
  name = character(),
  path = character(),
  mem = logical(),
  parameters = numeric(),
  inputs = list(),
  log = character(),
  forest = data.frame(),
  ecosystem = data.frame(),
  species = data.frame(),
  las = list()
)
```

Arguments

name	char. Simulation name.
path	char. File path to the stack of simulation (parent folder).
mem	bool. Is the simulation in memory, see load_sim().
parameters	numeric. Parameters of the simulation (general inputs).
inputs	list. Simulation inputs (species, climate, daily, forest, lidar, see troll()).
log	chr. Simulation log, see get_log().
forest	df. Simulation initial and final forest, see get_forest().
ecosystem	df. Ecosystem metrics.
species	df. Species metrics (with OUTPUT_extended option, see generate_parameters()).
las	list. List with simulated point cloud in LAS from lidar parameters (with lidar option, see generate_lidar()). The LAS format correspond to lidR::LAS() package, a suggest dependency to be installed beforehand.

Value

An empty S4 trollsim() class object.

See Also

troll(), load_output(), trollstack()

`trollsim-class` *A* TROLL *simulations*

Description

`trollsim()` is an S4 class to represent a TROLL simulation. `trollsim` values can be accessed using object attributes in the form of simple R objects (with `@`). They consist of eight simulation attributes: (1) name, (2) path to saved files, (3) parameters, (4) inputs, (5) log, (6) initial and final state, (7) ecosystem output metrics, and (8) species output metrics. The initial and final states are represented by a table with the spatial position, size and other relevant traits of all trees at the start and end of the simulation. The ecosystem and species metrics are summaries of ecosystem processes and states, such as net primary production and aboveground biomass, and they are documented at species level and aggregated over the entire stand.

Value

An empty S4 `trollsim()` class object.

Slots

`name` char. Simulation name.

`path` char. File path to the simulation.

`mem` bool. Is the simulation in memory, see `load_sim()`.

`parameters` numeric. Parameters of the simulation (general inputs).

`inputs` list. Simulation inputs (species, climate, daily, forest, lidar, see `stack()`).

`log` chr. Simulation log, see `get_log()`.

`forest` df. Simulation initial and final forest, see `get_forest()`.

`ecosystem` df. Ecosystem metrics.

`species` df. Species metrics (with OUTPUT_extended option, see `generate_parameters()`).

`las` list. List with simulated point cloud in LAS from lidar parameters (with lidar option, see `generate_lidar()`). The LAS format correspond to lidR::LAS() package, a suggest dependency to be installed beforehand.

See Also

`troll()`, `load_output()`, `trollstack()`

trollstack *A stack of* TROLL *simulations*

Description

trollstack() is an S4 class to represent a stack of TROLL simulation. trollstack values can be accessed using object attributes in the form of simple R objects (with @). They consist of eight simulation attributes: (1) name, (2) path to saved files, (3) parameters, (4) inputs, (5) log, (6) initial and final state, (7) ecosystem output metrics, and (8) species output metrics. The initial and final states are represented by a table with the spatial position, size and other relevant traits of all trees at the start and end of the simulation. The ecosystem and species metrics are summaries of ecosystem processes and states, such as net primary production and aboveground biomass, and they are documented at species level and aggregated over the entire stand.

Usage

```
trollstack(
  name = character(),
  path = character(),
  mem = logical(),
  parameters = numeric(),
  inputs = list(),
  log = character(),
  forest = data.frame(),
  ecosystem = data.frame(),
  species = data.frame(),
  las = list()
)
```

Arguments

name	char. Simulation name.
path	char. File path to the stack of simulation (parent folder).
mem	bool. Is the simulation in memory, see load_sim().
parameters	numeric. Parameters of the simulation (general inputs).
inputs	list. Simulation inputs (species, climate, daily, forest, lidar, see stack()).
log	chr. Simulation log, see get_log().
forest	df. Simulation initial and final forest, see get_forest().
ecosystem	df. Ecosystem metrics.
species	df. Species metrics (with OUTPUT_extended option, see generate_parameters()).
las	list. List with simulated point cloud in LAS from lidar parameters (with lidar option, see generate_lidar()). The LAS format correspond to lidR::LAS() package, a suggest dependency to be installed beforehand.

Value

An empty S4 `trollstack()` class object.

See Also

`stack()`, `load_stack()`, `trollsim()`

---

trollstack-class *A stack of* TROLL *simulations*

Description

`trollstack()` is an S4 class to represent a stack of TROLL simulation. `trollstack` values can be accessed using object attributes in the form of simple R objects (with `@`). They consist of eight simulation attributes: (1) name, (2) path to saved files, (3) parameters, (4) inputs, (5) log, (6) initial and final state, (7) ecosystem output metrics, and (8) species output metrics. The initial and final states are represented by a table with the spatial position, size and other relevant traits of all trees at the start and end of the simulation. The ecosystem and species metrics are summaries of ecosystem processes and states, such as net primary production and aboveground biomass, and they are documented at species level and aggregated over the entire stand.

TROLLv3_climatedaytime12

TROLL *climate parameters over months*

Description

Climate parameters used by TROLL model over months.

Usage

```
TROLLv3_climatedaytime12
```

Format

A data frame with 12 rows and 12 variables:

Temperature monthly average of temperature (degree C)

DaytimeMeanTemperature the monthly average of daytime temperature (degree C, 7am-7pm)

NightTemperature the monthly average of temperature at night (degree C, 8pm-6am)

Rainfall monthly average of cumulative rainfall (cm)

WindSpeed monthly average of wind speed (m/s)

DaytimeMeanIrradiance monthly average of cumulative solar irradiance averaged over one day (W/m2, 7am-7pm)

MeanIrradiance monthly average of cumulative solar irradiance over 24 hours (W/m2)

SaturatedVapourPressure monthly average of saturation vapour pressure (hPa)

VapourPressure monthly average of vapour pressur (hPa)

VaporPressureDeficit monthly average of vapour pressure deficit (VPD, hPa)

DayTimeVapourPressureDeficitVPDbasic monthly average of daytime vapour pressure deficit (7am-7pm) according to basic formula (hPa)

DaytimeMeanVapourPressureDeficit monthly average of daytime vapour pressure deficit (7am-7pm) according to advanced formula (hPa)

See Also

generate_climate(), TROLLv3_daytimevar

TROLLv3_daytimevar TROLL *daytime variation parameters*

Description

Daytime variation parameters used by TROLLs models.

Usage

```
TROLLv3_daytimevar
```

Format

A data frame with 24 rows and 5 variables:

starttime starting time

endtime ending time

vardaytime_light daily variation in irradiance relative to the mean value of the day

vardaytime_vpd daily variation in vapour pressure deficit relative to the mean value of the day

vardaytime_T daily variation in temperature relative to the mean value of the day

See Also

generate_climate(), TROLLv3_climatedaytime12

TROLLv3_input — TROLL *global parameters*

Description

Global parameters definition used by TROLL model.

Usage

```
TROLLv3_input
```

Format

A data frame with 61 rows and 3 variables:

param global parameter

value value of the parameter

description description of the parameter

See Also

generate_parameters()

TROLLv3_output — TROLL *output*

Description

TROLL outputs from a 100-year simulation on a 100x100 grid with the other default parameters and using TROLLv3_species, TROLLv3_climatedaytime12, and TROLLv3_daytimevar for use in tests and examples. Ecosystem level output has been thinned and species output has been removed to save disk space.

Usage

```
TROLLv3_output
```

Format

A trollsim() object.

See Also

TROLLv3_species(), TROLLv3_climatedaytime12(), TROLLv3_daytimevar(), troll()

TROLLv3_pointcloud TROLL *lidar parameters*

Description

Lidar parameters definition used by TROLL for lidar simulations.

Usage

```
TROLLv3_pointcloud
```

Format

A data frame with 5 rows and 3 variables:

param lidar parameter

value value of the parameter

description description of the parameter

See Also

generate_lidar()

TROLLv3_species TROLL *species parameters*

Description

Functional traits used by TROLL model for 45 species in French Guiana.

Usage

```
TROLLv3_species
```

Format

A data frame with 45 rows and 12 variables:

s_name Species name genus_species

s_LMA leaf mass per area

s_Nmass leaf nitrogen mass

s_Pmass leaf phosphorus mass

s_wsg wood specific gravity

s_dbhmax maximum diameter

s_hmax maximum height

s_ah height-diameter allometry coefficient

s_regionalfreq regional frequency

s_tlp Turgor loss point

s_drymass leaf dry mass

s_seedmass seed mass

See Also

troll(), stack()

---

update_parameters *Update global parameters*

Description

update_parameters() update the global parameters used in the TROLL simulation from a TROLL outputs for a next simulation. All parameters have a default value used in French Guiana simulations.

Usage

```
update_parameters(sim, ...)

## S4 method for signature 'trollsim'
update_parameters(sim, ...)
```

Arguments

sim	trollsim.
...	parameters to update and their values (see generate_parameters() for a complete list).

Value

a data.frame()

See Also

troll(), stack(), generate_parameters()

Examples

```
data("TROLLv3_output")
head(update_parameters(TROLLv3_output, iters = 10))
```

Index

∗ **datasets**
TROLLv3_climatedaytime12, 30
TROLLv3_daytimevar, 31
TROLLv3_input, 32
TROLLv3_output, 32
TROLLv3_pointcloud, 33
TROLLv3_species, 33

autogif, 5
autogif(), *7*
autoplot,trollsim-method, *6*, 6

data.frame(), *10*, *16, 17*, *34*

generate_climate, 7
generate_climate(), *31*
generate_lidar, 11
generate_lidar(), *22*, *24*, *27–29*, *33*
generate_parameters, 12
generate_parameters(), *5*, *22*, *24*, *27–29*, *32*, *34*
get_chm, 16
get_chm,trollsim-method *(*get_chm*)*, 16
get_forest, 16
get_forest(), *5*, *22*, *24*, *27–29*
get_forest,trollsim-method *(*get_forest*)*, 16
get_log, 17
get_log(), *27–29*
get_log,trollsim-method *(*get_log*)*, 17

load_output, 18
load_output(), *19*, *27, 28*
load_sim, 19
load_sim(), *18–20*, *22*, *24*, *27–29*
load_sim,trollsim-method *(*load_sim*)*, 19
load_stack, 19
load_stack(), *18–20*, *30*
lutz::tz_lookup_coords(), *8*

nominatimlite::geo_lite_sf(), *8*

option.rcontroll, *5*, 20, *22*, *24, 25*

parallel::detectCores(), *22*
print,trollsim-method *(*print.trollsim*)*, 20
print.trollsim, 20

rcontroll *(*rcontroll-package*)*, 3
rcontroll-package, 3

show,trollsim-method *(*print.trollsim*)*, 20
stack, 21
stack(), *7*, *11*, *15–17*, *20, 21*, *24*, *28–30*, *34*
summary,trollsim-method, *7*
summary,trollsim-method *(*print.trollsim*)*, 20

troll, 23
troll(), *7*, *11*, *15–17*, *20–22*, *27, 28*, *32*, *34*
TROLL.version, 25
TROLL.version(), *10*, *20*
trollCpp, 25
trollsim, 26
trollsim(), *7*, *16–21*, *24*, *27, 28*, *30*, *32*
trollsim-class, 28
trollstack, 29
trollstack(), *7*, *17–22*, *27, 28*, *30*
trollstack-class, 30
TROLLv3_climatedaytime12, *5*, *9*, *22*, *24*, 30, *31*
TROLLv3_climatedaytime12(), *32*
TROLLv3_daytimevar, *5*, *9*, *22*, *24*, *31*, 31
TROLLv3_daytimevar(), *32*
TROLLv3_input, *5*, *22*, *24*, 32
TROLLv3_output, *5*, *22*, *24*, 32
TROLLv3_pointcloud, 33
TROLLv3_species, *5*, *22*, *24*, 33
TROLLv3_species(), *32*

update_parameters, 34

update_parameters(), *15*
update_parameters,trollsim-method
(update_parameters), 34