

Package ‘GenomicTools.fileHandler’

March 5, 2020

Type Package

Title File Handlers for Genomic Data Analysis

Version 0.1.5.9

Date 2020-03-05

Author Daniel Fischer

Maintainer Daniel Fischer <daniel.fischer@luke.fi>

Description

A collection of I/O tools for handling the most commonly used genomic datafiles, like fasta/-q, bed, gff, gtf, ped/map and vcf.

Depends R (>= 3.3), data.table (>= 1.9.6)

Imports snpStats

Suggests knitr, rmarkdown

VignetteBuilder knitr

License GPL (>= 2)

Encoding UTF-8

LazyLoad yes

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2020-03-05 08:00:07 UTC

R topics documented:

GenomicTools.fileHandler-package	2
example.bed	3
example.fasta	3
example.fastq	4
example.gff	4
example.gtf	5
example.ped	5

example.vcf	6
example2.gtf.gz	6
exportBed	7
exportFA	8
importBed	9
importBlastTab	10
importFA	10
importFeatureCounts	11
importFQ	12
importGFF	13
importGFF3	14
importGTF	15
importPED	16
importSTARLog	17
importVCF	18
importXML	19
plotTotalReads	20
plotUniquelyMappedReads	20
prereadGTF	21
print.bed	22
print.fa	22
print.featureCounts	23
print.fq	23
print.gtf	24
print.pedMap	25
print.vcf	25
summary.bed	26
summary.fa	26
summary.featureCounts	27
summary.fq	28
summary.gtf	28
summary.STARLog	29
Index	30

GenomicTools.fileHandler-package

R Package To Handle Files From Genomic Data *GenomicTools.fileHandler* is a loose collection of I/O Functions Needed in Genomic Data Analysis

Description

Package: GenomicTools.fileHandler
 Type: Package
 Version: 0.1.5.9
 Date: 2020-03-05

License: GPL
LazyLoad: yes

Author(s)

Daniel Fischer

Maintainer: Daniel Fischer <daniel.fischer@luke.fi>

example.bed

Example Gene Annotation in Bed-Format

Description

This file contains some example lines to represent a typical bed file that can be used to try the corresponding functions.

Format

A file with three column Chr, Start and End.

Details

The file is located in the /extdata folder of the package and is accessible after installation via `system.file("extdata", "example.bed", package="GenomicTools.fileHandler")`

Author(s)

Daniel Fischer

example.fasta

Example Sequencing Reads in fasta-Format

Description

This file contains some example reads to represent a typical fasta file that can be used to try the corresponding functions.

Details

The file is located in the /extdata folder of the package and is accessible after installation via `system.file("extdata", "example.fasta", package="GenomicTools.fileHandler")`

Author(s)

Daniel Fischer

`example.fastq`*Example Sequencing Reads in fastq-Format*

Description

This file contains some example reads to represent a typical fastq file that can be used to try the corresponding functions.

Details

The file is located in the `/extdata` folder of the package and is accessible after installation via `system.file("extdata", "example.fastq", package="GenomicTools.fileHandler")`

Author(s)

Daniel Fischer

`example.gff`*Example Gene Annotation in gff-Format*

Description

This file contains some example gene annotations to represent a typical gff file that can be used to try the corresponding functions.

Details

The file is located in the `/extdata` folder of the package and is accessible after installation via `system.file("extdata", "example.gff", package="GenomicTools.fileHandler")`

Author(s)

Daniel Fischer

`example.gtf`*Example Gene Annotation in gtf-Format*

Description

This file contains some example gene annotations to represent a typical gtf file that can be used to try the corresponding functions.

Details

The file is located in the `/extdata` folder of the package and is accessible after installation via `system.file("extdata", "example.gtf", package="GenomicTools.fileHandler")`

Author(s)

Daniel Fischer

`example.ped`*Example Variant data in ped/map-Format*

Description

This file contains some example variants to represent a typical ped/map file pair that can be used to try the corresponding functions.

Details

The file is located in the `/extdata` folder of the package and is accessible after installation via `system.file("extdata", "example.ped", package="GenomicTools.fileHandler")`

Author(s)

Daniel Fischer

`example.vcf`*Example Variant data in vcf-Format*

Description

This file contains some example variants to represent a typical vcf file that can be used to try the corresponding functions.

Details

The file is located in the `/extdata` folder of the package and is accessible after installation via `system.file("extdata", "example.vcf", package="GenomicTools.fileHandler")`

Author(s)

Daniel Fischer

`example2.gtf.gz`*Example Gene Annotation in zipped gtf-Format*

Description

This file contains some example gene annotations to represent a typical zipped gtf file that can be used to try the corresponding functions.

Details

The file is located in the `/extdata` folder of the package and is accessible after installation via `system.file("extdata", "example2.gtf.gz", package="GenomicTools.fileHandler")`

Author(s)

Daniel Fischer

exportBed	<i>Exporting a Bed File.</i>
-----------	------------------------------

Description

This function exports a standard bed file.

Usage

```
exportBed(x, file = NULL, header = FALSE)
```

Arguments

x	data.frame
file	Character, specifies filename/path
header	Logical, shall a header be written

Details

This function exports a data.frame to a standard bed file. If no file name is given, the variable name will be used instead.

Value

A bed file

Author(s)

Daniel Fischer

Examples

```
novelBed <- data.frame(Chr=c(11,18,3),
                      Start=c(72554673, 62550696, 18148822),
                      End=c(72555273, 62551296, 18149422),
                      Gene=c("LOC1", "LOC2", "LOC3"))

# Create a temporary file to where the output of the function is stored
myfile <- file.path(tempdir(), "myLocs.bed")

exportBed(novelBed, file=myfile)
exportBed(novelBed, file=myfile, header=TRUE)
```

`exportFA`*Exporting a Fasta File.*

Description

This function exports a standard fasta file.

Usage

```
exportFA(fa, file = NULL)
```

Arguments

<code>fa</code>	fasta object
<code>file</code>	Character, specifies filename/path

Details

This function exports a fasta object to a standard fasta file. If no file name is given, the variable name will be used instead.

Value

A fasta file

Author(s)

Daniel Fischer

Examples

```
# Define here the location on HDD for the example file
fpath <- system.file("extdata", "example.fasta", package="GenomicTools.fileHandler")
# Import the example fasta file
fastaFile <- importFA(file=fpath)
newFasta <- fastaFile[1:5]

myfile <- file.path(tempdir(), "myLocs.fa")

exportFA(newFasta, file=myfile)
```

`importBed`*Importing a Bed File.*

Description

This function imports a standard bed file

Usage

```
importBed(file, header = FALSE, sep = "\t")
```

Arguments

<code>file</code>	Specifies the filename/path
<code>header</code>	Logical, is a header present
<code>sep</code>	Column separator

Details

This function imports a standard bed-file into a data.frame. It is basically a convenience wrapper around `read.table`. However, if no header lines is given, this function automatically assigns the column names, as they are given in the bed-specification on the Ensembl page here: <https://www.ensembl.org/info/website/upload/bed.html>

Value

A data.frame

Author(s)

Daniel Fischer

See Also

[`exportBed`], [`read.table`]

Examples

```
# Define here the location on HDD for the example file
fpath <- system.file("extdata", "example.bed", package="GenomicTools.fileHandler")
# Import the example bed file
bedFile <- importBed(file=fpath)
```

importBlastTab	<i>Import a Tab Delimited Blast Output File</i>
----------------	---

Description

This function imports a tab delimited blast output.

Usage

```
importBlastTab(file)
```

Arguments

file	Filename
------	----------

Details

This function imports a tab delimited blast output file, currently the same as read.table

Value

A data.frame

Author(s)

Daniel Fischer

importFA	<i>Importing a Fasta File.</i>
----------	--------------------------------

Description

This function imports a standard fasta file

Usage

```
importFA(file)
```

Arguments

file	Specifies the filename/path
------	-----------------------------

Details

This function imports a standard fasta file. Hereby, it does not matter if the identifier and sequence are alternating or not, as the rows starting with '>' are used as identifier.

The example file was downloaded from here and was then further truncated respective transformed to fasta format:

```
ftp://ftp.1000genomes.ebi.ac.uk/vol1/ftp/phase3/data/HG00096/sequence_read/
```

Value

An object of class `fa` containing the sequences. The names correspond to the sequence names given in the fasta file.

Author(s)

Daniel Fischer

See Also

`print.fa`, `summary.fa`

Examples

```
# Define here the location on HDD for the example file
fpath <- system.file("extdata", "example.fasta", package="GenomicTools.fileHandler")
# Import the example fasta file
fastaFile <- importFA(file=fpath)
```

`importFeatureCounts` *Import from FeatureCounts*

Description

This functions imports the output from `FeatureCounts`

Usage

```
importFeatureCounts(file, skip = 0, headerLine = 2)
```

Arguments

<code>file</code>	Character, file name
<code>skip</code>	Number of lines to skip from txt file
<code>headerLine</code>	Linenumber that contains the header information

Details

FeatureCounts produces two files, the txt that contain the expression values and then the summary that contains all the information about the mapping statistics. This function imports both and stores them in a corresponding list.

Value

A list with expValues, geneInfo and summary

Author(s)

Daniel Fischer

Examples

```
# Define here the location on HDD for the example file
fpath <- system.file("extdata","featureCountsExample.txt", package="GenomicTools.fileHandler")
# Import the example featureCounts file
fcFile <- importFeatureCounts(file=fpath)
```

importFQ

Importing a Fastq File.

Description

This function imports a standard fastq file

Usage

```
importFQ(file)
```

Arguments

file Specifies the filename/path

Details

This function imports a standard fastq file that consists out of blocks of four lines per entry

Value

An object of class fq containing the sequences and the quality measure. The names correspond to the sequence names given in the fasta file.

Author(s)

Daniel Fischer

See Also

print.fq, summary.fq

Examples

```
# Define here the location on HDD for the example file
fpath <- system.file("extdata", "example.fastq", package="GenomicTools.fileHandler")
# Import the example fastq file
fastqFile <- importFQ(file=fpath)
```

importGFF

importGFF

Description

Import a GFF file

Usage

```
importGFF(file, skip = "auto", nrow = -1, use.data.table = TRUE,
  level = "gene", features = NULL, num.features = c("FPKM", "TPM"),
  print.features = FALSE, merge.feature = NULL, merge.all = TRUE,
  class.names = NULL, verbose = TRUE)
```

Arguments

file	file or folder
skip	numeric, lines to skip
nrow	numeric, lines to read
use.data.table	logical
level	Character, read level, default: "gene"
features	features to import
num.features	names of the numeric features
print.features	Logical, print available features
merge.feature	Character, merge multiple samples to dataset
merge.all	Logical, shall all samples be merged together
class.names	Definition of class name sin V9
verbose	Logical, verbose function output

Details

This function imports a standard gff file.

Value

A gff object

Author(s)

Daniel Fischer

Examples

```
# Define here the location on HDD for the example file
fpath <- system.file("extdata", "example.gff", package="GenomicTools.fileHandler")
# Import the example gff file
importGFF(fpath)
```

`importGFF3`

importGFF3

Description

Import a GFF3 file

Usage

```
importGFF3(gff, chromosomes)
```

Arguments

<code>gff</code>	file or folder
<code>chromosomes</code>	The chromosome to import

Details

This function imports a standard gff3 file.

Value

A gff object

Author(s)

Daniel Fischer

importGTF	<i>Import a GTF File</i>
-----------	--------------------------

Description

This function imports a gtf file.

Usage

```
importGTF(file, skip = "auto", nrow = -1, use.data.table = TRUE,
  level = "gene", features = NULL, num.features = c("FPKM", "TPM"),
  print.features = FALSE, merge.feature = NULL, merge.all = TRUE,
  class.names = NULL, verbose = TRUE)
```

Arguments

file	file or folder
skip	numeric, lines to skip
nrow	numeric, lines to read
use.data.table	logical
level	Character, read level, default: "gene"
features	features to import
num.features	names of the numeric features
print.features	Logical, print available features
merge.feature	Character, merge multiple samples to dataset
merge.all	Logical, shall all samples be merged
class.names	Vector with class names
verbose	Logical, verbose function output

Details

This function imports a gtf file. The features names to be imported are defined in features, several features are then provided as vector. A list of available feature can beprinted, by setting print.features=TRUE.

The skip option allows to skip a given number of rows, the default is, however, auto. In that case, all rows that start with the # symbol are skipped.

In case a set of expression values given in gtf format should be imported and to be merged into a single data table, the feature that should be used for merging can be provided to the merge.feature option. In that case the function expects a folder in file and it will import all gtfs located in that folder and merges them according to the merge.feature option. With the option class.names a vector of prefixes for the merged features can be provided. If this is kept empty, then the filenames of the gtf will be used instead (without gtf extension).

By default the function imprts all features in column 9 as string character. However, for common labels (FPKM and TPM) the class type is set automatically to numeric. Additional numerical feature names can be defined with the num.feature option.

Value

A gtf object

Author(s)

Daniel Fischer

Examples

```
# Define here the location on HDD for the example file
fpath <- system.file("extdata","example.gtf", package="GenomicTools.fileHandler")
# Same file, but this time as gzipped version
fpath.gz <- system.file("extdata","example2.gtf.gz", package="GenomicTools.fileHandler")

# Import the example gtf file
importGTF(fpath, level="transcript", features=c("gene_id","FPKM"))

## Not run:
# For the current you need to have zcat installed (should be standard on a Linux system)
importGTF(fpath.gz, level="transcript", features=c("gene_id","FPKM"))

## End(Not run)
```

importPED

importPED

Description

Import a PED/MAP file pair

Usage

```
importPED(file, n, snps = NULL, which, split = "\t| +", sep = ".",
na.strings = "0", lex.order = FALSE, verbose = TRUE)
```

Arguments

file	ped filename
n	Number of samples to read
snps	map filename
which	Names of SNPS to import
split	Columns separator in ped file
sep	Character that separates Alleles
na.strings	Definition for missing values
lex.order	Logical, lexicographical order
verbose	Logical, verbose output

Details

This function is to a large extent taken from `snpStat::read.pedmap`, but here is internally the `data.table::fread` function used that resulted in much faster file processing.

To import the data, the ped file can be provided to the `file` option and the map file to the `snps` option. If no option is given to `snps` and the `file` option is provided without any file extension, then the ped/map extension are automaticall added

Value

a pedmap object

Author(s)

Daniel Fischer

Examples

```
# Define here the location on HDD for the example file
pedPath <- system.file("extdata","example.ped", package="GenomicTools.fileHandler")
mapPath <- system.file("extdata","example.map", package="GenomicTools.fileHandler")
# Import the example ped/map files
importPED(file=pedPath, snps=mapPath)
```

importSTARLog

importSTARLog

Description

Import the Log-File from STAR

Usage

```
importSTARLog(dir, recursive = TRUE, log = FALSE, finalLog = TRUE,
  verbose = TRUE)
```

Arguments

<code>dir</code>	The directory name
<code>recursive</code>	Logical, check for sub-directories
<code>log</code>	boolean, import also log file
<code>finalLog</code>	boolean, import also <code>final_log</code> file
<code>verbose</code>	Logical, talkactive function feedback

Details

This function imports the Log file from STAR

Value

a data frame

Author(s)

Daniel Fischer

`importVCF`

importVCF

Description

Import a VCF function

Usage

```
importVCF(file, na.seq = "./.")
```

Arguments

<code>file</code>	The file name
<code>na.seq</code>	The missing value definition

Details

This function imports a VCF file.

In case the logicl flag 'phased' is set to TRUE then the genotypes are expected to be in the format 0/0, otherwise they are expected to be like 0/1 .

The example file was downloaded from here:

ftp://ftp.1000genomes.ebi.ac.uk/vol1/ftp/pilot_data/release/2010_07/exon/snps/

Value

A vcf object

Author(s)

Daniel Fischer

Examples

```
# Define here the location on HDD for the example file
fpath <- system.file("extdata","example.vcf", package="GenomicTools.fileHandler")
# Import the example vcf file
importVCF(fpath)
```

importXML

importXML

Description

Import an Blast XML file

Usage

```
importXML(folder, seqNames = NULL, which = NULL, idTH = 0.8,
          verbose = TRUE)
```

Arguments

folder	Character, folder path
seqNames	Names of sequences
which	Which sequences to import
idTH	Use the threshold as cut-off
verbose	Logical, verbose output

Details

This function imports XML files as provided as Blast output, it is mainly aimed to import the output of the hoardeR package

Value

An XML object

Author(s)

Daniel Fischer

<code>plotTotalReads</code>	<i>plotTotalReads</i>
-----------------------------	-----------------------

Description

Plot the total reads

Usage

```
plotTotalReads(STARLog)
```

Arguments

STARLog A STARLog object

Details

This function plots the total reads from a STARlog object

Part of the diagnostic plot series for of the STARLog. The function accepts also a list of STARLogs and creates then comparative boxplots

Value

A plot

Author(s)

Daniel Fischer

<code>plotUniquelyMappedReads</code>	<i>plotUniquelyMappedReads</i>
--------------------------------------	--------------------------------

Description

Plot the uniquely mapped reads

Usage

```
plotUniquelyMappedReads(STARLog)
```

Arguments

STARLog A STARLog object

Details

This function plots the percentage of uniquely reads from a STARlog object

Part of the diagnostic plot series for of the STARLog. The function accepts also a list of STARLogs and creates then comparative boxplots

Value

A plot

Author(s)

Daniel Fischer

```
prereadGTF
```

```
prereadGTF
```

Description

Preread a gtf file and prints features of it for importing it.

Usage

```
prereadGTF(file, nrow = 1000, skip = "auto")
```

Arguments

file	Filename
nrow	Number of rows to read
skip	Rows to skip from top

Details

This function reads in a gtf file and prints its features for the import step.

By default this function only imports the first 1000 rows, in case all rows should be imported set nrow=-1.

The number to skip in the beginning can be adjusted by the skip option. The default is here auto so that the function can identify the correct amount of header rows. Hence, this option should be changed only, if there is a good reason.

Value

A list of available features

Author(s)

Daniel Fischer

print.bed *Print a bed Object*

Description

Prints a bed object.

Usage

```
## S3 method for class 'bed'  
print(x, n = 6, ...)
```

Arguments

x	Object of class bed.
n	Number of lines to print
...	Additional parameters

Details

The print function displays a bed object

Author(s)

Daniel Fischer

print.fa *Print a fa Object*

Description

Prints a fa object.

Usage

```
## S3 method for class 'fa'  
print(x, n = 2, seq.out = 50, ...)
```

Arguments

x	Object of class fa.
n	Number of sequences to display
seq.out	Length of the subsequence to display
...	Additional parameters

Details

The print function displays a fa object

Author(s)

Daniel Fischer

`print.featureCounts` *Print a featureCounts Object*

Description

Prints an featureCounts object.

Usage

```
## S3 method for class 'featureCounts'  
print(x, ...)
```

Arguments

<code>x</code>	Object of class featureCounts.
<code>...</code>	Additional parameters

Details

The print function displays a featureCounts object

Author(s)

Daniel Fischer

`print.fq` *Print a fq Object*

Description

Prints a fq object.

Usage

```
## S3 method for class 'fq'  
print(x, n = 2, seq.out = 50, print.qual = TRUE, ...)
```

Arguments

x	Object of class fq.
n	Number of sequences to display
seq.out	Length of the subsequence to display
print.qual	Logical, shall the quality measures also be printed
...	Additional parameters

Details

The print function displays a fa object

Author(s)

Daniel Fischer

<code>print.gtf</code>	<i>Print a gtf Object</i>
------------------------	---------------------------

Description

Prints a gtf object.

Usage

```
## S3 method for class 'gtf'
print(x, n = 6, ...)
```

Arguments

x	Object of class gtf.
n	Number of lines to print
...	Additional parameters

Details

The print function displays a bed object

Author(s)

Daniel Fischer

```
print.pedMap          Print a pedMap Object
```

Description

Prints an pedMap object.

Usage

```
## S3 method for class 'pedMap'
print(x, n = 6, m = 6, ...)
```

Arguments

x	Object of class pedMap.
n	Number of samples to display
m	Number of columns to display
...	Additional parameters

Details

The print function displays a pedMap object

Author(s)

Daniel Fischer

```
print.vcf          Print a vcf Object
```

Description

Prints an vcf object.

Usage

```
## S3 method for class 'vcf'
print(x, n = 6, m = 6, fullHeader = FALSE, ...)
```

Arguments

x	Object of class vcf.
n	Number of samples to display
m	Number of columns to display
fullHeader	Logical, shall the whole header be printed
...	Additional parameters

Details

The print function displays a vcf object

Author(s)

Daniel Fischer

summary.bed

Summary of a bed Object

Description

Summarizes a bed object.

Usage

```
## S3 method for class 'bed'  
summary(object, ...)
```

Arguments

object	Object of class bed.
...	Additional parameters

Details

The summary function displays an informative summary of a bed object

Author(s)

Daniel Fischer

summary.fa

Summary of a fa Object

Description

Summarizes a fa object.

Usage

```
## S3 method for class 'fa'  
summary(object, ...)
```

Arguments

object	Object of class fa.
...	Additional parameters

Details

The summary function displays an informative summary of a fa object

Author(s)

Daniel Fischer

summary.featureCounts *Summary of a featureCounts Object*

Description

Summarizes a featureCounts object.

Usage

```
## S3 method for class 'featureCounts'  
summary(object, ...)
```

Arguments

object	Object of class featureCounts.
...	Additional parameters

Details

The summary function displays an informative summary of a featureCounts object

Author(s)

Daniel Fischer

summary.fq

Summary of a fq Object

Description

Summarizes a fq object.

Usage

```
## S3 method for class 'fq'  
summary(object, ...)
```

Arguments

object	Object of class fq.
...	Additional parameters

Details

The summary function displays an informative summary of a fq object

Author(s)

Daniel Fischer

summary.gtf

Summary of a gtf Object

Description

Summarizes a gtf object.

Usage

```
## S3 method for class 'gtf'  
summary(object, ...)
```

Arguments

object	Object of class gtf.
...	Additional parameters

Details

The summary function displays an informative summary of a gtf object

Author(s)

Daniel Fischer

summary.STARLog *Summary of a STARLog Object*

Description

Summarizes a STARLog object.

Usage

```
## S3 method for class 'STARLog'  
summary(object, ...)
```

Arguments

object Object of class STARLog.
... Additional parameters

Details

The summary function displays an informative summary of a STARLog object

Author(s)

Daniel Fischer

Index

*Topic **data**

- example.bed, 3
- example.fasta, 3
- example.fastq, 4
- example.gff, 4
- example.gtf, 5
- example.ped, 5
- example.vcf, 6
- example2.gtf.gz, 6

*Topic **methods**

- print.bed, 22
- print.fa, 22
- print.featureCounts, 23
- print.fq, 23
- print.gtf, 24
- print.pedMap, 25
- print.vcf, 25
- summary.bed, 26
- summary.fa, 26
- summary.featureCounts, 27
- summary.fq, 28
- summary.gtf, 28
- summary.STARLog, 29

*Topic **print**

- print.bed, 22
- print.fa, 22
- print.featureCounts, 23
- print.fq, 23
- print.gtf, 24
- print.pedMap, 25
- print.vcf, 25

*Topic **summary**

- summary.bed, 26
- summary.fa, 26
- summary.featureCounts, 27
- summary.fq, 28
- summary.gtf, 28
- summary.STARLog, 29

example.bed, 3

- example.fasta, 3
- example.fastq, 4
- example.gff, 4
- example.gtf, 5
- example.ped, 5
- example.vcf, 6
- example2.gtf.gz, 6
- exportBed, 7
- exportFA, 8

GenomicTools.fileHandler-package, 2

- importBed, 9
- importBlastTab, 10
- importFA, 10
- importFeatureCounts, 11
- importFQ, 12
- importGFF, 13
- importGFF3, 14
- importGTF, 15
- importPED, 16
- importSTARLog, 17
- importVCF, 18
- importXML, 19

- plotTotalReads, 20
- plotUniquelyMappedReads, 20
- prereadGTF, 21
- print.bed, 22
- print.fa, 22
- print.featureCounts, 23
- print.fq, 23
- print.gtf, 24
- print.pedMap, 25
- print.vcf, 25

- summary.bed, 26
- summary.fa, 26
- summary.featureCounts, 27
- summary.fq, 28

summary.gtf, [28](#)

summary.STARLog, [29](#)