

# Package ‘d3r’

May 8, 2026

**Type** Package

**Title** 'd3.js' Utilities for R

**Version** 1.1.0

**Date** 2023-10-01

**Maintainer** Kent Russell <kent.russell@timelyportfolio.com>

**URL** <https://github.com/timelyportfolio/d3r>

**BugReports** <https://github.com/timelyportfolio/d3r/issues>

**Description** Provides a suite of functions to help ease the use of 'd3.js' in R. These helpers include 'htmltools::htmlDependency' functions, hierarchy builders, and conversion tools for 'partykit', 'igraph', 'table', and 'data.frame' R objects into the 'JSON' that 'd3.js' expects.

**License** BSD\_3\_clause + file LICENSE

**Encoding** UTF-8

**Imports** dplyr, htmltools, tidyr (>= 0.8.3)

**Suggests** httr, jsonlite, listviewer, purrr, testthat

**Enhances** igraph, partykit, rpart, treemap, V8

**RoxygenNote** 7.2.3

**NeedsCompilation** no

**Author** Mike Bostock [aut, cph] (d3.js library in htmlwidgets/lib, <http://d3js.org>),  
Kent Russell [aut, cre, cph] (R interface),  
Gregor Aisch [aut, cph] (d3-jetpack creator, <https://github.com/gka/d3-jetpack>),  
Adam Pearce [aut] (core contributor to d3-jetpack),  
Ben Ortiz [ctb]

**Repository** CRAN

**Date/Publication** 2023-10-02 14:00:02 UTC

## Contents

change_to_name . . . . .	2
d3_dep_jetpack . . . . .	3
d3_dep_v3 . . . . .	4
d3_dep_v4 . . . . .	5
d3_dep_v5 . . . . .	6
d3_dep_v6 . . . . .	6
d3_dep_v7 . . . . .	7
d3_igraph . . . . .	8
d3_json . . . . .	9
d3_nest . . . . .	9
d3_party . . . . .	10
d3_table . . . . .	12
d3_v8 . . . . .	12
promote_na . . . . .	15
promote_na_one . . . . .	15
<b>Index</b>	<b>16</b>

---

change_to_name	<i>Change Column Name in Children to "name"</i>
----------------	---

---

### Description

Change Column Name in Children to "name"

### Usage

```
change_to_name(x, column = 1)
```

### Arguments

x	data.frame or data.frame derivative, such as tibble
column	column to convert

### Value

data.frame

---

d3_dep_jetpack	<i>'d3.js' Dependency for Version 4 Jetpack</i>
----------------	---

---

## Description

d3-jetpack is a set of nifty convenience wrappers that speed up your daily work with d3.js. Must be included after `d3_dep_v4()`. Learn more by reading [d3-jetpack](#) or by watching this [YouTube](#).

## Usage

```
d3_dep_jetpack(offline = TRUE)
```

## Arguments

offline	logical to specify whether to use a local copy of d3.js (TRUE) or use cdn (FALSE)
---------	---

## Value

```
htmltools::htmlDependency
```

## See Also

Other 'd3' dependency functions: [d3\\_dep\\_v3\(\)](#), [d3\\_dep\\_v4\(\)](#), [d3\\_dep\\_v5\(\)](#), [d3\\_dep\\_v6\(\)](#), [d3\\_dep\\_v7\(\)](#)

## Examples

```
## Not run:

library(d3r)
library(htmltools)

t1 <- tagList(tags$script(HTML(sprintf(
"
var x = 5;

var svg = d3.select('body')
  .append('svg');

svg.append('rect')
  .at({
    x: 100,
    y: 100,
    width: 100,
    height: 100
  })
  .st({
    fill: 'blue',
    stroke: 'purple'
  })

```

```

    });
    "
  ))) , d3_dep_v4(), d3_dep_jetpack()
  browsable(t1)

  t1 <- tagList(tags$script(HTML(sprintf(
    "
    var svg = d3.select('body')
      .append('svg');

    test_data = [{x: 250, y: 250}, {x: 300, y: 300}, {x: 300, y: 100}];

    svg.appendMany(test_data, 'circle')
      .at({
        cx: function(d){return d.x},
        cy: function(d){return d.y},
        r: 50
      })
      .st({
        fill: 'purple',
        stroke: 'blue'
      })
    "
  ))) , d3_dep_v4(), d3_dep_jetpack()

  browsable(t1)

  ## End(Not run)

```

---

d3\_dep\_v3

*'d3.js' Dependency for Version 3*


---

### Description

'd3.js' Dependency for Version 3

### Usage

```
d3_dep_v3(offline = TRUE)
```

### Arguments

`offline`            logical to specify whether to use a local copy of d3.js (TRUE) or use cdn (FALSE)

### Value

htmltools::htmlDependency

**See Also**

[d3\\_dep\\_v7](#), [d3\\_dep\\_v6](#), [d3\\_dep\\_v5](#), [d3\\_dep\\_v4](#), and [d3\\_dep\\_jetpack](#).

Other 'd3' dependency functions: [d3\\_dep\\_jetpack\(\)](#), [d3\\_dep\\_v4\(\)](#), [d3\\_dep\\_v5\(\)](#), [d3\\_dep\\_v6\(\)](#), [d3\\_dep\\_v7\(\)](#)

**Examples**

```
library(d3r)
library(htmltools)

tagList(d3_dep_v3())
```

---

d3\_dep\_v4

*'d3.js' Dependency for Version 4*

---

**Description**

'd3.js' Dependency for Version 4

**Usage**

```
d3_dep_v4(offline = TRUE)
```

**Arguments**

`offline` logical to specify whether to use a local copy of d3.js (TRUE) or use cdn (FALSE)

**Value**

htmltools::htmlDependency

**See Also**

[d3\\_dep\\_v7](#), [d3\\_dep\\_v6](#), [d3\\_dep\\_v5](#), [d3\\_dep\\_v3](#), and [d3\\_dep\\_jetpack](#).

Other 'd3' dependency functions: [d3\\_dep\\_jetpack\(\)](#), [d3\\_dep\\_v3\(\)](#), [d3\\_dep\\_v5\(\)](#), [d3\\_dep\\_v6\(\)](#), [d3\\_dep\\_v7\(\)](#)

**Examples**

```
library(d3r)
library(htmltools)

tagList(d3_dep_v4())
```

---

d3\_dep\_v5                    *'d3.js' Dependency for Version 5*

---

**Description**

'd3.js' Dependency for Version 5

**Usage**

```
d3_dep_v5(offline = TRUE)
```

**Arguments**

offline                    logical to specify whether to use a local copy of d3.js (TRUE) or use cdn (FALSE)

**Value**

htmltools::htmlDependency

**See Also**

[d3\\_dep\\_v7](#), [d3\\_dep\\_v6](#), [d3\\_dep\\_v4](#), [d3\\_dep\\_v3](#), and [d3\\_dep\\_jetpack](#).

Other 'd3' dependency functions: [d3\\_dep\\_jetpack\(\)](#), [d3\\_dep\\_v3\(\)](#), [d3\\_dep\\_v4\(\)](#), [d3\\_dep\\_v6\(\)](#), [d3\\_dep\\_v7\(\)](#)

**Examples**

```
library(d3r)
library(htmltools)

tagList(d3_dep_v5())
```

---

d3\_dep\_v6                    *'d3.js' Dependency for Version 6*

---

**Description**

'd3.js' Dependency for Version 6

**Usage**

```
d3_dep_v6(offline = TRUE)
```

**Arguments**

offline            logical to specify whether to use a local copy of d3.js (TRUE) or use cdn (FALSE)

**Value**

htmltools::htmlDependency

**See Also**

[d3\\_dep\\_v7](#), [d3\\_dep\\_v5](#), [d3\\_dep\\_v4](#), [d3\\_dep\\_v3](#), and [d3\\_dep\\_jetpack](#).

Other 'd3' dependency functions: [d3\\_dep\\_jetpack\(\)](#), [d3\\_dep\\_v3\(\)](#), [d3\\_dep\\_v4\(\)](#), [d3\\_dep\\_v5\(\)](#), [d3\\_dep\\_v7\(\)](#)

**Examples**

```
library(d3r)
library(htmltools)

tagList(d3_dep_v6())
```

---

d3\_dep\_v7

*'d3.js' Dependency for Version 7*

---

**Description**

'd3.js' Dependency for Version 7

**Usage**

```
d3_dep_v7(offline = TRUE)
```

**Arguments**

offline            logical to specify whether to use a local copy of d3.js (TRUE) or use cdn (FALSE)

**Value**

htmltools::htmlDependency

**See Also**

[d3\\_dep\\_v6](#), [d3\\_dep\\_v5](#), [d3\\_dep\\_v4](#), [d3\\_dep\\_v3](#), and [d3\\_dep\\_jetpack](#).

Other 'd3' dependency functions: [d3\\_dep\\_jetpack\(\)](#), [d3\\_dep\\_v3\(\)](#), [d3\\_dep\\_v4\(\)](#), [d3\\_dep\\_v5\(\)](#), [d3\\_dep\\_v6\(\)](#)

**Examples**

```
library(d3r)
library(htmltools)

tagList(d3_dep_v7())
```

---

d3_igraph	<i>Convert 'igraph' to 'd3.js'</i>
-----------	------------------------------------

---

**Description**

Convert 'igraph' to 'd3.js'

**Usage**

```
d3_igraph(igrf = NULL, json = TRUE)
```

**Arguments**

igrf	igraph
json	logical to return as JSON

**Value**

list

**Examples**

```
## Not run:
library(igraph)
library(igraphdata)
library(d3r)

# with random graph
d3r::d3_igraph(igraph::sample_pa(100))

# check case where vertices 0 cols
d3_igraph(igraph::watts.strogatz.game(1, 50, 4, 0.05))

# with karate from igraphdata
# notice graph attributes are added
data("karate",package="igraphdata")
(karate_d3 <- d3r::d3_igraph(karate))

listviewer::jsonedit(karate_d3)

data("kite",package="igraphdata")
listviewer::jsonedit(d3_igraph(kite))

## End(Not run)
```

---

d3_json	<i>Create 'JSON' that 'd3.js' Expects</i>
---------	---

---

**Description**

Create 'JSON' that 'd3.js' Expects

**Usage**

```
d3_json(x = NULL, strip = TRUE)
```

**Arguments**

x	data, usually in the form of <code>data.frame</code> or <code>list</code>
strip	logical to remove outer array. Use <code>strip=TRUE</code> for hierarchies from <code>d3_nest</code>

**Value**

string of 'JSON' data

---

d3_nest	<i>Convert a <code>data.frame</code> to a 'd3.js' Hierarchy</i>
---------	---

---

**Description**

Convert a `data.frame` to a 'd3.js' Hierarchy

**Usage**

```
d3_nest(data = NULL, value_cols = character(), root = "root", json = TRUE)
```

**Arguments**

data	<code>data.frame</code> or <code>data.frame</code> derivative, such as <code>tibble</code>
value_cols	character vector with the names of the columns to use as data
root	character name of the root level of the hierarchy
json	logical to return as JSON

**Value**

nested `data.frame`

**Examples**

```

# convert Titanic to a nested d3 hierarchy

# devtools::install_github("timelyportfolio/d3r")
library(d3r)
library(dplyr)

titanic_df <- data.frame(Titanic)
tit_tb <- titanic_df %>%
  select(Class, Age, Survived, Sex, Freq) %>%
  d3_nest(value_cols="Freq", root="titanic")

tit_tb

# see as tibble
titanic_df %>%
  select(Class, Age, Survived, Sex, Freq) %>%
  d3_nest(value_cols="Freq", root="titanic", json=FALSE)

# see the structure with listviewer
tit_tb %>%
  listviewer::jsonedit()
## Not run:
library(treemap)
library(d3r)
library(dplyr)
library(tidyr)

treemap::random.hierarchical.data() %>%
  d3_nest(value_cols = "x")

# use example from ?treemap
data(GNI2014)
treemap(
  GNI2014,
  index=c("continent", "iso3"),
  vSize="population",
  vColor="GNI",
  type="value",
  draw=FALSE
) %>%
  {.$tm} %>%
  select(continent, iso3, color, vSize) %>%
  d3_nest(value_cols = c("color", "vSize"))

## End(Not run)

```

**Description**

This thing is not even close to being done, so please help with ideas and contributions.

**Usage**

```
d3_party(tree = NULL, json = TRUE)
```

**Arguments**

tree	partykit object to be converted
json	logical to return list or json

**Value**

list or json depending on json arg

**Examples**

```
## Not run:

library(d3r)
# from ?rpart
data("kyphosis", package="rpart")
d3_party(
  rpart::rpart(Kyphosis ~ Age + Number + Start, data = kyphosis)
)

# if you want the list instead of json
d3_party(
  rpart::rpart(Kyphosis ~ Age + Number + Start, data = kyphosis),
  json = FALSE
)

# with ctree instead of rpart
# using example from ?ctree
d3_party(partykit::ctree(Species ~ ., data = iris))

#devtools::install_github("timelyportfolio/d3treeR")

library(d3treeR)

d3tree2(
  d3_party(
    rpart::rpart(Kyphosis ~ Age + Number + Start, data = kyphosis)
  ),
  celltext = "rule",
  valueField = "n"
)

## End(Not run)
```

---

d3_table	<i>Converts Table to 'd3' Nodes and Links</i>
----------	---

---

**Description**

Converts Table to 'd3' Nodes and Links

**Usage**

```
d3_table(tB = NULL, vars = NULL, agg = "Freq")
```

**Arguments**

tB	table to convert
vars	character vector of column names
agg	character column name of aggregated value

**Value**

list of two data.frames - one for nodes and one for links of the network. This structure is helpful when working with networkD3 and visNetwork.

**Examples**

```
library(d3r)
d3_table(Titanic, c("Class", "Sex"))
```

---

d3_v8	<i>Create V8 Context with D3</i>
-------	----------------------------------

---

**Description**

Create V8 Context with D3

**Usage**

```
d3_v8(...)
```

**Arguments**

... arguments passed to v8()

**Value**

v8 context with d3.js loaded and available as d3

## Examples

```
## Not run:

# to do this all in R, please see ggraph
# https://github.com/thomasp85/ggraph
# by Thomas Lin Pedersen
library(d3r)

# make a simple data.frame of US state data
states <- data.frame(
  region = as.character(state.region),
  state = as.character(state.abb),
  population = state.x77[,"Population"],
  stringsAsFactors = FALSE
)

# use d3_nest to get the data.frame in a d3 hierarchy
state_hier <- d3_nest(
  states,
  value_cols = "population"
)

# use d3_v8 to do something useful with d3 and, our state data
ctx <- d3_v8()
ctx$eval(sprintf(
  " var states = %s",
  state_hier
))
ctx$eval(
  "
  // we assigned the variable states above
  // so now make it a real d3 hierarchy
  var root = d3.hierarchy(states);

  // sum on population
  root.sum(function(d) {return d.population ? d.population : 0});

  // use d3 to circle pack or state hierarchy
  d3.pack()(root);

  // get something we can convert into a data.frame in R
  var states_packed = [];
  root.each(function(d) {
    states_packed.push({
      name: d.data.name,
      radius: d.r,
      x: d.x,
      y: d.y
    });
  });
  });
"
```

```

)

# now get states_packed from our context
# to plot in R
states_packed <- ctx$get("states_packed")
opar <- par(no.readonly=TRUE)
# make it square
par(pty="s")
symbols(
  states_packed$x,
  states_packed$y,
  states_packed$radius,
  inches=FALSE,
  asp=1
)
text(y~x, data=states_packed, labels=states_packed$name)
# return to original par before we made it square
par(opar)

# d3.quadtree example

library(d3r)

x = runif(100)
y = runif(100)

ctx <- d3_v8()
# assign pts as array of pts in V8
ctx$assign("pts", matrix(c(x,y),ncol=2,byrow=TRUE))
# use d3.quadtree() to plot rects
ctx$eval(
  "
  var d3q = d3.quadtree()
  .addAll(pts);
  // nodes function from https://bl.ocks.org/mbostock/4343214
  function nodes(quadtree) {
  var nodes = [];
  quadtree.visit(function(node, x0, y0, x1, y1) {
  nodes.push({x0:x0, y0:y0, x1: x1, y1: y1})
  });
  return nodes;
  }
  "
)

nodes <- ctx$get("nodes(d3q)", simplifyVector = FALSE)
# draw points
opar <- par(no.readonly=TRUE)
# make it square
par(pty="s")
plot(y~x)
# draw quadtree rects
rect(

```

```
lapply(nodes, function(x){x$x0}),
lapply(nodes, function(x){x$y0}),
lapply(nodes, function(x){x$x1}),
lapply(nodes, function(x){x$y1})
)
par(opar)

## End(Not run)
```

---

promote\_na                      *Apply 'promote\_na' to All Rows*

---

**Description**

Apply 'promote\_na' to All Rows

**Usage**

```
promote_na(x)
```

**Arguments**

x                      data.frame

**Value**

data.frame

---

promote\_na\_one                      *Promote NA to Top Level*

---

**Description**

Promote NA to Top Level

**Usage**

```
promote_na_one(x)
```

**Arguments**

x                      data.frame

**Value**

data.frame

# Index

## \* 'd3' dependency functions

d3\_dep\_jetpack, [3](#)

d3\_dep\_v3, [4](#)

d3\_dep\_v4, [5](#)

d3\_dep\_v5, [6](#)

d3\_dep\_v6, [6](#)

d3\_dep\_v7, [7](#)

change\_to\_name, [2](#)

d3\_dep\_jetpack, [3](#), [5–7](#)

d3\_dep\_v3, [3](#), [4](#), [5–7](#)

d3\_dep\_v4, [3](#), [5](#), [5](#), [6](#), [7](#)

d3\_dep\_v5, [3](#), [5](#), [6](#), [7](#)

d3\_dep\_v6, [3](#), [5](#), [6](#), [6](#), [7](#)

d3\_dep\_v7, [3](#), [5–7](#), [7](#)

d3\_igraph, [8](#)

d3\_json, [9](#)

d3\_nest, [9](#)

d3\_party, [10](#)

d3\_table, [12](#)

d3\_v8, [12](#)

promote\_na, [15](#)

promote\_na\_one, [15](#)