Package 'dataRetrieval'

October 14, 2026

Type Package

Title Retrieval Functions for USGS and EPA Hydrology and Water Quality Data

Version 2.7.27

Description Collection of functions to help retrieve U.S. Geological Survey and U.S. Environmental Protection Agency water quality and hydrology data from web services.

License CC0

Copyright This software is in the public domain because it contains materials that originally came from the United States Geological Survey, an agency of the United States Department of Interior.

Depends R (>= 4.1.0)

Imports curl (>= 7.0.0), lubridate (>= 1.5.0), stats, utils, xml2, readr (>= 1.4.0), jsonlite, httr2, whisker, sf, data.table, rlang

Suggests covr, dplyr, knitr, rmarkdown, testthat

Encoding UTF-8

BuildVignettes true

VignetteBuilder knitr

BugReports https://github.com/DOI-USGS/dataRetrieval/issues

Config/roxygen2/version 8.1.1

NeedsCompilation no

Author Laura DeCicco [aut, cre] (ORCID: <https://orcid.org/0000-0002-3915-9487>), Robert Hirsch [aut] (ORCID: <https://orcid.org/0000-0002-4534-075X>), David Lorenz [aut], Jordan Read [ctb], Jordan Walker [ctb], Lindsay Platt [ctb], David Watkins [aut] (ORCID: <https://orcid.org/0000-0002-7544-0700>),

David Blodgett [aut] (ORCID: <https://orcid.org/0000-0001-9489-1710>),
Mike Johnson [aut] (ORCID: <https://orcid.org/0000-0002-5288-8350>),
Aliesha Krall [ctb] (ORCID: <https://orcid.org/0000-0003-2521-5043>),
Lee Stanish [ctb] (ORCID: <https://orcid.org/0000-0002-9775-6861>),
Joseph Zemmels [aut] (ORCID: <https://orcid.org/0009-0008-1463-6313>),
Elise Hinman [aut] (ORCID: <https://orcid.org/0000-0001-5396-1583>),
Michael Mahoney [ctb] (ORCID: <https://orcid.org/0000-0003-2402-304X>),
Matthew Conlon [ctb] (ORCID: <https://orcid.org/0000-0001-8266-9610>)

Maintainer Laura DeCicco <ldecicco@usgs.gov>

Repository CRAN

Date/Publication 2026-10-14 16:12:07 UTC

Contents

addWaterYear 4
calcWaterYear 4
checkWQPdates 5
check_waterdata_sample_params 6
constructNWISURL 7
constructWQPURL 8
countyCd 9
countyCdLookup 10
create_NWIS_bib 11
create_WQP_bib 11
findNLDI 12
getQuerySummary 14
getWebServiceData 15
get_monitoring_location_arguments 15
get_nldi_sources 20
get_ogc_params 21
importNGWMN 21
importRDB1 22
importWaterML1 24
importWaterML2 27
importWQP 28
is_dataRetrieval_user 29
parameterCdFile 29
parse_WQP 30
pcode_to_name 31
readNWISdata 31
readNWISdv 33
readNWISpCode 35
readNWISpeak 36
readNWISrating 38
readNWISsite 39
readNWISstat 41
readNWISuv 43

readWQPdata . . . 45
readWQPqw . . . 50
readWQPsummary . . . 52
read_ngwmn . . . 53
read_ngwmn_lithology . . . 55
read_ngwmn_providers . . . 57
read_ngwmn_sites . . . 58
read_ngwmn_water_level . . . 62
read_ngwmn_well_construction . . . 64
read_waterdata . . . 66
read_waterdata_channel . . . 67
read_waterdata_combined_meta . . . 71
read_waterdata_continuous . . . 80
read_waterdata_daily . . . 85
read_waterdata_field_measurements . . . 89
read_waterdata_field_meta . . . 94
read_waterdata_latest_continuous . . . 98
read_waterdata_latest_daily . . . 102
read_waterdata_latest_field_measurements . . . 106
read_waterdata_metadata . . . 110
read_waterdata_monitoring_location . . . 111
read_waterdata_parameter_codes . . . 118
read_waterdata_peaks . . . 120
read_waterdata_ratings . . . 124
read_waterdata_samples . . . 126
read_waterdata_stats_por . . . 129
read_waterdata_ts_meta . . . 132
renameNWISColumns . . . 137
setAccess . . . 139
stateCd . . . 139
stateCdLookup . . . 140
summarize_waterdata_samples . . . 141
whatNWISdata . . . 142
whatNWISsites . . . 143
whatWQPdata . . . 145
whatWQPsamples . . . 146
wqp_check_status . . . 147
zeroPad . . . 148

Index **150**

addWaterYear *add a water year column*

Description

Add a column to the dataRetrieval data frame with the water year. WQP queries will return a water year column for the start and end dates of the data.

Usage

```
addWaterYear(rawData)
```

Arguments

rawData	the daily- or unit-values datset retrieved from NWISweb. Must have at least one of the following columns to add the new water year columns: dateTime, Date, ActivityStartDate, or ActivityEndDate. The date column(s) can be character, POSIXct, Date. They cannot be numeric.

Value

data.frame with an additional integer column with "WY" appended to the date column name. For WQP, there will be 2 columns: ActivityStartDateWY and ActivityEndDateWY.

Examples

```
# nwisData <- readNWISdv("04085427", "00060", "2022-01-01", "2022-06-30")
# nwisData <- addWaterYear(nwisData)

# wqpData <- readWQPqw("USGS-01594440", "01075", "", "")
# wqpData <- addWaterYear(wqpData)
```

calcWaterYear *Extract WY from a date*

Description

Determine the correct water year based on a calendar date.

Usage

```
calcWaterYear(dateVec)
```

Arguments

dateVec	vector of dates as character ("YYYY-DD-MM"), Date, or POSIXct. Numeric does not work.

Details

This function calculates a water year based on the USGS definition that a water year starts on October 1 of the year before, and ends on September 30. For example, water year 2015 started on 2014-10-01 and ended on 2015-09-30.

Value

numeric vector indicating the water year

Examples

```
x <- seq(as.Date("2010-01-01"), as.Date("2010-12-31"), by = "month")
calcWaterYear(x)

y <- c("2010-01-01", "1994-02", "1980", "2009-11-01", NA)
calcWaterYear(y)
```

---

checkWQPdates *Date Check for Water Quality Portal*

Description

Checks date format for inputs to the Water Quality Portal. Used in readWQPqw and readWQPdata.

Usage

```
checkWQPdates(values)
```

Arguments

values	named list with arguments to send to the Water Quality Portal

Value

values named list with corrected arguments to send to the Water Quality Portal

Examples

```
values <- list(
  startDateLo = "01-01-2002",
  characteristicName = "Phosphorous",
  endDate = as.Date("2014-01-01")
)
values <- checkWQPdates(values)
```

check_waterdata_sample_params *Check values from codeservice*

Description

Call a service to check on values from: https://api.waterdata.usgs.gov/samples-data/codeservice/docs.

Usage

```
check_waterdata_sample_params(service = "characteristicgroup", ...)
```

Arguments

service	Options are: "characteristicgroup", "states", "counties", "countries", "sitetype", "samplemedia", "characteristics", "observedproperty"
...	Optional additional query arguments. Only "characteristics" and "observedproperty" have additional parameters options.

Value

List, structure depends on service.

Examples

```
groups <- check_waterdata_sample_params("characteristicgroup")
states <- check_waterdata_sample_params("states")
countries <- check_waterdata_sample_params("countries")
counties <- check_waterdata_sample_params("counties")
sitetypes <- check_waterdata_sample_params("sitetype")
samplemedia <- check_waterdata_sample_params("samplemedia")
characteristics <- check_waterdata_sample_params("characteristics",
                                group = "Biological")
observedProperties <- check_waterdata_sample_params("observedproperty",
                                    text = "phosphorus")
ref_list <- check_waterdata_sample_params("reference-list")
```

constructNWISURL *Construct NWIS url for data retrieval*

Description

Using USGS water web services to construct urls.

Usage

```
constructNWISURL(
  siteNumbers,
  parameterCd = "00060",
  startDate = "",
  endDate = "",
  service,
  statCd = "00003",
  format = "xml",
  expanded = TRUE,
  ratingType = "base",
  statReportType = "daily",
  statType = "mean"
)
```

Arguments

siteNumbers	string or vector of strings USGS site number. This is usually an 8 digit number
parameterCd	string or vector of USGS parameter code. This is usually an 5 digit number.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record.
service	string USGS service to call. Possible values are "dv" (daily values), "uv" (unit/instantaneous values), and "rating" (rating curve), "peak", "stat" (statistics web service BETA).
statCd	string or vector USGS statistic code only used for daily value service. This is usually 5 digits. Daily mean (00003) is the default.
format	string, can be "tsv" or "xml", and is only applicable for daily and unit value requests. "tsv" returns results faster, but there is a possibility that an incomplete file is returned without warning. XML is slower, but will offer a warning if the file was incomplete (for example, if there was a momentary problem with the internet connection). It is possible to safely use the "tsv" option, but the user must carefully check the results to see if the data returns matches what is expected. The default is therefore "xml".
expanded	logical defaults to TRUE. If TRUE, retrieves additional information, only applicable for qw data.
ratingType	can be "base", "corr", or "exsa". Only applies to rating curve data.

`statReportType` character Only used for statistics service requests. Time division for statistics: daily, monthly, or annual. Default is daily. Note that daily provides statistics for each calendar day over the specified range of water years, i.e. no more than 366 data points will be returned for each site/parameter. Use `readNWISdata` or `readNWISdv` for daily averages. Also note that "annual" returns statistics for the calendar year. Use `readNWISdata` for water years. Monthly and yearly provide statistics for each month and year within the range individually.

`statType` character Only used for statistics service requests. Type(s) of statistics to output for daily values. Default is mean, which is the only option for monthly and yearly report types.

Value

url string

Examples

```
site_id <- "01594440"
startDate <- "1985-01-01"
endDate <- ""
pCode <- c("00060", "00010")
url_daily <- constructNWISURL(site_id, pCode,
  startDate, endDate, "dv",
  statCd = c("00003", "00001")
)
url_unit <- constructNWISURL(site_id, pCode, "2012-06-28", "2012-06-30", "iv")

url_daily_tsv <- constructNWISURL(site_id, pCode, startDate, endDate, "dv",
  statCd = c("00003", "00001"), format = "tsv"
)
url_rating <- constructNWISURL(site_id, service = "rating", ratingType = "base")
url_peak <- constructNWISURL(site_id, service = "peak")
```

---

constructWQPURL *Construct WQP url for data retrieval*

Description

Construct WQP url for data retrieval. This function gets the data from here: https://www.waterqualitydata.us

Usage

```
constructWQPURL(siteNumbers, parameterCd, startDate, endDate, legacy = TRUE)
```

Arguments

siteNumbers	string or vector of strings USGS site number.
parameterCd	string or vector of USGS parameter code. This is usually an 5 digit number.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record.
legacy	Logical. If TRUE, uses legacy WQP services. Default is TRUE. Setting legacy = FALSE uses WQX3.0 WQP services, which are in-development, use with caution.

Value

url string

Examples

```
site_ids <- c("USGS-02292010", "USGS-02276877")
startDate <- "2020-01-01"
endDate <- ""
pCode <- c("80154", "00613")
url_wqp <- constructWQPURL(
  site_ids,
  pCode,
  startDate, endDate
)
url_wqp
charNames <- c(
  "Temperature",
  "Temperature, sample",
  "Temperature, water",
  "Temperature, water, deg F"
)
obs_url_orig <- constructWQPURL(
  siteNumbers = c(
    "IIDFG-41WSSPAHS",
    "USGS-02352560"
  ),
  parameterCd = charNames,
  startDate, ""
)
obs_url_orig
```

---

countyCd *US County Code Lookup Table*

Description

Classic lookup table for counties. Has been replaced in functions with `check_waterdata_sample_params("counties")`.

Value

countyCd data frame.

Name	Type	Description
STUSAB	character	State abbreviation
STATE	character	two-digit ANSI code
COUNTY	character	three-digit county code
COUNTY_NAME	character	County full name
COUNTY_ID	character	County id

Examples

```
head(countyCd)
```

---

countyCdLookup *US county code look up*

Description

Function to simplify finding county and county code definitions. Used in `readNWISdata` and `readNWISuse`. Currently only has US counties.

Usage

```
countyCdLookup(state, county, outputType = "fips")
```

Arguments

`state`	could be character (full name, abbreviation, id), or numeric (id)
`county`	could be character (name, with or without "County") or numeric (id)
`outputType`	character can be "fullName", "tableIndex", "id", or "fullEntry".

Examples

```
fips <- countyCdLookup(state = "WI", county = "Dane")
id <- countyCdLookup(state = "WI", county = "Dane", outputType = "id")
name <- countyCdLookup(state = "OH", county = 13, output = "fullName")
entry <- countyCdLookup(state = "Pennsylvania", county = "ALLEGHENY COUNTY", output = "fullEntry")
fromIDs <- countyCdLookup(state = 13, county = 5, output = "fullName")
```

create_NWIS_bib *Create NWIS data citation*

Description

Uses attributes from the NWIS functions to create data citations.

Usage

```
create_NWIS_bib(x)
```

Arguments

x	Any data returned from an NWIS function, must include "queryTime" and "url" attributes, which should come with the data by default.

Details

See ?bibentry for more information.

Value

bibentry object to use for citing the data.

Examples

```
nwisData <- read_waterdata_daily(monitoring_location_id = "USGS-04085427",
                                 parameter_code = "00060",
                                 time = c("2012-01-01", "2012-06-30"))
nwis_citation <- create_NWIS_bib(nwisData)
nwis_citation

print(nwis_citation, style = "Bibtex")
print(nwis_citation, style = "citation")
```

create_WQP_bib *Create WQP data citation*

Description

Uses attributes from the WQP functions to create data citations.

Usage

```
create_WQP_bib(x)
```

Arguments

x	Any data returned from an NWIS function, must include "queryTime" and "url" attributes, which should come with the data by default.

Details

See ?bibentry for more information.

Value

bibentry object to use for citing the data.

Examples

```
# WQPData <- readWQPqw("USGS-05288705",
#                      parameterCd = "00300")
# wqp_citation <- create_WQP_bib(WQPData)
# wqp_citation

# print(wqp_citation, style = "Bibtex")
# print(wqp_citation, style = "citation")
```

---

findNLDI *R Client for the Network Linked Data Index*

Description

Provides a formal client to the USGS Network Linked Data Index.

Usage

```
findNLDI(
  comid = NULL,
  nwis = NULL,
  wqp = NULL,
  huc12 = NULL,
  location = NULL,
  origin = NULL,
  nav = NULL,
  find = c("flowlines"),
  distance_km = 100,
  no_sf = FALSE,
  warn = TRUE
)
```

Arguments

comid	numeric or character. An NHDPlusV2 COMID
nwis	numeric or character. A USGS NWIS surface water siteID
wqp	numeric or character. A water quality point ID
huc12	numeric or character. A WBD HUC12 unit ID
location	numeric vector. Coordinate pair in WGS84 SRS ordered lng/lat (X,Y)
origin	named list. Specifying a feature type and ID (e.g. list("comid" = 101))
nav	character vector. where to navigate from the starting point. Options include along the upper mainsteam (UM), upstream tributary (UT), downstream mainstem (DM) and downstream divergences (DD). You may select one or more of the abbreviations ("UM", "UT", DM", "DD").
find	character vector. Define what resources to find along the navigation path(s) (see get_nldi_sources()$source). Can also include 'basin' or 'flowline', which will return the upstream basin of the starting feature or flowlines along the navigation respectively. The default is "flowlines". If you provide any other resource, AND want flowlines, then flowlines must be explicitly requested.
distance_km	numeric. Define how far to look along the navigation path in kilometers (default = 100)
no_sf	if available, should sf be used for parsing, defaults to TRUE if sf is locally installed
warn	(default TRUE) should warnings be printed

Details

The function is useful for topology and location based feature discovery. A user must specify an origin feature, optional navigation direction(s) along the network, as well as features to identify along the navigated paths. Valid starting options can be given by one of the following arguments: comid, nwis, huc12, wqp, location, and start.

Value

a list of data.frames if sf is not installed, a list of sf objects if it is

Examples

```
# Find Features / Define origin features

## Find feature by COMID
findNLDI(comid = 101)

## Find feature by NWIS ID
findNLDI(nwis = "11120000")


## Find feature by LOCATION
```

```
findNLDI(location = c(-115, 40))

## GENERAL ORIGIN: COMID
findNLDI(origin = list("comid" = 101))

# Navigation (flowlines will be returned if find is unspecified)
# UPPER MAINSTEM of USGS-11120000
findNLDI(nwis = "11120000", nav = "UM")

# MULTI-REQUEST
# UPPER MAINSTEM and TRIBUTARY of USGS-11120000
findNLDI(nwis = "11120000", nav = c("UT", "UM"))

# Discover Features(flowlines will not be returned unless included in find)

## Find feature(s) on the upper tributary of USGS-11120000
findNLDI(nwis = "11120000", nav = "UT", find = c("nwis"))

## Find upstream basin boundary and  of USGS-11120000
findNLDI(nwis = "11120000", find = "basin")

# Control Distance
## Limit search to 50 km
findNLDI(comid = 101, nav = "DM", find = c("nwis", "flowlines"), distance_km = 50)
```

`getQuerySummary` *getting header information from a WQP query*

Description

getting header information from a WQP query

Usage

```
getQuerySummary(url)
```

Arguments

`url`	the query url

getWebServiceData *Function to return data from web services*

Description

This function accepts a url parameter, and returns the raw data.

Usage

```
getWebServiceData(obs_url, ...)
```

Arguments

obs_url	character containing the url for the retrieval
...	information to pass to header request

Details

To add a custom user agent, create an environmental variable: CUSTOM_DR_UA

Value

Returns xml, json, or text depending on the requested data.

Examples

```
siteNumber <- "02177000"
startDate <- "2012-09-01"
endDate <- "2012-10-01"
offering <- "00003"
property <- "00060"
obs_url <- constructNWISURL(siteNumber, property, startDate, endDate, "dv")

rawData <- getWebServiceData(obs_url)
```

get_monitoring_location_arguments *Get Monitoring Location Arguments*

Description

Many read_waterdata functions have a long list of arguments that can be used to find sites that have data. Users can use this function as a reference of possible arguments that can be used as input. Additionally, this function is also used by other functions to check that the user supplied parameters are available to their queries

Usage

```
get_monitoring_location_arguments(
  service = "daily",
  agency_code = NA_character_,
  agency_name = NA_character_,
  monitoring_location_number = NA_character_,
  monitoring_location_name = NA_character_,
  district_code = NA_character_,
  country_code = NA_character_,
  country_name = NA_character_,
  state_code = NA_character_,
  state_name = NA_character_,
  county_code = NA_character_,
  county_name = NA_character_,
  minor_civil_division_code = NA_character_,
  site_type_code = NA_character_,
  site_type = NA_character_,
  hydrologic_unit_code = NA_character_,
  basin_code = NA_character_,
  altitude = NA_character_,
  altitude_accuracy = NA_character_,
  altitude_method_code = NA_character_,
  altitude_method_name = NA_character_,
  vertical_datum = NA_character_,
  vertical_datum_name = NA_character_,
  horizontal_positional_accuracy_code = NA_character_,
  horizontal_positional_accuracy = NA_character_,
  horizontal_position_method_code = NA_character_,
  horizontal_position_method_name = NA_character_,
  original_horizontal_datum = NA_character_,
  original_horizontal_datum_name = NA_character_,
  drainage_area = NA_character_,
  contributing_drainage_area = NA_character_,
  time_zone_abbreviation = NA_character_,
  uses_daylight_savings = NA_character_,
  construction_date = NA_character_,
  aquifer_code = NA_character_,
  national_aquifer_code = NA_character_,
  aquifer_type_code = NA_character_,
  well_constructed_depth = NA_character_,
  hole_constructed_depth = NA_character_,
  depth_source_code = NA_character_,
  data_gap_interval = NA_character_,
  ...,
  check_arguments = FALSE
)
```

Arguments

service	Endpoint to check arguments against. Possible values are "daily", "latest-continuous", "field-measurements", "latest-daily", "latest-field-measurements", "continuous", "peaks".
agency_code	The agency that is reporting the data. Agency codes are fixed values assigned by the National Water Information System (NWIS). A list of agency codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/agency-codes/items.
agency_name	The name of the agency that is reporting the data.
monitoring_location_number	Each monitoring location in the USGS data base has a unique 8- to 15-digit identification number.
monitoring_location_name	This is the official name of the monitoring location in the database. For well information this can be a district-assigned local number.
district_code	The Water Science Centers (WSCs) across the United States use the FIPS state code as the district code. In some case, monitoring locations and samples may be managed by a water science center that is adjacent to the state in which the monitoring location actually resides. For example a monitoring location may have a district code of 30 which translates to Montana, but the state code could be 56 for Wyoming because that is where the monitoring location actually is located.
country_code	The code for the country in which the monitoring location is located.
country_name	The name of the country in which the monitoring location is located.
state_code	State code. A two-digit ANSI code (formerly FIPS code) as defined by the American National Standards Institute, to define States and equivalents. A three-digit ANSI code is used to define counties and county equivalents. A lookup table is available. The only countries with political subdivisions other than the US are Mexico and Canada. The Mexican states have US state codes ranging from 81-86 and Canadian provinces have state codes ranging from 90-98.
state_name	The name of the state or state equivalent in which the monitoring location is located.
county_code	The code for the county or county equivalent (parish, borough, etc.) in which the monitoring location is located. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/counties/items.
county_name	The name of the county or county equivalent (parish, borough, etc.) in which the monitoring location is located. [A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/counties/items.
minor_civil_division_code	Codes for primary governmental or administrative divisions of the county or county equivalent in which the monitoring location is located.
site_type_code	A code describing the hydrologic setting of the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/site-types/items.

site_type A description of the hydrologic setting of the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/site-types/items.

hydrologic_unit_code
The hydrologic unit code (HUC) for the monitoring location. Supports prefix matching — querying with a shorter HUC (e.g. "04") matches all locations within that hydrologic region.

basin_code The Basin Code or "drainage basin code" is a two-digit code that further subdivides the 8-digit hydrologic-unit code. The drainage basin code is defined by the USGS State Office where the monitoring location is located.

altitude Altitude of the monitoring location referenced to the specified Vertical Datum.

altitude_accuracy
Accuracy of the altitude, in feet. An accuracy of +/- 0.1 foot would be entered as ".1". Many altitudes are interpolated from the contours on topographic maps; accuracies determined in this way are generally entered as one-half of the contour interval.

altitude_method_code
Codes representing the method used to measure altitude.

altitude_method_name
The name of the method used to measure altitude.

vertical_datum The datum used to determine altitude and vertical position at the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/altitude-datums/items.

vertical_datum_name
The datum used to determine altitude and vertical position at the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/altitude-datums/items.

horizontal_positional_accuracy_code
Indicates the accuracy of the latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-accuracy-codes items.

horizontal_positional_accuracy
The agency that is reporting the data. Agency codes are fixed values assigned by the National Water Information System (NWIS). A list of agency codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/agency-codes/items.

horizontal_position_method_code
Indicates the method used to determine latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-method-codes/items.

horizontal_position_method_name
Indicates the method used to determine latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-method-codes/items.

original_horizontal_datum
Coordinates are published in EPSG:4326 / WGS84 / World Geodetic System 1984. This field indicates the original datum used to determine coordinates be-

fore they were converted. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-datum-codes/items.

original_horizontal_datum_name
: Coordinates are published in EPSG:4326 / WGS84 / World Geodetic System 1984. This field indicates the original datum used to determine coordinates before they were converted. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-datum-codes/items.

drainage_area
: The area enclosed by a topographic divide from which direct surface runoff from precipitation normally drains by gravity into the stream above that point.

contributing_drainage_area
: The contributing drainage area of a lake, stream, wetland, or estuary monitoring location, in square miles. This item should be present only if the contributing area is different from the total drainage area. This situation can occur when part of the drainage area consists of very porous soil or depressions that either allow all runoff to enter the groundwater or traps the water in ponds so that rainfall does not contribute to runoff. A transbasin diversion can also affect the total drainage area.

time_zone_abbreviation
: A short code describing the time zone used by a monitoring location.

uses_daylight_savings
: The agency that is reporting the data. Agency codes are fixed values assigned by the National Water Information System (NWIS). A list of agency codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/agency-codes/items.

construction_date
: Date the well was completed.

aquifer_code
: Local aquifers in the USGS water resources data base are identified by a geohydrologic unit code (a three-digit number related to the age of the formation, followed by a 4 or 5 character abbreviation for the geologic unit or aquifer name).

national_aquifer_code
: National aquifers are the principal aquifers or aquifer systems in the United States, defined as regionally extensive aquifers or aquifer systems that have the potential to be used as a source of potable water. Not all groundwater monitoring locations can be associated with a National Aquifer. Such monitoring locations will not be retrieved using this search criteria. A list of National aquifer codes and names is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/national-aquifer-codes/items.

aquifer_type_code
: The agency that is reporting the data. Agency codes are fixed values assigned by the National Water Information System (NWIS). A list of agency codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/agency-codes/items.

well_constructed_depth
: The depth of the finished well, in feet below land surface datum. Note: Not all groundwater monitoring locations have information on Well Depth. Such monitoring locations will not be retrieved using this search criteria.

hole_constructed_depth
: The total depth to which the hole is drilled, in feet below land surface datum. Note: Not all groundwater monitoring locations have information on Hole Depth. Such monitoring locations will not be retrieved using this search criteria.

depth_source_code
: A code indicating the source of water-level data.

data_gap_interval
: The time interval threshold used for gap detection in the time series.

...
: Not used. Used to make sure the user isn't passing in arguments that aren't available.

check_arguments
: Logical. Used to decide if the arguments passed in are available or not. The default is FALSE. Using TRUE will make two calls to the API, so if you are concerned with minimizing API calls, keep this value as FALSE. If you are concerned with making sure your calls are accepted by the service, set to TRUE.

Examples

```
get_monitoring_location_arguments(service = "daily", agency_name = "USGS")
get_monitoring_location_arguments(service = "field-measurements",
                                  state_name = c("Ohio", "Wisconsin"))
```

---

get_nldi_sources *Get current NLDI offerings*

Description

Used to query the current resources available through the NLDI

Usage

```
get_nldi_sources(url = getOption("dataRetrieval.nldi_base"))
```

Arguments

url
: URL for NLDI sources. Default is supplied by package environment.

Value

data.frame

Examples

```
get_nldi_sources()
```

get_ogc_params *Get parameter descriptions*

Description

This function returns a list of properties available from an endpoint. When available, it will also contain a description.

Usage

```
get_ogc_params(service, base = "OGC")
```

Arguments

service	Character, can be any of the USGS Waterdata API endpoints or collections.
base	Either "OGC" for waterdata, or "NGWMN" for National Groundwater Monitoring Network.

Value

list

Examples

```
ml <- dataRetrieval::get_ogc_params("monitoring-locations")
ml$national_aquifer_code
```

importNGWMN *Function to return data from the National Ground Water Monitoring Network waterML2 format*

Description

This function accepts a url parameter for a WaterML2 getObservation. This function is still under development, but the general functionality is correct.

Usage

```
importNGWMN(input, asDateTime = FALSE, tz = "UTC")
```

Arguments

input	character or raw, containing the url for the retrieval or a path to the data file, or raw XML.
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, character
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided time zone offset. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.

Value

mergedDF a data frame source, time, value, uom, uomTitle, comment, gmlID

Examples

```
params <- list(request = "GetObservation",
               service = "SOS",
               version = "2.0.0",
               observedProperty = "urn:ogc:def:property:OGC:GroundWaterLevel",
               responseFormat = "text/xml",
               featureOfInterest = "VW_GWDP_GEOSERVER.USGS.403836085374401")

obs_url <- httr2::request("https://cida.usgs.gov") |>
 httr2::req_url_path_append("ngwmn_cache") |>
 httr2::req_url_path_append("sos") |>
 httr2::req_url_query(!!!params)

#data_returned <- importNGWMN(obs_url)
```

---

importRDB1 *Function to return data from the NWIS RDB 1.0 format*

Description

This function accepts a url parameter that already contains the desired NWIS site, parameter code, statistic, startdate and enddate. It is not recommended to use the RDB format for importing multi-site data.

Usage

```
importRDB1(obs_url, asDateTime = TRUE, convertType = TRUE, tz = "UTC")
```

Arguments

obs_url	character containing the url for the retrieval or a file path to the data file.
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, Date
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character
tz	character to set timezone attribute of datetime. Default converts the datetimes to UTC (properly accounting for daylight savings times based on the data's provided tz_cd column). Recommended US values include "UTC", "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". For a complete list, see https://en.wikipedia.org/wiki/List_of_tz_database_time_zones

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
datetime	POSIXct	The date and time of the value converted to UTC (if asDateTime = TRUE
	character	or raw character string (if asDateTime = FALSE)
tz_cd	character	The time zone code for datetime
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter
tz_cd_reported	The originally reported time zone	

Note that code and value are repeated for the parameters requested. The names are of the form XD_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable). If a date/time (dt) column contained incomplete date and times, a new column of dates and time was inserted. This could happen when older data was reported as dates, and newer data was reported as a date/time.

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file

Examples

```
site_id <- "02177000"
startDate <- "2012-09-01"
endDate <- "2012-10-01"
offering <- "00003"
property <- "00060"

obs_url <- constructNWISURL(site_id, property,
  startDate, endDate, "dv",
  format = "tsv"
)

data <- importRDB1(obs_url)


urlMultiPcodes <- constructNWISURL("04085427", c("00060", "00010"),
  startDate, endDate, "dv",
  statCd = c("00003", "00001"), "tsv"
)

multiData <- importRDB1(urlMultiPcodes)

unitDataURL <- constructNWISURL(site_id, property,
  "2020-10-30", "2020-11-01", "uv",
  format = "tsv"
) # includes timezone switch

unitData <- importRDB1(unitDataURL, asDateTime = TRUE)

iceSite <- "04024000"
start <- "2015-11-09"
end <- "2015-11-24"
urlIce <- constructNWISURL(iceSite, "00060", start, end, "uv", format = "tsv")

ice <- importRDB1(urlIce, asDateTime = TRUE)
iceNoConvert <- importRDB1(urlIce, convertType = FALSE)

# User file:
filePath <- system.file("extdata", package = "dataRetrieval")
fileName <- "RDB1Example.txt"
fullPath <- file.path(filePath, fileName)
importUserRDB <- importRDB1(fullPath)
```

`importWaterML1` *Function to return data from the NWISWeb WaterML1.1 service*

Description

This function accepts a url parameter that already contains the desired NWIS site, parameter code, statistic, startdate and enddate.

Usage

```
importWaterML1(obs_url, asDateTime = FALSE, tz = "UTC")
```

Arguments

obs_url	character or raw, containing the url for the retrieval or a file path to the data file, or raw XML.
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, Date
tz	character to set timezone attribute of datetime. Default converts the datetimes to UTC (properly accounting for daylight savings times based on the data's provided tz_cd column). Recommended US values include "UTC", "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". For a complete list, see https://en.wikipedia.org/wiki/List_of_tz_database_time_zones

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
	POSIXct	The date and time of the value converted to UTC (if asDateTime = TRUE),
	character	or raw character string (if asDateTime = FALSE)
tz_cd	character	The time zone code for
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter

Note that code and value are repeated for the parameters requested. The names are of the form X_D_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable).

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
statisticInfo	data.frame	A data frame containing information on the requested statistics on the data
queryTime	POSIXct	The time the data was returned

See Also

renameNWISColumns()

Examples

```
site_id <- "02177000"
startDate <- "2012-09-01"
endDate <- "2012-10-01"
offering <- "00003"
property <- "00060"
obs_url <- constructNWISURL(site_id, property, startDate, endDate, "dv")

data <- importWaterML1(obs_url, asDateTime = TRUE)


unitDataURL <- constructNWISURL(
  site_id, property,
  "2013-11-03", "2013-11-03", "uv"
)
unitData <- importWaterML1(unitDataURL, TRUE)

# Two sites, two pcodes, one site has two data descriptors:
siteNumber <- c("01480015", "04085427")
obs_url <- constructNWISURL(
  siteNumber, c("00060", "00010"),
  startDate, endDate, "dv"
)
data <- importWaterML1(obs_url)
data$dateTime <- as.Date(data$dateTime)
data <- renameNWISColumns(data)
names(attributes(data))
attr(data, "url")
attr(data, "disclaimer")

inactiveSite <- "05212700"
inactiveSite <- constructNWISURL(inactiveSite, "00060",
                                 "2014-01-01", "2014-01-10", "dv")
inactiveSite <- importWaterML1(inactiveSite)

inactiveAndAcitive <- c("07334200", "05212700")
inactiveAndAcitive <- constructNWISURL(inactiveAndAcitive,
                         "00060", "2014-01-01", "2014-01-10", "dv")
inactiveAndAcitive <- importWaterML1(inactiveAndAcitive)

# Timezone change with specified local timezone:
tzURL <- constructNWISURL("04027000", c("00300", "63680"),
                          "2011-11-05", "2011-11-07", "uv")
tzIssue <- importWaterML1(tzURL,
  asDateTime = TRUE, tz = "America/Chicago"
)


filePath <- system.file("extdata", package = "dataRetrieval")
fileName <- "WaterML1Example.xml"
fullPath <- file.path(filePath, fileName)
importFile <- importWaterML1(fullPath, TRUE)
```

importWaterML2 *Parse the WaterML2 timeseries portion of a waterML2 file*

Description

Returns data frame columns of all information with each time series measurement; Anything defined as a default, is returned as an attribute of that data frame.

Usage

```
importWaterML2(input, asDateTime = FALSE, tz = "UTC")
```

Arguments

input	XML with only the wml2:MeasurementTimeseries node and children
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, character
tz	character to set timezone attribute of datetime. Default is an empty quote, which converts the datetimes to UTC (properly accounting for daylight savings times based on the data's provided time zone offset). Possible values are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla"

Examples

```
baseURL <- httr2::request("https://waterservices.usgs.gov/nwis/dv")
baseURL <- httr2::req_url_query(baseURL,
                                format = "waterml,2.0",
                                sites = "01646500",
                                startDT = "2014-09-01",
                                endDT = "2014-09-08",
                                statCd = "00003",
                                parameterCd = "00060" )

timeseries <- importWaterML2(baseURL, asDateTime = TRUE, tz = "UTC")
```

importWQP *Basic Water Quality Portal Data parser*

Description

Imports data from the Water Quality Portal based on a specified url.

Usage

```
importWQP(obs_url, tz = "UTC", csv = TRUE, convertType = TRUE)
```

Arguments

obs_url	character URL to Water Quality Portal#' @keywords data import USGS web service
tz	character to set timezone attribute of datetime. Default is UTC (properly accounting for daylight savings times based on the data's provided tz_cd column). Possible values include "America/New_York","America/Chicago", "America/Denver","America/Los_An "America/Anchorage","America/Honolulu","America/Jamaica","America/Managua", "America/Phoenix", and "America/Metlakatla"
csv	logical. Is the data coming back with a csv or tsv format. Default is FALSE. Currently, the summary service does not support tsv, for other services tsv is the safer choice.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character.

Value

retval dataframe raw data returned from the Water Quality Portal. Additionally, a POSIXct dateTime column is supplied for start and end times, and converted to UTC. See https://www.waterqualitydata.us/portal_userguide/ for more information.

See Also

readWQPdata(), readWQPqw(), whatWQPsites()

Examples

```
# These examples require an internet connection to run

## Examples take longer than 5 seconds:

rawSampleURL <- constructWQPURL("USGS-01594440", "01075", "", "")

rawSample <- importWQP(rawSampleURL)
```

```
STORETex <- constructWQPURL("WIDNR_WQX-10032762", "Specific conductance", "", "")

STORETdata <- importWQP(STORETex)

STORETdata_char <- importWQP(STORETex, convertType = FALSE)
```

---

is_dataRetrieval_user *Is this a dataRetrieval user*

Description

Reveals if this is a user or not

Usage

```
is_dataRetrieval_user()
```

Examples

```
is_dataRetrieval_user()
```

---

parameterCdFile *List of USGS parameter codes*

Description

Complete list of USGS parameter codes as of Oct. 24, 2024.

Value

parameterData data frame with information about USGS parameters.

Name	Type	Description
parameter_cd	character	5-digit USGS parameter code
parameter_group_nm	character	USGS parameter group name
parameter_nm	character	USGS parameter name
casrn	character	Chemical Abstracts Service (CAS) Registry Number
srsname	character	Substance Registry Services Name
parameter_units	character	Parameter units

Examples

```
head(parameterCdFile[, 1:2])
```

parse_WQP *Convert WQP columns to correct types*

Description

Takes the character results and converts to numeric and dates.

Usage

```
parse_WQP(retval, tz = "UTC")
```

Arguments

retval	Data frame from WQP
tz	character to set timezone attribute of datetime. Default is UTC (properly accounting for daylight savings times based on the associated "TimeZone" column). Possible values include "America/New_York","America/Chicago", "America/Denver","America/Los_Angeles", "America/Anchorage","America/Honolulu","America/Jamaica","A "America/Phoenix", and "America/Metlakatla"

Value

data frame retval with converted columns

Examples

```
# These examples require an internet connection to run
rawSampleURL <- constructWQPURL("USGS-01594440", "01075", "", "")

## Examples take longer than 5 seconds:


rawSample <- importWQP(rawSampleURL, convertType = FALSE)
convertedSample <- parse_WQP(rawSample)
```

pcode_to_name *Parameter code to characteristic name*

Description

This function no longer works because the underlying service has been removed. Similar functionality can be found with `check_waterdata_sample_params`.

Usage

```
pcode_to_name(parameterCd = "all")
```

Arguments

`parameterCd`	character that contains the code for a character vector of 5-digit parameter codes.

Examples

```
pcodes <- c("00070", "00075", "00430", "52642")

all_new <- read_waterdata_parameter_codes(parameter_code = pcodes)
ref_list <- check_waterdata_sample_params("reference-list")
ref_list_sm <- ref_list[ref_list$parm_cd %in% pcodes, ]
```

readNWISdata *General Data Import from NWIS*

Description

Returns data from the NWIS web service. Arguments to the function should be based on https://waterservices.usgs.gov service calls. See examples below for ideas of constructing queries.

Usage

```
readNWISdata(
  ...,
  asDateTime = TRUE,
  convertType = TRUE,
  tz = "UTC",
  override_error = FALSE
)
```

Arguments

...	see https://waterservices.usgs.gov/docs/site-service/ for a complete list of options. A list of arguments can also be supplied. One important argument to include is "service". Possible values are "iv" (for instantaneous), "dv" (for daily values), "site" (for site service), and "stat" (for statistics service). The statistics service has a limited selection of arguments (see https://waterservices.usgs.gov/docs/site-service/).
asDateTime	logical, if TRUE returns date and time as POSIXct, if FALSE, Date
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also OlsonNames() for more information on time zones.
override_error	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to TRUE should only be used as a tool to convert readNWIS to read_waterdata functions.

Details

This function requires users to create their own arguments based on the NWIS web services. It is a more complicated function to use compared to other NWIS functions such as readNWISdv(), readNWISuv(), etc. However, this function adds a lot of flexibility to the possible queries. This function will also behave exactly as NWIS when it comes to date queries. NWIS by default will only return the latest value for the daily and instantaneous services. So if you do not provide a starting date, you will only get back the latest value. If you want the full period of record, you can use "startDate = '1900-01-01'". Other options for dates are periods, such as "period = 'P7D'" which translates to a period of 7 days. For period, use only a positive ISO-8601 duration format, which should not be expressed in periods of less than a day, or in increments of months M or years Y. period returns data for a site generally from now to a time in the past. Note that when period is used all data up to the most recent value are returned.

Value

A data frame with the following columns:

Name	Type	Description
agency	character	The NWIS code for the agency reporting the data
site	character	The USGS site number
dateTime	POSIXct	The date and time (if applicable) of the measurement, converted to UTC for unit value data. R only al
tz_cd	character	The time zone code for dateTime column

code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter

Note that code and value are repeated for the parameters requested. The names are of the form X_D_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable).

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
statisticInfo	data.frame	A data frame containing information on the requested statistics on the data
queryTime	POSIXct	The time the data was returned

See Also

`read_waterdata()`

`readNWISdv` *Daily Value USGS NWIS Data Retrieval*

Description

Imports data from NWIS daily web service. This function gets the data from here: https://waterservices.usgs.gov/docs/dv-service/daily-values-service-details/ Inputs to this function are just USGS site ids, USGS parameter codes, USGS statistic codes, and start and end date. For a more complex query, use `readNWISdata()`, with an argument service = "dv". Data coming the daily web services are aggregates of the instantaneous (sensor) web services. Not all statistical codes are available for all data. Use the function `whatNWISdata()` to discover what data is available for a USGS site. The column data_type_cd with the values "dv" returned from `whatNWISdata()`) are available from this service.

Usage

```
readNWISdv(
  siteNumbers,
  parameterCd,
  startDate = "",
  endDate = "",
  statCd = "00003",
  override_error = FALSE
)
```

Arguments

siteNumbers	character USGS site number. This is usually an 8 digit number. Multiple sites can be requested with a character vector.
parameterCd	character of USGS parameter code(s). This is usually an 5 digit number.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record. Date arguments are always specified in local time.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. Date arguments are always specified in local time.
statCd	character USGS statistic code. This is usually 5 digits. Daily mean (00003) is the default.
override_error	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to TRUE should only be used as a tool to convert readNWIS to read_waterdata functions.

Details

More information on the web service can be found here: https://waterservices.usgs.gov/test-tools, choosing the "Daily Value Service".

Value

A data frame with the following columns:

Name	Type	Description
agency	character	The NWIS code for the agency reporting the data
site	character	The USGS site number
Date	Date	The date of the value
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter

Note that code and value are repeated for the parameters requested. The names are of the form X_D_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable).

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
statisticInfo	data.frame	A data frame containing information on the requested statistics on the data
queryTime	POSIXct	The time the data was returned

See Also

read_waterdata_daily()

---

readNWISpCode *USGS Parameter Data Retrieval*

Description

Imports data from NWIS about measured parameter based on user-supplied parameter code or codes.

Usage

```
readNWISpCode(parameterCd, override_error = FALSE)
```

Arguments

parameterCd	character of USGS parameter codes (or multiple parameter codes). These are 5 digit number codes. To get a complete list of all current parameter codes in the USGS, use "all" as the input.
override_error	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to TRUE should only be used as a tool to convert readNWIS to read_waterdata functions.

Value

parameterData data frame with the following information:

Name	Type	Description
parameter_cd	character	5-digit USGS parameter code
parameter_group_nm	character	USGS parameter group name
parameter_nm	character	USGS parameter name
casrn	character	Chemical Abstracts Service (CAS) Registry Number
srsname	character	Substance Registry Services Name
parameter_units	character	Parameter units

See Also

importRDB1()

`readNWISpeak` *Peak flow data from USGS (NWIS)*

Description

Reads peak flow from NWISweb.

Usage

```
readNWISpeak(
  siteNumbers,
  startDate = "",
  endDate = "",
  asDateTime = TRUE,
  convertType = TRUE,
  override_error = FALSE
)
```

Arguments

`siteNumbers`	character USGS site number(or multiple sites). This is usually an 8 digit number.
`startDate`	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record.
`endDate`	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record.
`asDateTime`	logical default to `TRUE`. When `TRUE`, the peak_dt column is converted to a Date object, and incomplete dates are removed. When `FALSE`, no columns are removed, but no dates are converted.
`convertType`	logical, defaults to `TRUE`. If `TRUE`, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character
`override_error`	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to `TRUE` should only be used as a tool to convert readNWIS to read_waterdata functions.

Details

In some cases, the specific date of the peak data is not know. This function will default to converting complete dates to a "Date" object, and converting incomplete dates to "NA". If those incomplete dates are needed, set the `asDateTime` argument to FALSE. No dates will be converted to R Date objects.

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
peak_dt	Date	Date of peak streamflow
peak_tm	character	Time of peak streamflow as character
peak_va	numeric	Annual peak streamflow value in cfs
peak_cd	character	Peak Discharge-Qualification codes (see `comment` for more information)
gage_ht	numeric	Gage height for the associated peak streamflow in feet
gage_ht_cd	character	Gage height qualification codes
year_last_pk	numeric	Peak streamflow reported is the highest since this year
ag_dt	Date	Date of maximum gage-height for water year (if not concurrent with peak)
ag_tm	character	Time of maximum gage-height for water year (if not concurrent with peak)
ag_gage_ht	numeric	maximum Gage height for water year in feet (if not concurrent with peak)
ag_gage_ht_cd	character	maximum Gage height code

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file
siteInfo	data.frame	A data frame containing information on the requested sites

See Also

`constructNWISURL()`, `importRDB1()`

Examples

```
#site_ids <- c("01594440", "040851325")

#data <- readNWISpeak(site_ids)
#data2 <- readNWISpeak(site_ids, asDateTime = FALSE)
#stations <- c("06011000")
#peakdata <- readNWISpeak(stations, convertType = FALSE)
```

`readNWISrating` *Rating table for an active USGS streamgage retrieval*

Description

Reads current rating table for an active USGS streamgage from NWISweb.

Usage

```
readNWISrating(
  siteNumber,
  type = "base",
  convertType = TRUE,
  override_error = FALSE
)
```

Arguments

`siteNumber`	character USGS site number. This is usually an 8 digit number
`type`	character can be "base", "corr", or "exsa"
`convertType`	logical, defaults to `TRUE`. If `TRUE`, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character
`override_error`	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to `TRUE` should only be used as a tool to convert readNWIS to read_waterdata functions.

Value

A data frame. If `type` is "base, " then the columns are INDEP, typically the gage height, in feet; DEP, typically the streamflow, in cubic feet per second; and STOR, where "*" indicates that the pair are a fixed point of the rating curve. If `type` is "exsa, " then an additional column, SHIFT, is included that indicates the current shift in the rating for that value of INDEP. If `type` is "corr, " then the columns are INDEP, typically the gage height, in feet; CORR, the correction for that value; and CORRINDEP, the corrected value for CORR.
If `type` is "base, " then the data frame has an attribute called "RATING" that describes the rating curve is included.

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file
siteInfo	data.frame	A data frame containing information on the requested sites
RATING	character	Rating information

Note

Not all active USGS streamgages have traditional rating curves that relate flow to stage.

See Also

constructNWISURL(), importRDB1()

Examples

```
site_id <- "01594440"

#data <- readNWISrating(site_id, "base")
#attr(data, "RATING")
```

---

readNWISsite *USGS Site File Data Retrieval*

Description

Imports data from USGS site file site. This function gets data from here: https://waterservices.usgs.gov/

Usage

```
readNWISsite(siteNumbers, override_error = FALSE)
```

Arguments

siteNumbers	character USGS site number (or multiple sites). This is usually an 8 digit number
override_error	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to TRUE should only be used as a tool to convert readNWIS to read_waterdata functions.

Value

A data frame with at least the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
station_nm	character	Site name
site_tp_cd	character	Site type

lat_va	numeric	DMS latitude
long_va	numeric	DMS longitude
dec_lat_va	numeric	Decimal latitude
dec_long_va	numeric	Decimal longitude
coord_meth_cd	character	Latitude-longitude method
coord_acy_cd	character	Latitude-longitude accuracy
coord_datum_cd	character	Latitude-longitude datum
dec_coord_datum_cd	character	Decimal Latitude-longitude datum
district_cd	character	District code
state_cd	character	State code
county_cd	character	County code
country_cd	character	Country code
land_net_ds	character	Land net location description
map_nm	character	Name of location map
map_scale_fc	character	Scale of location map
alt_va	numeric	Altitude of Gage/land surface
alt_meth_cd	character	Method altitude determined
alt_acy_va	numeric	Altitude accuracy
alt_datum_cd	character	Altitude datum
huc_cd	character	Hydrologic unit code
basin_cd	character	Drainage basin code
topo_cd	character	Topographic setting code
instruments_cd	character	Flags for instruments at site
construction_dt	character	Date of first construction
inventory_dt	character	Date site established or inventoried
drain_area_va	numeric	Drainage area
contrib_drain_area_va	numeric	Contributing drainage area
tz_cd	character	Time Zone abbreviation
local_time_fg	character	Site honors Daylight Savings Time
reliability_cd	character	Data reliability code
gw_file_cd	character	Data-other GW files
nat_aqfr_cd	character	National aquifer code
aqfr_cd	character	Local aquifer code
aqfr_type_cd	character	Local aquifer type code
well_depth_va	numeric	Well depth
hole_depth_va	numeric	Hole depth
depth_src_cd	character	Source of depth data
project_no	character	Project number

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned
comment	character	Header comments from the RDB file

See Also

read_waterdata_monitoring_location()

Examples

```
# see ?read_waterdata_monitoring_location
# siteINFOMulti <- readNWISsite(c("05114000", "09423350"))
```

---

readNWISstat *Site statistics retrieval from USGS (NWIS)*

Description

Retrieves site statistics from the USGS Statistics Web Service beta.

Usage

```
readNWISstat(
  siteNumbers,
  parameterCd,
  startDate = "",
  endDate = "",
  convertType = TRUE,
  statReportType = "daily",
  statType = "mean",
  override_error = FALSE
)
```

Arguments

siteNumbers	character USGS site number (or multiple sites). This is usually an 8 digit number.
parameterCd	character USGS parameter code. This is usually a 5 digit number.
startDate	character starting date for data retrieval in the form YYYY, YYYY-MM, or YYYY-MM-DD. Dates cannot be more specific than the statReportType, i.e. startDate for monthly statReportTypes cannot include days, and annual statReportTypes cannot include days or months. Months and days are optional for the daily statReportType. Default is "" which indicates retrieval for the earliest possible record. For daily data, this indicates the start of the period the statistics will be computed over.
endDate	character ending date for data retrieval in the form YYYY, YYYY-MM, or YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. For daily data, this indicates the end of the period the statistics will be computed over. The same restrictions as startDate apply.

convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to numerics based on a standard algorithm. Years, months, and days (if appliccable) are also returned as numerics in separate columns. If convertType is false, everything is returned as a character.
statReportType	character time division for statistics: daily, monthly, or annual. Default is daily. Note that daily provides statistics for each calendar day over the specified range of water years, i.e. no more than 366 data points will be returned for each site/parameter. Use readNWISdata or readNWISdv for daily averages. Also note that 'annual' returns statistics for the calendar year. Use readNWISdata for water years. Monthly and yearly provide statistics for each month and year within the range indivually.
statType	character type(s) of statistics to output for daily values. Default is mean, which is the only option for monthly and yearly report types.
override_error	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to TRUE should only be used as a tool to convert readNWIS to read_waterdata functions.

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency repor
site_no	character	The USGS site number
parameter_cd	character	The USGS parameter code

Other columns will be present depending on statReportType and statType

See Also

constructNWISURL(), importRDB1()

Examples

```
# x1 <- readNWISstat(
#   siteNumbers = c("02319394"),
#   parameterCd = c("00060"),
#   statReportType = "annual"
# )

# all the annual mean discharge data for two sites
#x2 <- readNWISstat(
#   siteNumbers = c("02319394", "02171500"),
#   parameterCd = c("00010", "00060"),
#   statReportType = "annual"
# )

# Request p25, p75, and mean values for temperature and discharge for the 2000s
# Note that p25 and p75 were not available for temperature, and return NAs
```

```
#x <- readNWISstat(
#   siteNumbers = c("02171500"),
#   parameterCd = c("00010", "00060"),
#   statReportType = "daily",
#   statType = c("mean", "median"),
#   startDate = "2000", endDate = "2010"
# )
```

---

readNWISuv *Instantaneous value data retrieval from USGS (NWIS)*

Description

Imports data from NWIS web service. Inputs to this function are USGS site ids, USGS parameter codes, and start and end date. For a more complex query, use readNWISdata(), including an arguement service="uv". Not all parameter codes are available for all data. Use the function whatNWISdata() to discover what data is available for a USGS site. The column data_type_cd with the values "uv" returned from whatNWISdata()) are available from this service.

Usage

```
readNWISuv(
  siteNumbers,
  parameterCd,
  startDate = "",
  endDate = "",
  tz = "UTC",
  override_error = FALSE
)
```

Arguments

siteNumbers	character USGS site number (or multiple sites). This is usually an 8 digit number
parameterCd	character USGS parameter code. This is usually an 5 digit number.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record. Simple date arguments are specified in local time.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. Simple date arguments are specified in local time.
tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data provided tz_cd column. Possible values to provide are "America/New_York", "America/Chicago", "America/Denver", "America/Los_Angeles",

"America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica", "America/Managua", "America/Phoenix", and "America/Metlakatla". See also `OlsonNames()` for more information on time zones.

`override_error` Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to `TRUE` should only be used as a tool to convert readNWIS to read_waterdata functions.

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
dateTime	POSIXct	The date and time of the value converted to UTC
tz_cd	character	The time zone code for dateTime
code	character	Any codes that qualify the corresponding value
value	numeric	The numeric value for the parameter

Note that code and value are repeated for the parameters requested. The names are of the form: X_D_P_S, where X is literal, D is an option description of the parameter, P is the parameter code, and S is the statistic code (if applicable).

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
statisticInfo	data.frame	A data frame containing information on the requested statistics on the data
queryTime	POSIXct	The time the data was returned

See Also

`renameNWISColumns()`, `importWaterML1()`

Examples

```
site_id <- "05114000"
parameterCd <- "00060"
startDate <- "2014-10-10"
endDate <- "2014-10-10"


#rawData <- readNWISuv(site_id, parameterCd, startDate, endDate)
```

```
#rawData_today <- readNWISuv(site_id, parameterCd, Sys.Date(), Sys.Date())
```

`readWQPdata` *General Data Import from Water Quality Portal*

Description

Imports data from Water Quality Portal web service. This function gets the data from here: https://www.waterqualitydata.us.

Usage

```
readWQPdata(
  ...,
  service = "Result",
  querySummary = FALSE,
  tz = "UTC",
  ignore_attributes = FALSE,
  convertType = TRUE
)
```

Arguments

`...`	A list of arguments can also be supplied. For more information see the above description for this help file. One way to figure out how to construct a WQP query is to go to the "Advanced" form in the Water Quality Portal. Use the form to discover what parameters are available. Once the query is set in the form, scroll down to the "Query URL". You will see the parameters after "https://www.waterqualitydata.us/#". For example, if you chose "Nutrient" in the Characteristic Group dropdown, you will see characteristicType=Nutrient in the Query URL. The corresponding argument for dataRetrieval is characteristicType = "Nutrient". dataRetrieval users do not need to include mimeType, and providers is optional (these arguments are picked automatically).
`service`	character. See Details for more information.
`querySummary`	logical to only return the number of records and unique sites that will be returned from this query. Choosing TRUE is deprecated, readWQPsummary is recommended instead.
`tz`	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data's provided tz_cd column. Possible values to provide are "America/New_York","America/Chicago", "America/Denver","America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica","America/Managua","America/Phoenix", and "America/Metlakatla". See also `OlsonNames()` for more information on time zones.

`ignore_attributes`
: logical to choose to ignore fetching site and status attributes. Default is `FALSE`.

`convertType`
: logical, defaults to `TRUE`. If `TRUE`, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character.

Details

This function uses ... as a query input, which can be very flexible, but also has a steeper learning curve. For a quick overview, scroll down to the Examples in this help file to see many query options.

There are currently 10 legacy options for data provided by the Water Quality Portal:

Legacy:

WQP Radio Button	service argument	Base URL
Sample Results	Result	/data/Result/search
Site Data Only	Station	/data/Station/search
Sampling Activity	Activity	/data/Activity/search
Sampling Activity Metrics	ActivityMetric	/data/ActivityMetric/search
Site Summary (not advertised on WQP)	SiteSummary	/data/summary/monitoringLocation/se
Project Data	Project	/data/Project/search
Project Monitoring Location Weighting Data	ProjectMonitoringLocationWeighting	/data/ProjectMonitoringLocationWeig
Result Detection Quantitation Limit Data	ResultDetectionQuantitationLimit	/data/ResultDetectionQuantitationLim
Biological Habitat Metrics	BiologicalMetric	/data/BiologicalMetric/search
Organization Data	Organization	/data/Organization/search

There are 5 WQX3 options. These are still in-development, and should be used with caution.

WQP Radio Button	service argument	Base URL	dataProfile
Monitoring Locations	StationWQX3	/wqx3/Station/search	
Full Physical Chemical	ResultWQX3	/wqx3/Result/search	fullPhysChem
Narrow	ResultWQX3	/wqx3/Result/search	narrow
Basic Physical Chemical	ResultWQX3	/wqx3/Result/search	basicPhysChem
Sampling Activity	ActivityWQX3	/wqx3/Activity/search	

Value

A data frame, the specific columns will depend on the "service" and/or "dataProfile".

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
headerInfo	data.frame	A data frame returned from the WQP status service
queryTime	POSIXct	The time the data was returned

Examples

```
# Legacy:
#nameToUse <- "pH"
#pHData <- readWQPdata(siteid = "USGS-04024315",
#                      characteristicName = nameToUse)
#ncol(pHData)
#attr(pHData, "siteInfo")
#attr(pHData, "queryTime")
#attr(pHData, "url")

# WQX3:
#pHData_wqx3 <- readWQPdata(siteid = "USGS-04024315",
#                           characteristicName = nameToUse,
#                           service = "ResultWQX3",
#                           dataProfile = "basicPhysChem")
# attr(pHData_wqx3, "url")

# More examples:
# querying by county
#DeWitt <- readWQPdata(
#   statecode = "Illinois",
#   countycode = "DeWitt",
#   characteristicName = "Nitrogen"
# )

#attr(DeWitt, "url")

#DeWitt_wqx3 <- readWQPdata(
#    statecode = "Illinois",
#    countycode = "DeWitt",
#    characteristicName = "Nitrogen",
#    service = "ResultWQX3",
#    dataProfile = "basicPhysChem",
#    ignore_attributes = TRUE)

#attr(DeWitt_wqx3, "url")

# Data profile: "Sampling Activity"
#activity <- readWQPdata(
#   siteid = "USGS-04024315",
#   service = "Activity"
#)
#attr(activity, "url")

# activity_wqx3 <- readWQPdata(
#   siteid = "USGS-04024315",
#   service = "ActivityWQX3"
# )
# attr(activity_wqx3, "url")
```

```
#Dane_activity <- readWQPdata(
#   statecode = "Wisconsin",
#   countycode = "Dane",
#   startDateLo = "2023-01-01",
#   startDateHi = "2023-12-31",
#   service = "Activity"
# )
#attr(Dane_activity, "url")

# Dane_activity_wqx3 <- readWQPdata(
#   statecode = "Wisconsin",
#   countycode = "Dane",
#   startDateLo = "2023-01-01",
#   startDateHi = "2023-12-31",
#   service = "ActivityWQX3"
# )
# attr(Dane_activity_wqx3, "url")

########################################################
# Additional examples:


# Data profiles: "Organization Data"
#org_data <- readWQPdata(
#   statecode = "WI",
#   countycode = "Dane",
#   service = "Organization"
# )

# Data profiles: "Project Data"
#project_data <- readWQPdata(
#   statecode = "WI",
#   countycode = "Dane",
#   service = "Project"
# )

# Data profiles: "Project Monitoring Location Weighting Data"
#proj_mlwd <- readWQPdata(
#   statecode = "WI",
#   countycode = "Dane",
#   service = "ProjectMonitoringLocationWeighting"
# )

# Data profiles: "Sample Results (physical/chemical metadata)"
# samp_data <- readWQPdata(
#   siteid = "USGS-04024315",
#   dataProfile = "resultPhysChem",
#   service = "Result"
# )

# Data profiles: "Sample Results (biological metadata)"
#samp_bio <- readWQPdata(
#   siteid = "USGS-04024315",
```

```
#   dataProfile = "biological",
#   service = "Result"
# )


# Data profiles: "Sample Results (narrow)"
# samp_narrow <- readWQPdata(
#   siteid = "USGS-04024315",
#   service = "Result",
#   dataProfile = "narrowResult"
# )

# samp_narrow_wqx3 <- readWQPdata(
#   siteid = "USGS-04024315",
#   service = "ResultWQX3",
#   dataProfile = "narrow"
# )


# Data profiles: "Sampling Activity"
#samp_activity <- readWQPdata(
#   siteid = "USGS-04024315",
#   dataProfile = "activityAll",
#   service = "Activity"
#  )

# Data profile: "Sampling Activity Metrics"
# act_metrics <- readWQPdata(
#   statecode = "WI",
#   countycode = "Dane",
#   service = "ActivityMetric"
# )

# Data profile: "Result Detection Quantitation Limit Data"
# dl_data <- readWQPdata(
#   siteid = "USGS-04024315",
#   service = "ResultDetectionQuantitationLimit"
# )

# other options:
# Phosphorus <- readWQPdata(
#   statecode = "WI", countycode = "Dane",
#   characteristicName = "Phosphorus",
#   startDateLo = "2023-01-01",
#   ignore_attributes = TRUE,
#   convertType = FALSE
# )

#rawPHsites_legacy <- readWQPdata(siteid = c("USGS-05406450", "USGS-05427949", "WIDNR_WQX-133040"),
#                          characteristicName = "pH",
#                          service = "Result",
#                          dataProfile = "narrowResult" )
```

```
# rawPHsites <- readWQPdata(siteid = c("USGS-05406450", "USGS-05427949", "WIDNR_WQX-133040"),
#                           characteristicName = "pH",
#                           service = "ResultWQX3",
#                           dataProfile = "narrow" )
```

---

readWQPqw *Raw Data Import for Water Quality Portal*

Description

Imports data from the Water Quality Portal. This function gets the data from here: https://www.waterqualitydata.us. There are four required input arguments: siteNumbers, parameterCd, startDate, and endDate. parameterCd can either be a USGS 5-digit code, or a characteristic name. The sites can be either USGS, or other Water Quality Portal offered sites. It is required to use the 'full' site name, such as 'USGS-01234567'.

Usage

```
readWQPqw(
  siteNumbers,
  parameterCd,
  startDate = "",
  endDate = "",
  tz = "UTC",
  legacy = TRUE,
  querySummary = FALSE,
  ignore_attributes = FALSE,
  convertType = TRUE
)
```

Arguments

siteNumbers	character site number. This needs to include the full agency code prefix.
parameterCd	vector of USGS 5-digit parameter code or characteristicNames. Leaving this blank will return all of the measured values during the specified time period.
startDate	character starting date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the earliest possible record. Date arguments are always specified in local time.
endDate	character ending date for data retrieval in the form YYYY-MM-DD. Default is "" which indicates retrieval for the latest possible record. Date arguments are always specified in local time.

tz	character to set timezone attribute of dateTime. Default is "UTC", and converts the date times to UTC, properly accounting for daylight savings times based on the data provided tz_cd column. Possible values to provide are "America/New_York","America/Chicago", "America/Denver","America/Los_Angeles", "America/Anchorage", as well as the following which do not use daylight savings time: "America/Honolulu", "America/Jamaica","America/Managua","America/Phoenix", and "America/Metlakatla". See also `OlsonNames()` for more information on time zones.
legacy	Logical. If TRUE, uses legacy WQP services. Default is TRUE. Setting legacy = FALSE uses WQX3.0 WQP services, which are in-development, use with caution.
querySummary	logical to look at number of records and unique sites that will be returned from this query.
ignore_attributes	logical to choose to ignore fetching site and parameter attributes. Default is `FALSE`.
convertType	logical, defaults to `TRUE`. If `TRUE`, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character.

Value

A data frame derived from the default data profile.

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
siteInfo	data.frame	A data frame containing information on the requested sites
variableInfo	data.frame	A data frame containing information on the requested parameters
queryTime	POSIXct	The time the data was returned

See Also

`readWQPdata()`, `whatWQPsites()`, and `importWQP()`

Examples

```
#rawPcode <- readWQPqw("USGS-01594440", "01075", "", "")

#attr(rawPcode, "siteInfo")
#attr(rawPcode, "queryTime")
#attr(rawPcode, "url")

#rawCharacteristicName <- readWQPqw("WIDNR_WQX-10032762", "Specific conductance", "", "")
#pHsites_legacy <- readWQPqw(c("USGS-05406450", "USGS-05427949", "WIDNR_WQX-133040"),
#                            "pH", "", "")
#ncol(pHsites_legacy)
```

```
#attr(pHsites_legacy, "url")

# pHsites_modern <- readWQPqw(c("USGS-05406450", "USGS-05427949", "WIDNR_WQX-133040"),
#                          "pH", "", "", legacy = FALSE)
# ncol(pHsites_modern)
# attr(pHsites_modern, "url")

# nwisEx <- readWQPqw("USGS-04024000", c("34247", "30234", "32104", "34220"), "", "2022-12-20")

# DO <- readWQPqw(siteNumbers = "USGS-05288705",
#                 parameterCd = "00300",
#                 convertType = FALSE)
```

`readWQPsummary` *Summary of Data Available from Water Quality Portal*

Description

Returns a list of sites with year-by-year information on what data is available. The function gets the data from: https://www.waterqualitydata.us. The information returned from this function describes the available data at the WQP sites, and some metadata on the sites themselves.

Usage

```
readWQPsummary(...)
```

Arguments

...	Named arguments. A list of arguments can also be supplied. One way to figure out how to construct a WQP query is to go to the "Advanced" form in the Water Quality Portal. Use the form to discover what parameters are available. Once the query is set in the form, scroll down to the "Query URL". You will see the parameters after "https://www.waterqualitydata.us/#". For example, if you chose "Nutrient" in the Characteristic Group dropdown, you will see characteristicType=Nutrient in the Query URL. The corresponding argument for dataRetrieval is characteristicType = "Nutrient". dataRetrieval users do not need to include mimeType, and providers is optional (these arguments are picked automatically).

Value

A data frame from the data returned from the Water Quality Portal about the data available for the query parameters.

See Also

whatWQPsites whatWQPdata

Examples

```
# Summary of a single site for the last 5 years:
#site_5 <- readWQPsummary(
#   siteid = "USGS-07144100",
#   summaryYears = 5
#  )

# Summary of a single site for the full period of record:
#site_all <- readWQPsummary(
#   siteid = "USGS-07144100",
#   summaryYears = "all"
# )

# Summary of the data available from streams in a single county:
# dane_county_data <- readWQPsummary(
#   countycode = "US:55:025",
#   summaryYears = 5,
#   siteType = "Stream"
# )

# Summary of the data all available from lakes in a single county:
# lake_sites <- readWQPsummary(
#   siteType = "Lake, Reservoir, Impoundment",
#   countycode = "US:55:025"
# )

# Summary of the data available for the last 5 years in New Jersey:
#state1 <- readWQPsummary(
#   statecode = "NJ",
#   summaryYears = 5,
#    siteType = "Stream"
# )
```

`read_ngwmn` *Generalized NGWMN API retrieval function*

Description

Function that allows complex CQL queries on National Groundwater Monitoring Network API. See https://api.waterdata.usgs.gov/docs/ogcapi/complex-queries/ for more information.

Usage

```
read_ngwmn(
  service,
  CQL = NA_character_,
```

```
  monitoring_location_id = NA_character_,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

service	character, can be any existing collection. Can be: "providers", "constructionObs", "waterLevelObs", "sites", or "lithologyObs". The date of an observation. Date and time expressions adhere to RFC 3339. Intervals may be bounded or half-bounded (double-dots at start or end). Examples: • A date-time: "2018-02-12T23:20:50-00:00" • A bounded interval:"2018-02-12T00:00:00+05:00/2018-03-18T12:31:12+05:00" • Half-bounded intervals: "2018-02-12T00:00:00-05:00/.." or "../2018-03-18T12:31:12-05:00" Only features that have a sample_time that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties. See also Details below for more information.
CQL	A string in a Common Query Language format.
monitoring_location_id	This field is required. Combined site identifier of agency code and site number (format of {agency_code}-{monitoring_location_number}). A list of values can be passed for this field, separated by commas.
...	Additional arguments to send to the request.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates and qualifier to string vector.
limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
cql <- '{
 "op": "between",
   "args": [
      { "property": "water_level_above_navd88_ft" },
      [ "100.00", "200.00" ]
```

```
   ]
}'

wl_data <- read_ngwmn(service = "waterLevelObs",
                      monitoring_location_id = c("USGS-272838082142201",
                                                 "USGS-404159100494601",
                                                 "USGS-401216080362703"),
                      CQL = cql)

cql3 <- '{
"op": "and",
"args": [
 {
   "op": "between",
   "args": [
     { "property": "water_level_above_navd88_ft" },
     [ "100.00", "200.00" ]
   ]
 },
 {
   "op": "in",
   "args": [
     { "property": "monitoring_location_id" },
     [ "USGS-272838082142201", "USGS-404159100494601", "USGS-401216080362703" ]
   ]
 }
]
}'


wl_data_alt <- read_ngwmn(service = "waterLevelObs",
                          CQL = cql3)
```

---

read_ngwmn_lithology *Get NGWMN Lithology Observations*

Description

Lithology Observations data

Usage

```
read_ngwmn_lithology(
  monitoring_location_id = NA_character_,
  monitoring_location_obs_number = NA_character_,
  properties = NA_character_,
  ...,
```

```
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

monitoring_location_id	This field is required. Combined site identifier of agency code and site number (format of {agency_code}-{monitoring_location_number}). A list of values can be passed for this field, separated by commas.
monitoring_location_obs_number	Number of observation for given site. A list of values can be passed for this field, separated by commas.
properties	A vector of requested columns to be returned from the query. Available options are: agency_code, monitoring_location_number, monitoring_location_id, monitoring_location_obs_number, lithology_id, lithology_description, lithology_controlled_concept, lithology_depth_from, lithology_depth_to, lithology_depth_to_unit, lithology_depth_from_unit. The default (NA) will return all columns of the data.
...	Not used. Included to help differentiate official NGWMN API arguments from more seldom used, optional dataRetrieval-specific arguments.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.
no_paging	logical, defaults to FALSE. If TRUE, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use TRUE with caution.
chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.
limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
site <- "AKDNR-535134236016630"
ngwmn_lith <- read_ngwmn_lithology(monitoring_location_id = site)
```

```
sites <- c("ISWS-P428197",
           "AKDNR-535143966816631",
           "AKDNR-535134236016630")
ngwml_lith_sites <- read_ngwmn_lithology(monitoring_location_id = sites)
```

`read_ngwmn_providers` *Get NGWMN Provider Data*

Description

NGWMN contributing providers

Usage

```
read_ngwmn_providers(
  state = NA_character_,
  agency_code = NA_character_,
  organization_type = NA_character_,
  properties = NA_character_,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`state`	State code for provider. A list of values can be passed for this field, separated by commas.
`agency_code`	Code for the name of the agency or organization that owns the site and/or contributed it to the network. A list of values can be passed for this field, separated by commas.
`organization_type`	Type of organization of data provider.
`properties`	A vector of requested columns to be returned from the query. Available options are: agency_name, agency_code, organization_type, state, link. The default (`NA`) will return all columns of the data.
`...`	Not used. Included to help differentiate official NGWMN API arguments from more seldom used, optional dataRetrieval-specific arguments.
`convertType`	logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

no_paging	logical, defaults to FALSE. If TRUE, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use TRUE with caution.
chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.
limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
ngwmn_providers <- read_ngwmn_providers(state = "WI")

ngwml_providers2 <- read_ngwmn_providers(state = c("WI", "CA", "AZ", "MN"))

org_type <- read_ngwmn_providers(organization_type = "NWIS", state = c("WI", "MN"))
```

---

read_ngwmn_sites *Get NGWMN Site Data*

Description

Site data (from Monitoring Location Registry), including the name, identifier, agency, features, and location of the site

Usage

```
read_ngwmn_sites(
  monitoring_location_id = NA_character_,
  agency_code = NA_character_,
  monitoring_location_number = NA_character_,
  altitude = NA_character_,
  national_aquifer_code = NA_character_,
  national_aquifer_description = NA_character_,
  country_code = NA_character_,
```

```
  country_name = NA_character_,
  state_name = NA_character_,
  county_name = NA_character_,
  aquifer_name = NA_character_,
  site_type = NA_character_,
  aquifer_type_code = NA_character_,
  qw_sys_name = NA_character_,
  qw_sn_flag = NA_character_,
  qw_baseline_flag = NA_character_,
  qw_well_chars = NA_character_,
  qw_well_type = NA_character_,
  qw_well_purpose = NA_character_,
  wl_sys_name = NA_character_,
  wl_sn_flag = NA_character_,
  wl_baseline_flag = NA_character_,
  wl_well_chars = NA_character_,
  wl_well_type = NA_character_,
  wl_well_purpose = NA_character_,
  bbox = NA,
  properties = NA_character_,
  skipGeometry = FALSE,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: Site identifier, combination of agency code and site number (format `agency_code-monitoring_location_number`). A list of values can be passed for this field, separated by commas.

`agency_code`
: Code for the name of the agency or organization that owns the site and/or contributed it to the network. A list of values can be passed for this field, separated by commas.

`monitoring_location_number`
: Local, unique well or spring identification number or code. A list of values can be passed for this field, separated by commas.

`altitude`
: Elevation of the land surface at the site.

`national_aquifer_code`
: Code for U.S. Principal Aquifer. A list of values can be passed for this field, separated by commas.

`national_aquifer_description`
: Name for U.S. Principal Aquifer, lookup here. A list of values can be passed for this field, separated by commas.

`country_code` Abbreviation of country of site location. A list of values can be passed for this field, separated by commas.

`country_name` Name of country of site location.

`state_name` Name of state of site location. A list of values can be passed for this field, separated by commas.

`county_name` Name of county of site location. A list of values can be passed for this field, separated by commas.

`aquifer_name` Name of local aquifer of site. A list of values can be passed for this field, separated by commas.

`site_type` Type of groundwater site (Spring or Well).

`aquifer_type_code` Characteristic of the type of aquifer that the well is completed in (Confined or Unconfined). For NGWMN, shallow semi-confined wells can be considered unconfined if they respond to climatic fluctuations in a relatively short period of time.

`qw_sys_name` The system from which water quality data from the well or spring is served to the portal. A list of values can be passed for this field, separated by commas.

`qw_sn_flag` Flag for whether the well or spring is part of the NGWMN water-quality network.

`qw_baseline_flag` Flag for whether the well or spring has completed its 5-year baseline period, classifies it as being in one of the three QW subnetworks.

`qw_well_chars` The characteristics of the aquifer the well represents. There are 3 options: 'Background', 'Suspected / Anticipated Changes', 'Known Changes'. The field is NULL if the site is still in the baseline period.

`qw_well_type` Description of the assigned QW monitoring category for the well or spring.

`qw_well_purpose` Description of the prupose of conducting QW monitoring of the well or spring.

`wl_sys_name` The system from which water level data from the well or spring is served to the portal. A list of values can be passed for this field, separated by commas.

`wl_sn_flag` Flag for whether the well or spring is part of the NGWMN water-level network.

`wl_baseline_flag` Flag for whether the well or spring has completed its 5-year baseline period, classifies it as being in one of the three WL subnetworks.

`wl_well_chars` The characteristics of the aquifer the well represents. There are 3 options: 'Background', 'Suspected / Anticipated Changes', 'Known Changes'. The field is NULL if the site is still in the baseline period.

`wl_well_type` Description of the assigned WL monitoring category for the well or spring

`wl_well_purpose` Description of the purpose of conducting WL monitoring of the well or spring.

`bbox` Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth).

	Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).
properties	A vector of requested columns to be returned from the query. Available options are: geometry, monitoring_location_id, agency_code, agency_name, monitoring_location_number, monitoring_location_name, longitude, original_horizontal_datum, horizontal_position_accuracy_code, altitude, vertical_datum, altitude_method_name, altitude_accuracy, well_constructed_depth, well_depth_units, national_aquifer_code, national_aquifer_description, country_code, country_name, state_name, county_name, aquifer_name, site_type, aquifer_type_code, qw_sys_name, qw_sn_flag, qw_baseline_flag, qw_well_chars, qw_well_type, qw_well_purpose, qw_well_purpose_notes, wl_sys_name, wl_sn_flag, wl_baseline_flag, wl_well_chars, wl_well_type, wl_well_purpose, wl_well_purpose_notes, link. The default (NA) will return all columns of the data.
skipGeometry	This option can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information.
...	Not used. Included to help differentiate official NGWMN API arguments from more seldom used, optional dataRetrieval-specific arguments.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.
no_paging	logical, defaults to FALSE. If TRUE, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use TRUE with caution.
chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.
limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
ngwmn_sites <- read_ngwmn_sites(state_name = "Minnesota")

org_type <- read_ngwmn_sites(agency_code = "MN_DNR",
                             county_name = "Washington County")
```

`read_ngwmn_water_level` *Get NGWMN Water Level Data*

Description

Water Level Observations data

Usage

```
read_ngwmn_water_level(
  monitoring_location_id = NA_character_,
  monitoring_location_obs_number = NA_character_,
  sample_time = NA_character_,
  data_provided_by = NA_character_,
  water_depth_below_land_surface_ft = NA_character_,
  water_level_above_site_datum_ft = NA_character_,
  monitoring_location_vertical_datum = NA_character_,
  water_level_above_navd88_ft = NA_character_,
  properties = NA_character_,
  datetime = NA_character_,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: This field is required. Combined site identifier of agency code and site number (format of `{agency_code}-{monitoring_location_number}`). A list of values can be passed for this field, separated by commas.

`monitoring_location_obs_number`
: Number of observation for given site. A list of values can be passed for this field, separated by commas.

`sample_time`
: The date of an observation. Date and time expressions adhere to RFC 3339. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50-00:00"
  - A bounded interval:"2018-02-12T00:00:00+05:00/2018-03-18T12:31:12+05:00"
  - Half-bounded intervals: "2018-02-12T00:00:00-05:00/.." or "../2018-03-18T12:31:12-05:00"

Only features that have a `sample_time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

See also Details below for more information.

`data_provided_by`
: Code for the agency or organization that provides, collects, owns, and/or manages the water level measurement record.

`water_depth_below_land_surface_ft`
: Calculated depth to water in feet.

`water_level_above_site_datum_ft`
: Water-level value represented as depth to site datum in feet.

`monitoring_location_vertical_datum`
: Code indicating the vertical datum.

`water_level_above_navd88_ft`
: Mediated water-level value represented as depth to water relative to the NAVD88 datum.

`properties`
: A vector of requested columns to be returned from the query. Available options are: agency_code, monitoring_location_number, monitoring_location_id, monitoring_location_obs_number, sample_time, orig_unit, orig_value, accuracy_unit, accuracy_value, obs_datum_cd, obs_comment, obs_method, data_provided_by, water_depth_below_land_surface_ft, water_level_above_site_datum_ft, monitoring_location_vertical_datum, water_level_above_navd88_ft. The default (`NA`) will return all columns of the data.

`datetime`
: The date of an observation. Date and time expressions adhere to RFC 3339. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50-00:00"
  - A bounded interval:"2018-02-12T00:00:00+05:00/2018-03-18T12:31:12+05:00"
  - Half-bounded intervals: "2018-02-12T00:00:00-05:00/.." or "../2018-03-18T12:31:12-05:00"

  Only features that have a `sample_time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

`...`
: Not used. Included to help differentiate official NGWMN API arguments from more seldom used, optional dataRetrieval-specific arguments.

`convertType`
: logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

`no_paging`
: logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.

`chunk_size`
: Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to `NA` will eliminate site chunking, giving users full control.

limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
site <- "USGS-272838082142201"
ngwmn_wl <- read_ngwmn_water_level(monitoring_location_id = site)

ngwmn_wl_sub <- read_ngwmn_water_level(monitoring_location_id = site,
                    monitoring_location_obs_number = 1:5)

ngwml_wl_time2 <- read_ngwmn_water_level(monitoring_location_id = site,
                    datetime = c("2022-01-01", "2024-01-01"))

sites <- c("USGS-272838082142201", "USGS-404159100494601",
           "USGS-401216080362703", "MBMG-702934")
ngwml_wl_sites <- read_ngwmn_water_level(monitoring_location_id = sites)
```

---

read_ngwmn_well_construction

Get NGWMN Well Construction Data

Description

Well Construction Observations data

Usage

```
read_ngwmn_well_construction(
  monitoring_location_id = NA_character_,
  monitoring_location_obs_number = NA_character_,
  material = NA_character_,
  properties = NA_character_,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

monitoring_location_id	This field is required. Combined site identifier of agency code and site number (format of {agency_code}-{monitoring_location_number}). A list of values can be passed for this field, separated by commas.
monitoring_location_obs_number	Number of observation for given site. A list of values can be passed for this field, separated by commas.
material	Screen type or material.
properties	A vector of requested columns to be returned from the query. Available options are: agency_code, monitoring_location_number, monitoring_location_id, monitoring_location_obs_number, type, depth_from, depth_to, depth_from_unit, depth_to_unit, material, diameter, diameter_unit, hole_size, hole_size_unit. The default (NA) will return all columns of the data.
...	Not used. Included to help differentiate official NGWMN API arguments from more seldom used, optional dataRetrieval-specific arguments.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.
no_paging	logical, defaults to FALSE. If TRUE, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use TRUE with caution.
chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.
limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
site <- "USGS-272838082142201"
ngwmn_well <- read_ngwmn_well_construction(monitoring_location_id = site)

ngwmn_well_sub <- read_ngwmn_well_construction(monitoring_location_id = site,
                    monitoring_location_obs_number = 2)

sites <- c("USGS-272838082142201", "USGS-404159100494601",
           "USGS-401216080362703", "MBMG-702934")
ngwml_well_sites <- read_ngwmn_well_construction(monitoring_location_id = sites)
```

`read_waterdata` *Generalized USGS Water Data API retrieval function*

Description

Function that allows complex CQL queries. See https://api.waterdata.usgs.gov/docs/ogcapi/complex-queries/ for more information.

Usage

```
read_waterdata(
  service,
  CQL,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`service`	character, can be any existing collection.
`CQL`	A string in a Common Query Language format.
`...`	Additional arguments to send to the request.
`convertType`	logical, defaults to `TRUE`. If `TRUE`, the function will convert the data to dates and qualifier to string vector.
`limit`	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.
`attach_request`	logical, defaults to TRUE. If set to `TRUE`, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
cql <- '{
"op": "and",
"args": [
  {
    "op": "in",
    "args": [
```

```
      { "property": "parameter_code" },
      [ "00060", "00065" ]
    ]
  },
 {
    "op": "in",
    "args": [
      { "property": "monitoring_location_id" },
      [ "USGS-07367300", "USGS-03277200" ]
    ]
  }
]
}'

dv_data <- read_waterdata(service = "daily",
                          CQL = cql,
                          time = c("2023-01-01", "2024-01-01"))

# A wildcard in CQL2 is %
# Here's how to get HUCs that fall within 02070010
cql_huc_wildcard <- '{
"op": "like",
"args": [
  { "property": "hydrologic_unit_code" },
  "02070010%"
]
}'

what_huc_sites <- read_waterdata(service = "monitoring-locations",
                                 CQL = cql_huc_wildcard)
```

`read_waterdata_channel`

Get USGS Channel Measurements

Description

Channel measurements taken as part of streamflow field measurements.

Usage

```
read_waterdata_channel(
  monitoring_location_id = NA_character_,
  field_visit_id = NA_character_,
  measurement_number = NA_character_,
  time = NA_character_,
  channel_name = NA_character_,
```

```
  channel_flow = NA_character_,
  channel_flow_unit = NA_character_,
  channel_width = NA_character_,
  channel_width_unit = NA_character_,
  channel_area = NA_character_,
  channel_area_unit = NA_character_,
  channel_velocity = NA_character_,
  channel_velocity_unit = NA_character_,
  channel_location_distance = NA_character_,
  channel_location_distance_unit = NA_character_,
  channel_location_direction = NA_character_,
  channel_stability = NA_character_,
  channel_material = NA_character_,
  channel_evenness = NA_character_,
  horizontal_velocity_description = NA_character_,
  vertical_velocity_description = NA_character_,
  longitudinal_velocity_description = NA_character_,
  measurement_type = NA_character_,
  last_modified = NA_character_,
  channel_measurement_type = NA_character_,
  properties = NA_character_,
  skipGeometry = NA,
  bbox = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  limit = getOption("dataRetrieval.limit"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`

A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

Multiple monitoring_location_ids can be requested as a character vector.

`field_visit_id` A universally unique identifier (UUID) for the field visit. Multiple measurements may be made during a single field visit.

`measurement_number`

Measurement number.

`time` The date an observation represents. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"

- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

`channel_name` The channel name.

`channel_flow` Channel discharge.

`channel_flow_unit`
: The units for channel discharge.

`channel_width` The channel width.

`channel_width_unit`
: The units for channel width.

`channel_area` The channel area.

`channel_area_unit`
: The units for channel area.

`channel_velocity`
: The mean channel velocity.

`channel_velocity_unit`
: The units for channel velocity.

`channel_location_distance`
: The channel location distance.

`channel_location_distance_unit`
: The units for channel location distance.

`channel_location_direction`
: Location of the measurement from the gage.

`channel_stability`
: The stability of the channel material.

`channel_material`
: The channel material.

`channel_evenness`
: The channel evenness from bank to bank.

`horizontal_velocity_description`
: The horizontal velocity description.

`vertical_velocity_description`
: The vertical velocity description.

`longitudinal_velocity_description`
: The longitudinal velocity description.

`measurement_type`
: The measurement type.

`last_modified` The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

field_visit_id = NA_character_,

`channel_measurement_type`

The channel measurement type.

`properties` A vector of requested columns to be returned from the query. Available options are: geometry, channel_measurements_id, monitoring_location_id, field_visit_id, measurement_number, time, channel_name, channel_flow, channel_flow_unit, channel_width, channel_width_unit, channel_area, channel_area_unit, channel_velocity, channel_velocity_unit, channel_location_distance, channel_location_distance_unit, channel_stability, channel_material, channel_evenness, horizontal_velocity_description, vertical_velocity_description, longitudinal_velocity_description, measurement_type, last_modified, channel_measurement_type, channel_location_direction. The default (`NA`) will return all columns of the data.

`skipGeometry` This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`bbox` Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`...` Not used. Included to help differentiate official Water Data API arguments from more seldom used, optional dataRetrieval-specific arguments.

`convertType` logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

`no_paging` logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.

`limit` numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.

chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

Examples

```
site <- "USGS-02238500"
df <- read_waterdata_channel(monitoring_location_id = site)
```

---

read_waterdata_combined_meta

Get USGS Monitoring Location Metadata

Description

This endpoint combines metadata from timeseries and field measurements collections by site.

Usage

```
read_waterdata_combined_meta(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  parameter_name = NA_character_,
  unit_of_measure = NA_character_,
  statistic_id = NA_character_,
  parameter_description = NA_character_,
  data_type = NA_character_,
  computation_identifier = NA_character_,
```

```
computation_period_identifier = NA_character_,
thresholds = NA_character_,
sublocation_identifier = NA_character_,
primary = NA_character_,
web_description = NA_character_,
parent_time_series_id = NA_character_,
begin = NA_character_,
end = NA_character_,
last_modified = NA_character_,
agency_code = NA_character_,
agency_name = NA_character_,
monitoring_location_number = NA_character_,
monitoring_location_name = NA_character_,
district_code = NA_character_,
country_code = NA_character_,
country_name = NA_character_,
state_code = NA_character_,
state_name = NA_character_,
county_code = NA_character_,
county_name = NA_character_,
minor_civil_division_code = NA_character_,
site_type_code = NA_character_,
site_type = NA_character_,
hydrologic_unit_code = NA_character_,
basin_code = NA_character_,
altitude = NA_character_,
altitude_accuracy = NA_character_,
altitude_method_code = NA_character_,
altitude_method_name = NA_character_,
vertical_datum = NA_character_,
vertical_datum_name = NA_character_,
horizontal_positional_accuracy_code = NA_character_,
horizontal_positional_accuracy = NA_character_,
horizontal_position_method_code = NA_character_,
horizontal_position_method_name = NA_character_,
original_horizontal_datum = NA_character_,
original_horizontal_datum_name = NA_character_,
drainage_area = NA_character_,
contributing_drainage_area = NA_character_,
time_zone_abbreviation = NA_character_,
uses_daylight_savings = NA_character_,
construction_date = NA_character_,
aquifer_code = NA_character_,
national_aquifer_code = NA_character_,
aquifer_type_code = NA_character_,
well_constructed_depth = NA_character_,
hole_constructed_depth = NA_character_,
depth_source_code = NA_character_,
```

```
  properties = NA_character_,
  skipGeometry = NA,
  bbox = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  limit = getOption("dataRetrieval.limit"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_meta"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

  Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code`
: Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

  Multiple parameter_codes can be requested as a character vector.

`parameter_name`
: A human-understandable name corresponding to `parameter_code`. Multiple parameter_names can be requested as a character vector.

`unit_of_measure`
: A human-readable description of the units of measurement associated with an observation.

`statistic_id`
: A code corresponding to the statistic an observation represents. Example codes include 00001 (max), 00002 (min), and 00003 (mean). A complete list of codes and their descriptions can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/statistic-codes/items.

  Multiple statistic_ids can be requested as a character vector.

`parameter_description`
: A description of what the parameter code represents, as used by WDFN and other USGS data dissemination products.

`data_type`
: The computational period type of data collected at the monitoring location.

`computation_identifier`
: Indicates the computation performed to calculate this time series. Values of "Instantaneous" reflect point measurements. Multiple computation_identifiers can be requested as a character vector.

`computation_period_identifier`
: Multiple computation_period_identifiers can be requested as a character vector.

`thresholds` Thresholds represent known numeric limits for a time series, for example the historic maximum value for a parameter or a level below which a sensor is non-operative. These thresholds are sometimes used to automatically determine if an observation is erroneous due to sensor error, and therefore shouldn't be included in the time series.

`sublocation_identifier` An optional human-readable identifier used to specify where measurements are recorded at a monitoring location.

`primary` A flag identifying if the time series is a "primary" time series. "Primary" time series (which have this flag) are standard observations which undergo Bureau review and approval processes. Non-primary time series, which will have missing values for "primary", are provisional datasets made available to meet the need for timely best science and to assist with daily operations which need real-time information. Non-primary time series data are only retained by this system for 120 days.

`web_description` An optional description of the time series. WDFN and other USGS data dissemination products use this field, in combination with sublocation_identifier, to distinguish the differences between multiple time series for the same parameter code, statistic code, and monitoring location.

`parent_time_series_id` The unique identifier representing the parent or "upchain" time series that a daily values time series is generated from. Daily values time series have one and only one parent time series.

`begin` The datetime of the earliest observation in the time series. Together with `end_utc`, this field represents the period of record of a time series. Note that some time series may have large gaps in their collection record. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `begin_utc` that intersects the value of datetime are selected.

See also Details below for more information.

`end` The datetime of the most recent observation in the time series. Data returned by this endpoint updates at most once per day, and potentially less frequently than that, and as such there may be more recent observations within a time series than the time series `end_utc` value reflects. Together with `begin_utc`, this field represents the period of record of a time series. It is additionally used to determine whether a time series is "active". You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `end_utc` that intersects the value of datetime are selected.

See also Details below for more information.

`last_modified` The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

See also Details below for more information.

`agency_code` The agency that is reporting the data. Agency codes are fixed values assigned by the National Water Information System (NWIS). A list of agency codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/agency-codes/items.

`agency_name` The name of the agency that is reporting the data.

`monitoring_location_number`
Each monitoring location in the USGS data base has a unique 8- to 15-digit identification number.

`monitoring_location_name`
This is the official name of the monitoring location in the database. For well information this can be a district-assigned local number.

`district_code` The Water Science Centers (WSCs) across the United States use the FIPS state code as the district code. In some case, monitoring locations and samples may be managed by a water science center that is adjacent to the state in which the monitoring location actually resides. For example a monitoring location may have a district code of 30 which translates to Montana, but the state code could be 56 for Wyoming because that is where the monitoring location actually is located.

`country_code` The code for the country in which the monitoring location is located.

`country_name` The name of the country in which the monitoring location is located.

`state_code` State code. A two-digit ANSI code (formerly FIPS code) as defined by the American National Standards Institute, to define States and equivalents. A three-digit ANSI code is used to define counties and county equivalents. A lookup

table is available. The only countries with political subdivisions other than the US are Mexico and Canada. The Mexican states have US state codes ranging from 81-86 and Canadian provinces have state codes ranging from 90-98.

`state_name` The name of the state or state equivalent in which the monitoring location is located.

`county_code` The code for the county or county equivalent (parish, borough, etc.) in which the monitoring location is located. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/counties/items.

`county_name` The name of the county or county equivalent (parish, borough, etc.) in which the monitoring location is located. [A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/counties/items.

`minor_civil_division_code`
Codes for primary governmental or administrative divisions of the county or county equivalent in which the monitoring location is located.

`site_type_code` A code describing the hydrologic setting of the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/site-types/items.

`site_type` A description of the hydrologic setting of the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/site-types/items.

`hydrologic_unit_code`
The hydrologic unit code (HUC) for the monitoring location. Supports prefix matching — querying with a shorter HUC (e.g. "04") matches all locations within that hydrologic region.

`basin_code` The Basin Code or "drainage basin code" is a two-digit code that further subdivides the 8-digit hydrologic-unit code. The drainage basin code is defined by the USGS State Office where the monitoring location is located.

`altitude` Altitude of the monitoring location referenced to the specified Vertical Datum.

`altitude_accuracy`
Accuracy of the altitude, in feet. An accuracy of +/- 0.1 foot would be entered as ".1". Many altitudes are interpolated from the contours on topographic maps; accuracies determined in this way are generally entered as one-half of the contour interval.

`altitude_method_code`
Codes representing the method used to measure altitude.

`altitude_method_name`
The name of the method used to measure altitude.

`vertical_datum` The datum used to determine altitude and vertical position at the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/altitude-datums/items.

`vertical_datum_name`
The datum used to determine altitude and vertical position at the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/altitude-datums/items.

horizontal_positional_accuracy_code
: Indicates the accuracy of the latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-accuracy-codes/items.

horizontal_positional_accuracy
: Indicates the accuracy of the latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-accuracy-codes/items.

horizontal_position_method_code
: Indicates the method used to determine latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-method-codes/items.

horizontal_position_method_name
: Indicates the method used to determine latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-method-codes/items.

original_horizontal_datum
: Coordinates are published in EPSG:4326 / WGS84 / World Geodetic System 1984. This field indicates the original datum used to determine coordinates before they were converted. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-datum-codes/items.

original_horizontal_datum_name
: Coordinates are published in EPSG:4326 / WGS84 / World Geodetic System 1984. This field indicates the original datum used to determine coordinates before they were converted. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-datum-codes/items.

drainage_area
: The area enclosed by a topographic divide from which direct surface runoff from precipitation normally drains by gravity into the stream above that point.

contributing_drainage_area
: The contributing drainage area of a lake, stream, wetland, or estuary monitoring location, in square miles. This item should be present only if the contributing area is different from the total drainage area. This situation can occur when part of the drainage area consists of very porous soil or depressions that either allow all runoff to enter the groundwater or traps the water in ponds so that rainfall does not contribute to runoff. A transbasin diversion can also affect the total drainage area.

time_zone_abbreviation
: A short code describing the time zone used by a monitoring location.

uses_daylight_savings
: A flag indicating whether or not a monitoring location uses daylight savings.

construction_date
: Date the well was completed.

aquifer_code
: Local aquifers in the USGS water resources data base are identified by a geohydrologic unit code (a three-digit number related to the age of the formation, followed by a 4 or 5 character abbreviation for the geologic unit or aquifer name).

national_aquifer_code
: National aquifers are the principal aquifers or aquifer systems in the United States, defined as regionally extensive aquifers or aquifer systems that have the

potential to be used as a source of potable water. Not all groundwater monitoring locations can be associated with a National Aquifer. Such monitoring locations will not be retrieved using this search criteria. A list of National aquifer codes and names is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/national-aquifer-codes/items.

aquifer_type_code
: Describes the confinement status of an aquifer at the monitoring location. A confined aquifer is an aquifer below the land surface that is saturated with water. A water table–or unconfined–aquifer is an aquifer whose upper water surface (water table) is at atmospheric pressure, and thus is able to rise and fall.

well_constructed_depth
: The depth of the finished well, in feet below land surface datum. Note: Not all groundwater monitoring locations have information on Well Depth. Such monitoring locations will not be retrieved using this search criteria.

hole_constructed_depth
: The total depth to which the hole is drilled, in feet below land surface datum. Note: Not all groundwater monitoring locations have information on Hole Depth. Such monitoring locations will not be retrieved using this search criteria.

depth_source_code
: A code indicating the source of water-level data.

properties
: A vector of requested columns to be returned from the query. Available options are: geometry, monitoring_location_id, agency_code, agency_name, monitoring_location_number, monitoring_location_name, district_code, country_code, country_name, state_code, state_name, county_code, county_name, minor_civil_division_code, site_type_code, site_type, hydrologic_unit_code, basin_code, altitude, altitude_accuracy, altitude_method_code, altitude_method_name, vertical_datum, vertical_datum_name, horizontal_positional_accuracy_code, horizontal_positional_accuracy, horizontal_position_method_code, horizontal_position_method_name, original_horizontal_datum, original_horizontal_datum_name, drainage_area, contributing_drainage_area, time_zone_abbreviation, uses_daylight_savings, construction_date, aquifer_code, national_aquifer_code, aquifer_type_code, well_constructed_depth, hole_constructed_depth, depth_source_code, field_measurement_id, unit_of_measure, parameter_name, parameter_code, statistic_id, last_modified, begin, end, data_type, computation_identifier, thresholds, sublocation_identifier, primary, web_description, parameter_description, parent_time_series_id, data_gap_interval, reading_type. The default (NA) will return all columns of the data.

skipGeometry
: This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default NA will not specify the argument in the request.

bbox
: Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

...	Not used. Included to help differentiate official Water Data API arguments from more seldom used, optional dataRetrieval-specific arguments.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.
limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
no_paging	logical, defaults to FALSE. If TRUE, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use TRUE with caution.
chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

Examples

```
site <- "USGS-05407000"
available_data_sf <- read_waterdata_combined_meta(monitoring_location_id = site)

groundwater <- read_waterdata_combined_meta(monitoring_location_id = "USGS-375907091432201")

date_wi_data <- read_waterdata_combined_meta(state_name = "Wisconsin",
                                        county_name = "Dane County")


multi_site <- read_waterdata_combined_meta(
                               monitoring_location_id =  c("USGS-451605097071701",
                                                           "USGS-263819081585801"),
                               parameter_code = c("62611", "72019"))
```

```
surface_water <- read_waterdata_combined_meta(
                         monitoring_location_id = c("USGS-07069000",
                                                    "USGS-07064000",
                                                    "USGS-07068000"),
                         end = "P1M",
                         parameter_code = "00060")

hucs <- read_waterdata_combined_meta(
                         hydrologic_unit_code = c("11010008", "11010009"),
                         site_type = c("Stream", "Spring")
)

site_list <- read_waterdata_combined_meta(
                         monitoring_location_id = hucs$monitoring_location_id
)

# Query for instantaneous gage height data for a site in Iowa
sites_inst <- read_waterdata_combined_meta(
  monitoring_location_id = "USGS-05418400",
  parameter_code = "00065"
)

# parse individual thresholds lists:
threshold_1 <- jsonlite::fromJSON(sites_inst$thresholds[3])
```

`read_waterdata_continuous`

Get Continuous USGS Water Data

Description

Continuous data are collected via automated sensors installed at a monitoring location. They are collected at a high frequency and often at a fixed 15-minute interval. Depending on the specific monitoring location, the data may be transmitted automatically via telemetry and be available on WDFN within minutes of collection, while other times the delivery of data may be delayed if the monitoring location does not have the capacity to automatically transmit data. Continuous data are described by parameter name and parameter code (pcode). These data might also be referred to as "instantaneous values" or "IV".

Currently, the services only allow up to 3 years of data to be requested with a single request. If no "time" is specified, the service will return the last single year of data. If this is a bottleneck, please check back for new direct download functions that are expected to be available sometime in 2027.

Usage

```
read_waterdata_continuous(
```

```
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  properties = NA_character_,
  time_series_id = NA_character_,
  approval_status = NA_character_,
  unit_of_measure = NA_character_,
  qualifier = NA_character_,
  value = NA,
  last_modified = NA_character_,
  time = NA_character_,
  method_category = NA_character_,
  skipGeometry = TRUE,
  bbox = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  limit = getOption("dataRetrieval.limit"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

  Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code`
: Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

  Multiple parameter_codes can be requested as a character vector.

`properties`
: A vector of requested columns to be returned from the query. Available options are: geometry, time_series_id, monitoring_location_id, parameter_code, statistic_id, time, value, unit_of_measure, approval_status, qualifier, last_modified, method_category. The default (`NA`) will return all columns of the data.

`time_series_id`
: A unique identifier representing a single time series. This corresponds to the `id` field in the `time-series-metadata` endpoint.

  Multiple time_series_ids can be requested as a character vector.

`approval_status`
: Some of the data that you have obtained from this U.S. Geological Survey database may not have received Director's approval. Any such data values are qualified as provisional and are subject to revision. Provisional data are released on the condition that neither the USGS nor the United States Government may

be held liable for any damages resulting from its use. This field reflects the approval status of each record, and is either "Approved", meaining processing review has been completed and the data is approved for publication, or "Provisional" and subject to revision. For more information about provisional data, go to https://waterdata.usgs.gov/provisional-data-statement/.

`unit_of_measure`
: A human-readable description of the units of measurement associated with an observation.

`qualifier`
: This field indicates any qualifiers associated with an observation, for instance if a sensor may have been impacted by ice or if values were estimated.

`value`
: The value of the observation. Values are transmitted as strings in the JSON response format in order to preserve precision.

`last_modified`
: The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50Z"
  - A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
  - Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
  - Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

  Only features that have a `last_modified` that intersects the value of datetime are selected.

  See also Details below for more information.

`time`
: The date an observation represents. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50Z"
  - A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
  - Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
  - Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

  Only features that have a `time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

  See also Details below for more information.

`method_category`
: The RLMS method category code classifying the method in effect for this interval.

`skipGeometry`
: This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

bbox	Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).
...	Arguments that can be queried, but are not returned. These are used as alternatives to specifying specific monitoring_location_ids. See `?get_monitoring_location_arguments` for available arguments.
convertType	logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.
limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.
no_paging	logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.
chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to `NA` will eliminate site chunking, giving users full control.
attach_request	logical, defaults to TRUE. If set to `TRUE`, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

See Also

`get_monitoring_location_arguments()`

Examples

```
site <- "USGS-451605097071701"
```

```
pcode <- "72019"

uv_data_trim <- read_waterdata_continuous(monitoring_location_id = site,
                           parameter_code = pcode,
                           properties = c("value", "time"),
                           time = as.POSIXct(c("2026-02-07 12:00",
                                               "2026-02-08 12:00"),
                                             tz = "America/Chicago"))

uv_data <- read_waterdata_continuous(monitoring_location_id = site,
                           parameter_code = pcode,
                           time = "P2D")


# Only return data that has been modified in last 7 days
multi_site2 <- read_waterdata_continuous(monitoring_location_id =  c("USGS-451605097071701",
                                                                     "USGS-14181500"),
                                         parameter_code = c("00060", "72019"),
                                         last_modified = "P7D")

dane <- read_waterdata_continuous(
  state_name = "Wisconsin",
  county_name = "Dane County",
  parameter_code = "00060",
  time = "P1D")

# how to split up request into roughly 3 year chunks

site <- "USGS-0208458892"
pcode <- "00095" # Specific conductance
start <- as.Date("2013-01-01")
end <- as.Date("2025-12-31")

n_days <- difftime(end, start, units = "days")

# create a vector of dates that are about 3 years apart:
time_chunks <- seq(from = start,
                   to = end,
                   length.out = ceiling(n_days/(3*365.25)) + 1)


# create a list where each element starts at the beginning
# of a chunk, and ends the day before the next chunk:
time_df <- data.frame(start = time_chunks[-length(time_chunks)],
                      end = time_chunks[-1]-1)

#all_data <- data.frame()
#for(i in seq_along(time_df$start)){
#   sub_df <- read_waterdata_continuous(monitoring_location_id = site,
#                                       parameter_code = pcode,
#                                      time = c(time_df$start[i],
#                                               time_df$end[i]))
#   all_data <- rbind(all_data, sub_df)
```

```
# }

# Set the time to Eastern:
# all_data$time <- lubridate::force_tz(all_data$time, "America/New_York")
```

`read_waterdata_daily` *Get USGS Daily Data*

Description

Daily data provide one data value to represent water conditions for the day. Throughout much of the history of the USGS, the primary water data available was daily data collected manually at the monitoring location once each day. With improved availability of computer storage and automated transmission of data, the daily data published today are generally a statistical summary or metric of the continuous data collected each day, such as the daily mean, minimum, or maximum value. Daily data are automatically calculated from the continuous data of the same parameter code and are described by parameter code and a statistic code. These data have also been referred to as "daily values" or "DV".

Usage

```
read_waterdata_daily(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  statistic_id = NA_character_,
  properties = NA_character_,
  time_series_id = NA_character_,
  approval_status = NA_character_,
  unit_of_measure = NA_character_,
  qualifier = NA_character_,
  value = NA,
  last_modified = NA_character_,
  skipGeometry = NA,
  time = NA_character_,
  bbox = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

  Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code`
: Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

  Multiple parameter_codes can be requested as a character vector.

`statistic_id`
: A code corresponding to the statistic an observation represents. Example codes include 00001 (max), 00002 (min), and 00003 (mean). A complete list of codes and their descriptions can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/statistic-codes/items.

  Multiple statistic_ids can be requested as a character vector.

`properties`
: A vector of requested columns to be returned from the query. Available options are: geometry, time_series_id, monitoring_location_id, parameter_code, statistic_id, time, value, unit_of_measure, approval_status, qualifier, last_modified. The default (`NA`) will return all columns of the data.

`time_series_id`
: A unique identifier representing a single time series. This corresponds to the `id` field in the `time-series-metadata` endpoint.

  Multiple time_series_ids can be requested as a character vector.

`approval_status`
: Some of the data that you have obtained from this U.S. Geological Survey database may not have received Director's approval. Any such data values are qualified as provisional and are subject to revision. Provisional data are released on the condition that neither the USGS nor the United States Government may be held liable for any damages resulting from its use. This field reflects the approval status of each record, and is either "Approved", meaining processing review has been completed and the data is approved for publication, or "Provisional" and subject to revision. For more information about provisional data, go to https://waterdata.usgs.gov/provisional-data-statement/.

`unit_of_measure`
: A human-readable description of the units of measurement associated with an observation.

`qualifier`
: This field indicates any qualifiers associated with an observation, for instance if a sensor may have been impacted by ice or if values were estimated.

`value`
: The value of the observation. Values are transmitted as strings in the JSON response format in order to preserve precision.

`last_modified`
: The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or

intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

See also Details below for more information.

`skipGeometry` This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`time` The date an observation represents. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

See also Details below for more information.

`bbox` Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`...` Arguments that can be queried, but are not returned. These are used as alternatives to specifying specific monitoring_location_ids. See `?get_monitoring_location_arguments` for available arguments.

`convertType` logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

`no_paging` logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.

`chunk_size` Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to `NA` will eliminate site chunking, giving users full control.

limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

See Also

get_monitoring_location_arguments()

Examples

```
site <- "USGS-02238500"
dv_data_sf <- read_waterdata_daily(monitoring_location_id = site,
                               parameter_code = "00060",
                               time = c("2021-01-01", "2022-01-01"))

dv_data_last_modified <- read_waterdata_daily(monitoring_location_id = site,
                               parameter_code = "00060",
                               last_modified = "P7D")

dv_data_trim <- read_waterdata_daily(monitoring_location_id = site,
                          parameter_code = "00060",
                          properties = c("value",
                                         "time"),
                          time = c("2021-01-01", "2022-01-01"))

dv_data <- read_waterdata_daily(monitoring_location_id = site,
                           parameter_code = "00060",
                           skipGeometry = TRUE)

dv_data_period <- read_waterdata_daily(monitoring_location_id = site,
                                   parameter_code = "00060",
                                   time = "P7D")
```

```
multi_site <- read_waterdata_daily(monitoring_location_id =  c("USGS-01491000",
                                                               "USGS-01645000"),
                                   parameter_code = c("00060", "00010"),
                                   time = c("2023-01-01", "2024-01-01"))

dv_data_quick <- read_waterdata_daily(monitoring_location_id = site,
                                      parameter_code = "00060",
                                      no_paging = TRUE)

dv_post <- read_waterdata_daily(monitoring_location_id = site,
                                  approval_status = c("Approved", "Provisional"))
# Don't attach "request" attribute:
options("dataRetrieval.attach_request" = FALSE)
dv_data_no_request <- read_waterdata_daily(monitoring_location_id = site,
                                   parameter_code = "00060",
                                   time = c("2021-01-01", "2022-01-01"))

dv_dane <- read_waterdata_daily(
   state_name = "Wisconsin",
   county_name = "Dane County",
   parameter_code = "00060",
   time = "P7D")
```

`read_waterdata_field_measurements`

Get USGS Field Measurement Water Data

Description

Field measurements are physically measured values collected during a visit to the monitoring location. Field measurements consist of measurements of gage height and discharge, and readings of groundwater levels, and are primarily used as calibration readings for the automated sensors collecting continuous data. They are collected at a low frequency, and delivery of the data in WDFN may be delayed due to data processing time.

Usage

```
read_waterdata_field_measurements(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  observing_procedure_code = NA_character_,
  properties = NA_character_,
  field_visit_id = NA_character_,
  field_measurements_series_id = NA_character_,
  approval_status = NA_character_,
  unit_of_measure = NA_character_,
```

```
  qualifier = NA_character_,
  value = NA,
  last_modified = NA_character_,
  observing_procedure = NA_character_,
  vertical_datum = NA_character_,
  measuring_agency = NA_character_,
  control_condition = NA_character_,
  measurement_rated = NA_character_,
  sublocation_identifier = NA_character_,
  skipGeometry = NA,
  time = NA_character_,
  bbox = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  limit = getOption("dataRetrieval.limit"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_data"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

  Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code`
: Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

  Multiple parameter_codes can be requested as a character vector.

`observing_procedure_code`
: A short code corresponding to the observing procedure for the field measurement.

`properties`
: A vector of requested columns to be returned from the query. Available options are: geometry, field_measurements_series_id, reading_type, field_visit_id, parameter_code, monitoring_location_id, observing_procedure_code, observing_procedure, value, unit_of_measure, time, qualifier, vertical_datum, approval_status, measuring_agency, last_modified, control_condition, measurement_rated, year, month, day, time_of_day, sublocation_identifier. The default (`NA`) will return all columns of the data.

`field_visit_id`
: A universally unique identifier (UUID) for the field visit. Multiple measurements may be made during a single field visit.

`field_measurements_series_id`
: A unique identifier representing a single collection series. This corresponds to the `field_measurements_series_id` field in the `read_waterdata_field_meta` endpoint. Collection series are defined as the set of field measurements at a given monitoring location for a single parameter code using a single reading type.

`approval_status`
: Some of the data that you have obtained from this U.S. Geological Survey database may not have received Director's approval. Any such data values are qualified as provisional and are subject to revision. Provisional data are released on the condition that neither the USGS nor the United States Government may be held liable for any damages resulting from its use. This field reflects the approval status of each record, and is either "Approved", meaining processing review has been completed and the data is approved for publication, or "Provisional" and subject to revision. For more information about provisional data, go to https://waterdata.usgs.gov/provisional-data-statement/.

`unit_of_measure`
: A human-readable description of the units of measurement associated with an observation.

`qualifier`
: This field indicates any qualifiers associated with an observation, for instance if a sensor may have been impacted by ice or if values were estimated.

`value`
: The value of the observation. Values are transmitted as strings in the JSON response format in order to preserve precision.

`last_modified`
: The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50Z"
  - A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
  - Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
  - Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

  Only features that have a `last_modified` that intersects the value of datetime are selected.

  See also Details below for more information.

`observing_procedure`
: Water measurement or water-quality observing procedure descriptions.

`vertical_datum`
: The datum used to determine altitude and vertical position at the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/altitude-datums/items.

`measuring_agency`
: The agency performing the measurement.

`control_condition`
: The state of the control feature at the time of observation.

  What and where the control of flow is for the gage pool.

`measurement_rated`
: A qualitative estimate of the quality of a measurement.

  Rated measurement based on the hydrologic/hydraulic conditions in which the measurement was made (excellent (2 percent), good (5 percent), fair (8 percent), or poor (more than 8 percent). percent)

`sublocation_identifier`
: An optional human-readable identifier used to specify where measurements are recorded at a monitoring location.

`skipGeometry`
: This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`time`
: The date an observation represents. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50Z"
  - A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
  - Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
  - Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

  Only features that have a `time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

  See also Details below for more information.

`bbox`
: Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`...`
: Arguments that can be queried, but are not returned. These are used as alternatives to specifying specific monitoring_location_ids. See `?get_monitoring_location_arguments` for available arguments.

`convertType`
: logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

`no_paging`
: logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.

`limit`
: numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.

chunk_size Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.

attach_request logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

See Also

get_monitoring_location_arguments()

Examples

```
site <- "USGS-14202650"
field_data_sf <- read_waterdata_field_measurements(monitoring_location_id = site)

groundwater <- read_waterdata_field_measurements(monitoring_location_id = "USGS-375907091432201")

field_data <- read_waterdata_field_measurements(monitoring_location_id = "USGS-02238500",
                           parameter_code = "00060",
                           time = as.POSIXct(c("2024-02-26 15:00:00",
                                               "2025-08-27 12:00:00"),
                                             tz = "America/Chicago"),
                           skipGeometry = TRUE)

gwl_data_period <- read_waterdata_field_measurements(
                                  monitoring_location_id = "USGS-375907091432201",
                                  parameter_code = "72019",
                                  time = "P20Y")

multi_site <- read_waterdata_field_measurements(
                              monitoring_location_id =  c("USGS-451605097071701",
                                                          "USGS-263819081585801"),
                              parameter_code = c("62611", "72019"))

old_df <- read_waterdata_field_measurements(monitoring_location_id = "USGS-425957088141001",
                                            time = c("1980-01-01", NA))
```

```
new_df <- read_waterdata_field_measurements(monitoring_location_id = "USGS-425957088141001",
                                            time = c(NA, "2020-01-01"))

surface_water <- read_waterdata_field_measurements(
                          monitoring_location_id = c("USGS-07069000",
                                                     "USGS-07064000",
                                                     "USGS-07068000"),
                          time = "2024-07-01T00:00:00Z/..",
                          parameter_code = "00060")

dane <- read_waterdata_field_measurements(
  state_name = "Wisconsin",
  county_name = "Dane County",
  parameter_code = "00060",
  time = "P30D")
```

`read_waterdata_field_meta` *Get USGS Field Measurement Metadata*

Description

This endpoint provides metadata about field measurement collections, including when the earliest and most recent observations for a parameter occurred at a monitoring location and its units.

Usage

```
read_waterdata_field_meta(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  parameter_name = NA_character_,
  parameter_description = NA_character_,
  begin = NA_character_,
  end = NA_character_,
  last_modified = NA_character_,
  properties = NA_character_,
  sublocation_identifier = NA_character_,
  skipGeometry = NA,
  bbox = NA,
  limit = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_meta"),
```

```
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

  Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code`
: Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

  Multiple parameter_codes can be requested as a character vector.

`parameter_name`
: A human-understandable name corresponding to `parameter_code`. Multiple parameter_names can be requested as a character vector.

`parameter_description`
: A description of what the parameter code represents, as used by WDFN and other USGS data dissemination products.

  Multiple parameter_descriptions can be requested as a character vector.

`begin`
: The datetime of the earliest observation in the time series. Together with `end_utc`, this field represents the period of record of a time series. Note that some time series may have large gaps in their collection record. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50Z"
  - A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
  - Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
  - Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

  Only features that have a `begin_utc` that intersects the value of datetime are selected.

  See also Details below for more information.

`end`
: The datetime of the most recent observation in the time series. Data returned by this endpoint updates at most once per day, and potentially less frequently than that, and as such there may be more recent observations within a time series than the time series `end_utc` value reflects. Together with `begin_utc`, this field represents the period of record of a time series. It is additionally used to determine whether a time series is "active". You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50Z"

- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `end_utc` that intersects the value of datetime are selected.

`last_modified` The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

See also Details below for more information.

`properties` A vector of requested columns to be returned from the query. Available options are: geometry, field_measurement_id, reading_type, monitoring_location_id, parameter_code, parameter_name, parameter_description, begin, end, last_modified, sublocation_identifier. The default (`NA`) will return all columns of the data.

`sublocation_identifier`

An optional human-readable identifier used to specify where measurements are recorded at a monitoring location.

See also Details below for more information.

`skipGeometry` This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`bbox` Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`limit` numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.

`...` Not used. Included to help differentiate official Water Data API arguments from more seldom used, optional dataRetrieval-specific arguments.

convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.
no_paging	logical, defaults to FALSE. If TRUE, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use TRUE with caution.
chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

Examples

```
site <- "USGS-02238500"
field_data_sf <- read_waterdata_field_meta(monitoring_location_id = site)

groundwater <- read_waterdata_field_meta(monitoring_location_id = "USGS-375907091432201")

gwl_data <- read_waterdata_field_meta(monitoring_location_id = "USGS-02238500",
                           parameter_code = "00060",
                           begin = as.POSIXct(c(NA,
                                                "2025-08-27 12:00:00"),
                                              tz = "America/Chicago"),
                           skipGeometry = TRUE)

gwl_data_period <- read_waterdata_field_meta(
                                  monitoring_location_id = "USGS-375907091432201",
                                  parameter_code = "72019",
                                  last_modified = "P1Y")

multi_site <- read_waterdata_field_meta(
                               monitoring_location_id =  c("USGS-451605097071701",
                                                           "USGS-263819081585801"),
                               parameter_code = c("62611", "72019"))
```

```
surface_water <- read_waterdata_field_meta(
                          monitoring_location_id = c("USGS-07069000",
                                                     "USGS-07064000",
                                                     "USGS-07068000"),
                          end = "2024-07-01T00:00:00Z/..",
                          parameter_code = "00060")
```

`read_waterdata_latest_continuous` *Get Latest Continuous USGS Water Data*

Description

This endpoint provides the most recent observation for each time series of continuous data. Continuous data are collected via automated sensors installed at a monitoring location. They are collected at a high frequency and often at a fixed 15-minute interval. Depending on the specific monitoring location, the data may be transmitted automatically via telemetry and be available on WDFN within minutes of collection, while other times the delivery of data may be delayed if the monitoring location does not have the capacity to automatically transmit data. Continuous data are described by parameter name and parameter code. These data might also be referred to as "instantaneous values" or "IV"

Usage

```
read_waterdata_latest_continuous(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  properties = NA_character_,
  time_series_id = NA_character_,
  approval_status = NA_character_,
  unit_of_measure = NA_character_,
  qualifier = NA_character_,
  value = NA,
  last_modified = NA_character_,
  skipGeometry = NA,
  time = NA_character_,
  bbox = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_meta"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

  Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code`
: Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

  Multiple parameter_codes can be requested as a character vector.

`properties`
: A vector of requested columns to be returned from the query. Available options are: geometry, time_series_id, monitoring_location_id, parameter_code, statistic_id, time, value, unit_of_measure, approval_status, qualifier, last_modified. The default (`NA`) will return all columns of the data.

`time_series_id`
: A unique identifier representing a single time series. This corresponds to the `id` field in the `time-series-metadata` endpoint.

  Multiple time_series_ids can be requested as a character vector.

`approval_status`
: Some of the data that you have obtained from this U.S. Geological Survey database may not have received Director's approval. Any such data values are qualified as provisional and are subject to revision. Provisional data are released on the condition that neither the USGS nor the United States Government may be held liable for any damages resulting from its use. This field reflects the approval status of each record, and is either "Approved", meaining processing review has been completed and the data is approved for publication, or "Provisional" and subject to revision. For more information about provisional data, go to https://waterdata.usgs.gov/provisional-data-statement/.

`unit_of_measure`
: A human-readable description of the units of measurement associated with an observation.

`qualifier`
: This field indicates any qualifiers associated with an observation, for instance if a sensor may have been impacted by ice or if values were estimated.

`value`
: The value of the observation. Values are transmitted as strings in the JSON response format in order to preserve precision.

`last_modified`
: The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50Z"
  - A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
  - Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"

- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

See also Details below for more information.

`skipGeometry` This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`time` The date an observation represents. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

See also Details below for more information.

`bbox` Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`...` Arguments that can be queried, but are not returned. These are used as alternatives to specifying specific monitoring_location_ids. See `?get_monitoring_location_arguments` for available arguments.

`convertType` logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

`no_paging` logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.

`chunk_size` Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to `NA` will eliminate site chunking, giving users full control.

`limit` numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.

attach_request logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

See Also

get_monitoring_location_arguments()

Examples

```
site <- "USGS-451605097071701"
pcode <- "72019"
uv_data_sf <- read_waterdata_latest_continuous(monitoring_location_id = site,
                              parameter_code = pcode)

uv_data_trim <- read_waterdata_latest_continuous(monitoring_location_id = site,
                           parameter_code = pcode,
                           properties = c("monitoring_location_id",
                                          "value",
                                          "time"))

uv_data <- read_waterdata_latest_continuous(monitoring_location_id = site,
                            parameter_code = pcode,
                            skipGeometry = TRUE)

uv_data_period <- read_waterdata_latest_continuous(monitoring_location_id = site,
                                   parameter_code = pcode,
                                   time = "P7D")

multi_site <- read_waterdata_latest_continuous(monitoring_location_id = c("USGS-451605097071701",
                                                                          "USGS-14181500"),
                              parameter_code = c("00060", "72019"),
                              skipGeometry = TRUE)

# Only return data that has been modified in last 7 days
multi_site2 <- read_waterdata_latest_continuous(monitoring_location_id = c("USGS-451605097071701",
                                                                           "USGS-14181500"),
                                                parameter_code = c("00060", "72019"),
                                                last_modified = "P7D")
```

```
dane <- read_waterdata_latest_continuous(
  state_name = "Wisconsin",
  county_name = "Dane County",
  parameter_code = "00060",
  time = "P1D")
```

`read_waterdata_latest_daily` *Get Latest USGS Daily Data*

Description

Daily data provide one data value to represent water conditions for the day. Throughout much of the history of the USGS, the primary water data available was daily data collected manually at the monitoring location once each day. With improved availability of computer storage and automated transmission of data, the daily data published today are generally a statistical summary or metric of the continuous data collected each day, such as the daily mean, minimum, or maximum value. Daily data are automatically calculated from the continuous data of the same parameter code and are described by parameter code and a statistic code. These data have also been referred to as "daily values" or "DV".

Usage

```
read_waterdata_latest_daily(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  statistic_id = NA_character_,
  properties = NA_character_,
  time_series_id = NA_character_,
  approval_status = NA_character_,
  unit_of_measure = NA_character_,
  qualifier = NA_character_,
  value = NA,
  last_modified = NA_character_,
  skipGeometry = NA,
  time = NA_character_,
  bbox = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  limit = getOption("dataRetrieval.limit"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_meta"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

monitoring_location_id
: A unique identifier representing a single monitoring location. This corresponds to the id field in the monitoring-locations endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

  Multiple monitoring_location_ids can be requested as a character vector.

parameter_code
: Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

  Multiple parameter_codes can be requested as a character vector.

statistic_id
: A code corresponding to the statistic an observation represents. Example codes include 00001 (max), 00002 (min), and 00003 (mean). A complete list of codes and their descriptions can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/statistic-codes/items.

  Multiple statistic_ids can be requested as a character vector.

properties
: A vector of requested columns to be returned from the query. Available options are: geometry, time_series_id, monitoring_location_id, parameter_code, statistic_id, time, value, unit_of_measure, approval_status, qualifier, last_modified. The default (NA) will return all columns of the data.

time_series_id
: A unique identifier representing a single time series. This corresponds to the id field in the time-series-metadata endpoint.

  Multiple time_series_ids can be requested as a character vector.

approval_status
: Some of the data that you have obtained from this U.S. Geological Survey database may not have received Director's approval. Any such data values are qualified as provisional and are subject to revision. Provisional data are released on the condition that neither the USGS nor the United States Government may be held liable for any damages resulting from its use. This field reflects the approval status of each record, and is either "Approved", meaining processing review has been completed and the data is approved for publication, or "Provisional" and subject to revision. For more information about provisional data, go to https://waterdata.usgs.gov/provisional-data-statement/.

unit_of_measure
: A human-readable description of the units of measurement associated with an observation.

qualifier
: This field indicates any qualifiers associated with an observation, for instance if a sensor may have been impacted by ice or if values were estimated.

value
: The value of the observation. Values are transmitted as strings in the JSON response format in order to preserve precision.

last_modified
: The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or

intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

See also Details below for more information.

`skipGeometry` This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`time` The date an observation represents. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

See also Details below for more information.

`bbox` Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`...` Arguments that can be queried, but are not returned. These are used as alternatives to specifying specific monitoring_location_ids. See `?get_monitoring_location_arguments` for available arguments.

`convertType` logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

`no_paging` logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.

`limit` numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable

limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.

chunk_size — Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.

attach_request — logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

See Also

get_monitoring_location_arguments()

Examples

```
site <- "USGS-02238500"
pcode <- "00060"
dv_data_sf <- read_waterdata_latest_daily(monitoring_location_id = site,
                              parameter_code = pcode)

dv_data_last_modified <- read_waterdata_latest_daily(monitoring_location_id = site,
                              parameter_code = pcode,
                              last_modified = "P7D")

dv_data_trim <- read_waterdata_latest_daily(monitoring_location_id = site,
                          parameter_code = pcode,
                          properties = c("monitoring_location_id",
                                         "value",
                                         "time"))

dv_data <- read_waterdata_latest_daily(monitoring_location_id = site,
                           parameter_code = pcode,
                           skipGeometry = TRUE)

multi_site <- read_waterdata_latest_daily(monitoring_location_id =  c("USGS-01491000",
```

```
                                                                    "USGS-01645000"),
                                  parameter_code = c("00060", "00010"))

dane <- read_waterdata_latest_daily(
  state_name = "Wisconsin",
  county_name = "Dane County",
  parameter_code = "00060",
  time = "P7D")
```

`read_waterdata_latest_field_measurements` *Get Latest USGS Field Measurement Data*

Description

Field measurements are physically measured values collected during a visit to the monitoring location. Field measurements consist of measurements of gage height and discharge, and readings of groundwater levels, and are primarily used as calibration readings for the automated sensors collecting continuous data. They are collected at a low frequency, and delivery of the data in WDFN may be delayed due to data processing time.

Usage

```
read_waterdata_latest_field_measurements(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  statistic_id = NA_character_,
  properties = NA_character_,
  time_series_id = NA_character_,
  approval_status = NA_character_,
  unit_of_measure = NA_character_,
  qualifier = NA_character_,
  value = NA,
  last_modified = NA_character_,
  skipGeometry = NA,
  time = NA_character_,
  bbox = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  limit = getOption("dataRetrieval.limit"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_meta"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`
: A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

  Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code`
: Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

  Multiple parameter_codes can be requested as a character vector.

`statistic_id`
: Multiple statistic_ids can be requested as a character vector.

`properties`
: A vector of requested columns to be returned from the query. Available options are: geometry, field_measurements_series_id, field_visit_id, parameter_code, monitoring_location_id, observing_procedure_code, observing_procedure, value, unit_of_measure, time, qualifier, vertical_datum, approval_status, measuring_agency, last_modified, control_condition, measurement_rated, year, month, day, time_of_day, sublocation_identifier. The default (`NA`) will return all columns of the data.

`time_series_id`
: Multiple time_series_ids can be requested as a character vector.

`approval_status`
: Some of the data that you have obtained from this U.S. Geological Survey database may not have received Director's approval. Any such data values are qualified as provisional and are subject to revision. Provisional data are released on the condition that neither the USGS nor the United States Government may be held liable for any damages resulting from its use. This field reflects the approval status of each record, and is either "Approved", meaining processing review has been completed and the data is approved for publication, or "Provisional" and subject to revision. For more information about provisional data, go to https://waterdata.usgs.gov/provisional-data-statement/.

`unit_of_measure`
: A human-readable description of the units of measurement associated with an observation.

`qualifier`
: This field indicates any qualifiers associated with an observation, for instance if a sensor may have been impacted by ice or if values were estimated.

`value`
: The value of the observation. Values are transmitted as strings in the JSON response format in order to preserve precision.

`last_modified`
: The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

  - A date-time: "2018-02-12T23:20:50Z"
  - A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"

- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

See also Details below for more information.

`skipGeometry` This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`time` The date an observation represents. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `time` that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

See also Details below for more information.

`bbox` Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`...` Arguments that can be queried, but are not returned. These are used as alternatives to specifying specific monitoring_location_ids. See `?get_monitoring_location_arguments` for available arguments.

`convertType` logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

`no_paging` logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.

`limit` numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.

`chunk_size` Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to `NA` will eliminate site chunking, giving users full control.

attach_request logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

See Also

`get_monitoring_location_arguments()`

Examples

```
site <- "USGS-01435000"

field_data_sf <- read_waterdata_latest_field_measurements(monitoring_location_id = site)

dv_data_trim <- read_waterdata_latest_field_measurements(monitoring_location_id = site,
                          properties = c("monitoring_location_id",
                                         "value",
                                         "time"))

field_data <- read_waterdata_latest_field_measurements(monitoring_location_id = site,
                           skipGeometry = TRUE)

multi_site <- read_waterdata_latest_field_measurements(monitoring_location_id =  c("USGS-01435000",
                                                                                   "USGS-14202650"))

dane <- read_waterdata_latest_field_measurements(
  state_name = "Wisconsin",
  county_name = "Dane County",
  time = "P30D")
```

`read_waterdata_metadata` *Generalized USGS Water Meta Data API retrieval function*

Description

Function to get metadata from Water Data API. These are useful to get the human readable words and other metadata associated with USGS codes.

Usage

```
read_waterdata_metadata(
  collection,
  ...,
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`collection`	character, can be any existing collection such as "parameter-codes", "agency-codes", "altitude-datums", "aquifer-codes", "aquifer-types", "coordinate-accuracy-codes", "coordinate-datum-codes", "coordinate-method-codes", "hydrologic-unit-codes", "medium-codes", "national-aquifer-codes", "reliability-codes", "site-types", "statistic-codes", "topographic-codes", "time-zone-codes".
`...`	Optional arguments to pass to the query. Available parameters can be found with the `get_ogc_params` function.
`limit`	The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.
`attach_request`	logical, defaults to TRUE. If set to `TRUE`, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
agency_codes <- read_waterdata_metadata("agency-codes")
altitude_datums <- read_waterdata_metadata("altitude-datums")
aquifer_codes <- read_waterdata_metadata("aquifer-codes")
aquifer_types <- read_waterdata_metadata("aquifer-types")
counties <- read_waterdata_metadata("counties")
countries <- read_waterdata_metadata("countries")
us_counties <- read_waterdata_metadata("counties", country_code = "US")
coordinate_accuracy_codes <- read_waterdata_metadata("coordinate-accuracy-codes")
coordinate_datum_codes <- read_waterdata_metadata("coordinate-datum-codes")
```

```
coordinate_method_codes <- read_waterdata_metadata("coordinate-method-codes")
huc_codes <- read_waterdata_metadata("hydrologic-unit-codes")
methods <- read_waterdata_metadata("methods")
method_categories <- read_waterdata_metadata("method-categories")
method_citations <- read_waterdata_metadata("method-citations")
citations <- read_waterdata_metadata("citations")
national_aquifer_codes <- read_waterdata_metadata("national-aquifer-codes")
parameter_codes <- read_waterdata_metadata("parameter-codes")
reliability_codes <- read_waterdata_metadata("reliability-codes")
site_types <- read_waterdata_metadata("site-types")
states <- read_waterdata_metadata("states")
us_states_territories <- read_waterdata_metadata("states", country_code = "US")
statistic_codes <- read_waterdata_metadata("statistic-codes")
topographic_codes <- read_waterdata_metadata("topographic-codes")
time_zone_codes <- read_waterdata_metadata("time-zone-codes")
time_zone_limited <- read_waterdata_metadata("time-zone-codes",
                  time_zone_description = c("Alaska", "Hawaii", "Pacific North America"))
```

`read_waterdata_monitoring_location`
Get USGS Monitoring Location Data

Description

Location information is basic information about the monitoring location including the name, identifier, agency responsible for data collection, and the date the location was established. It also includes information about the type of location, such as stream, lake, or groundwater, and geographic information about the location, such as state, county, latitude and longitude, and hydrologic unit code (HUC).

Usage

```
read_waterdata_monitoring_location(
  monitoring_location_id = NA_character_,
  agency_code = NA_character_,
  agency_name = NA_character_,
  monitoring_location_number = NA_character_,
  monitoring_location_name = NA_character_,
  district_code = NA_character_,
  country_code = NA_character_,
  country_name = NA_character_,
  state_code = NA_character_,
  state_name = NA_character_,
  county_code = NA_character_,
  county_name = NA_character_,
  minor_civil_division_code = NA_character_,
```

```
  site_type_code = NA_character_,
  site_type = NA_character_,
  hydrologic_unit_code = NA_character_,
  basin_code = NA_character_,
  altitude = NA_character_,
  altitude_accuracy = NA_character_,
  altitude_method_code = NA_character_,
  altitude_method_name = NA_character_,
  vertical_datum = NA_character_,
  vertical_datum_name = NA_character_,
  horizontal_positional_accuracy_code = NA_character_,
  horizontal_positional_accuracy = NA_character_,
  horizontal_position_method_code = NA_character_,
  horizontal_position_method_name = NA_character_,
  original_horizontal_datum = NA_character_,
  original_horizontal_datum_name = NA_character_,
  drainage_area = NA_character_,
  contributing_drainage_area = NA_character_,
  time_zone_abbreviation = NA_character_,
  uses_daylight_savings = NA_character_,
  construction_date = NA_character_,
  aquifer_code = NA_character_,
  national_aquifer_code = NA_character_,
  aquifer_type_code = NA_character_,
  well_constructed_depth = NA_character_,
  hole_constructed_depth = NA_character_,
  depth_source_code = NA_character_,
  revision_note = NA_character_,
  revision_created = NA_character_,
  revision_modified = NA_character_,
  properties = NA_character_,
  q = NA_character_,
  bbox = NA,
  skipGeometry = NA,
  ...,
  convertType = getOption("dataRetrieval.convertType"),
  limit = getOption("dataRetrieval.limit"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_meta"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`

A unique identifier representing a single monitoring location. This corresponds to the `monitoring_location_id` field in other endpoints. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location

(e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

Multiple monitoring_location_ids can be requested as a character vector.

`agency_code` The agency that is reporting the data. Agency codes are fixed values assigned by the National Water Information System (NWIS). A list of agency codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/agency-codes/items.

`agency_name` The name of the agency that is reporting the data.

`monitoring_location_number`
Each monitoring location in the USGS data base has a unique 8- to 15-digit identification number.

`monitoring_location_name`
This is the official name of the monitoring location in the database. For well information this can be a district-assigned local number.

`district_code` The Water Science Centers (WSCs) across the United States use the FIPS state code as the district code. In some case, monitoring locations and samples may be managed by a water science center that is adjacent to the state in which the monitoring location actually resides. For example a monitoring location may have a district code of 30 which translates to Montana, but the state code could be 56 for Wyoming because that is where the monitoring location actually is located.

`country_code` The code for the country in which the monitoring location is located.

`country_name` The name of the country in which the monitoring location is located.

`state_code` State code. A two-digit ANSI code (formerly FIPS code) as defined by the American National Standards Institute, to define States and equivalents. A three-digit ANSI code is used to define counties and county equivalents. A lookup table is available. The only countries with political subdivisions other than the US are Mexico and Canada. The Mexican states have US state codes ranging from 81-86 and Canadian provinces have state codes ranging from 90-98.

`state_name` The name of the state or state equivalent in which the monitoring location is located.

`county_code` The code for the county or county equivalent (parish, borough, etc.) in which the monitoring location is located. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/counties/items.

`county_name` The name of the county or county equivalent (parish, borough, etc.) in which the monitoring location is located. [A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/counties/items.

`minor_civil_division_code`
Codes for primary governmental or administrative divisions of the county or county equivalent in which the monitoring location is located.

`site_type_code` A code describing the hydrologic setting of the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/site-types/items.

`site_type` A description of the hydrologic setting of the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/site-types/items.

hydrologic_unit_code
: The hydrologic unit code (HUC) for the monitoring location. Supports prefix matching — querying with a shorter HUC (e.g. "04") matches all locations within that hydrologic region.

basin_code
: The Basin Code or "drainage basin code" is a two-digit code that further subdivides the 8-digit hydrologic-unit code. The drainage basin code is defined by the USGS State Office where the monitoring location is located.

altitude
: Altitude of the monitoring location referenced to the specified Vertical Datum.

altitude_accuracy
: Accuracy of the altitude, in feet. An accuracy of +/- 0.1 foot would be entered as ".1". Many altitudes are interpolated from the contours on topographic maps; accuracies determined in this way are generally entered as one-half of the contour interval.

altitude_method_code
: Codes representing the method used to measure altitude.

altitude_method_name
: The name of the method used to measure altitude.

vertical_datum
: The datum used to determine altitude and vertical position at the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/altitude-datums/items.

vertical_datum_name
: The datum used to determine altitude and vertical position at the monitoring location. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/altitude-datums/items.

horizontal_positional_accuracy_code
: Indicates the accuracy of the latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-accuracy-codes/items.

horizontal_positional_accuracy
: Indicates the accuracy of the latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-accuracy-codes/items.

horizontal_position_method_code
: Indicates the method used to determine latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-method-codes/items.

horizontal_position_method_name
: Indicates the method used to determine latitude longitude values. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-method-codes/items.

original_horizontal_datum
: Coordinates are published in EPSG:4326 / WGS84 / World Geodetic System 1984. This field indicates the original datum used to determine coordinates before they were converted. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-datum-codes/items.

`original_horizontal_datum_name`
: Coordinates are published in EPSG:4326 / WGS84 / World Geodetic System 1984. This field indicates the original datum used to determine coordinates before they were converted. A list of codes is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/coordinate-datum-codes/items.

`drainage_area`
: The area enclosed by a topographic divide from which direct surface runoff from precipitation normally drains by gravity into the stream above that point.

`contributing_drainage_area`
: The contributing drainage area of a lake, stream, wetland, or estuary monitoring location, in square miles. This item should be present only if the contributing area is different from the total drainage area. This situation can occur when part of the drainage area consists of very porous soil or depressions that either allow all runoff to enter the groundwater or traps the water in ponds so that rainfall does not contribute to runoff. A transbasin diversion can also affect the total drainage area.

`time_zone_abbreviation`
: A short code describing the time zone used by a monitoring location.

`uses_daylight_savings`
: A flag indicating whether or not a monitoring location uses daylight savings.

`construction_date`
: Date the well was completed.

`aquifer_code`
: Local aquifers in the USGS water resources data base are identified by a geohydrologic unit code (a three-digit number related to the age of the formation, followed by a 4 or 5 character abbreviation for the geologic unit or aquifer name).

`national_aquifer_code`
: National aquifers are the principal aquifers or aquifer systems in the United States, defined as regionally extensive aquifers or aquifer systems that have the potential to be used as a source of potable water. Not all groundwater monitoring locations can be associated with a National Aquifer. Such monitoring locations will not be retrieved using this search criteria. A list of National aquifer codes and names is available at https://api.waterdata.usgs.gov/ogcapi/v1/collections/national-aquifer-codes/items.

`aquifer_type_code`
: Describes the confinement status of an aquifer at the monitoring location. A confined aquifer is an aquifer below the land surface that is saturated with water. A water table–or unconfined–aquifer is an aquifer whose upper water surface (water table) is at atmospheric pressure, and thus is able to rise and fall.

`well_constructed_depth`
: The depth of the finished well, in feet below land surface datum. Note: Not all groundwater monitoring locations have information on Well Depth. Such monitoring locations will not be retrieved using this search criteria.

`hole_constructed_depth`
: The total depth to which the hole is drilled, in feet below land surface datum. Note: Not all groundwater monitoring locations have information on Hole Depth. Such monitoring locations will not be retrieved using this search criteria.

`depth_source_code`
: A code indicating the source of water-level data.

`revision_note` Approved water data are considered published record, but on occasion changes or deletions (revisions) must be made to data after they are approved. Data revisions are rare because of USGS quality assurance practices, including documentation of all data before they are officially approved. This field contains text explanations for data revisions at this monitoring location. Changes to data also are indicated with revision qualifier codes alongside the data. Text explanations before 2017 are not necessarily available online, but can be requested.

`revision_created`
The date a revision statement was created.

`revision_modified`
The most recent date a revision statement was modified.

`properties` A vector of requested columns to be returned from the query. Available options are: geometry, monitoring_location_id, agency_code, agency_name, monitoring_location_number, monitoring_location_name, district_code, country_code, country_name, state_code, state_name, county_code, county_name, minor_civil_division_code, site_type_code, site_type, hydrologic_unit_code, basin_code, altitude, altitude_accuracy, altitude_method_code, altitude_method_name, vertical_datum, vertical_datum_name, horizontal_positional_accuracy_code, horizontal_positional_accuracy, horizontal_position_method_code, horizontal_position_method_name, original_horizontal_datum, original_horizontal_datum_name, drainage_area, contributing_drainage_area, time_zone_abbreviation, uses_daylight_savings, construction_date, aquifer_code, national_aquifer_code, aquifer_type_code, well_constructed_depth, hole_constructed_depth, depth_source_code, revision_note, revision_created, revision_modified. The default (`NA`) will return all columns of the data.

`q` Full-text search across the most relevant text fields for this collection (e.g. site name, identifier, number, state, county, and site type). Matching rules:

- Case-insensitive, with prefix matching (e.g. poud matches POUDRE).
- Words separated by spaces are AND'd together (all must match).
- Terms separated by commas are OR'd together (any may match).
- Common abbreviations are expanded, so river also matches sites stored as RV (and vice versa). Examples are: q=poudre - sites whose name/identifier starts with or contains poudre q=colorado river - sites matching both colorado and river/rv q=poudre,cache creek - sites matching poudre OR (cache AND creek/ck)

`bbox` Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`skipGeometry` This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`...` Not used. Included to help differentiate official Water Data API arguments from more seldom used, optional dataRetrieval-specific arguments.

convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.
limit	numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
no_paging	logical, defaults to FALSE. If TRUE, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use TRUE with caution.
chunk_size	Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
site <- "USGS-02238500"
site_info <- read_waterdata_monitoring_location(monitoring_location_id = site)

site_slim <- read_waterdata_monitoring_location(
                            monitoring_location_id = c("USGS-05114000",
                                                       "USGS-09423350"),
                            properties = c("monitoring_location_id",
                                           "state_name",
                                           "county_name",
                                           "country_name"))

site_slim_no_sf_slim <- read_waterdata_monitoring_location(state_name = "Wisconsin",
                                          properties = c("monitoring_location_id",
                                                         "state_name",
                                                         "county_name",
                                                         "country_name",
                                                         "site_type"),
                                          site_type = "Well",
                                          skipGeometry = TRUE)

site_info_no_sf <- read_waterdata_monitoring_location(
     monitoring_location_id = site_slim_no_sf_slim$monitoring_location_id[1:1000],
     skipGeometry = TRUE)

bbox_vals = c(-94.00, 35.0, -93.5, 35.5)
multi_site <- read_waterdata_monitoring_location(bbox = bbox_vals)

poudre <- read_waterdata_monitoring_location(q = "poudre")
```

`read_waterdata_parameter_codes` *Get USGS Parameter Code Information*

Description

Parameter codes are 5-digit codes and associated descriptions used to identify the constituent measured and the units of measure. Some parameter code definitions include information about the sampling matrix, fraction, and methods used to measure the constituent. Some parameters are fixed-value (fxd) numeric codes having textual meaning (for example: parameter code 00041 is a weather code parameter, code of 60 means rain), but more commonly represent a numeric value for chemical, physical, or biological data.

Usage

```
read_waterdata_parameter_codes(
  parameter_code = NA_character_,
  parameter_name = NA_character_,
  unit_of_measure = NA_character_,
  parameter_group_code = NA_character_,
  parameter_description = NA_character_,
  medium = NA_character_,
  statistical_basis = NA_character_,
  weight_basis = NA_character_,
  sample_fraction = NA_character_,
  temperature_basis = NA_character_,
  epa_equivalence = NA_character_,
  properties = NA_character_,
  ...,
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`parameter_code`	Parameter code.
`parameter_name`	Parameter short name.
`unit_of_measure`	Parameter reporting units defined to cooperate with descriptions by USEPA.
`parameter_group_code`	Categorical groupings of parameters by water-quality data type for display and report ordering
`parameter_description`	Parameter description.

medium	Parameter medium.
statistical_basis	Parameter statistical basis.
weight_basis	Parameter weight basis.
sample_fraction	Parameter fraction.
temperature_basis	Parameter temperature basis.
epa_equivalence	Indicates the relationship of the USGS parameter code to the EPA code.
properties	A vector of requested columns to be returned from the query. Available options are: geometry, parameter_code_id, parameter_name, unit_of_measure, parameter_group_code, parameter_description, medium, statistical_basis, time_basis, weight_basis, particle_size_basis, sample_fraction, temperature_basis, epa_equivalence. The default (NA) will return all columns of the data.
...	Not used. Included to help differentiate official Water Data API arguments from more seldom used, optional dataRetrieval-specific arguments.
limit	The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.
attach_request	logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Examples

```
pcode <- "00060"
pcode_info <- read_waterdata_parameter_codes(parameter_code = pcode)

pcodes <- read_waterdata_parameter_codes(parameter_code = c("00660", "00060"))

# equivalent to read_waterdata_metadata("parameter-codes")
all_pcodes <- read_waterdata_parameter_codes()

total_nutrients <- read_waterdata_parameter_codes(parameter_group_code = "NUT",
                                          sample_fraction = "Total")

group_of_nutrients <- read_waterdata_parameter_codes(parameter_group_code = "NUT",
                                                     unit_of_measure = c("mg/l",
                                                     "mg/l as N", "mg/l NO3",
                                                     "mg/l asNO2"))
```

read_waterdata_peaks *Get USGS Peak Data*

Description

Annual peak flow values are the maximum instantaneous streamflow values recorded at a particular site for the entire water year from October 1 to September 30. Note that the annual peak flow value may not occur at the same time the maximum water level occurs due to conditions such as backwater, tidal fluctuations, etc.

Usage

```
read_waterdata_peaks(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  properties = NA_character_,
  time_series_id = NA_character_,
  unit_of_measure = NA_character_,
  value = NA,
  last_modified = NA_character_,
  water_year = NA_character_,
  year = NA_character_,
  month = NA_character_,
  day = NA_character_,
  time_of_day = NA_character_,
  peak_since = NA_character_,
  qualifier = NA_character_,
  skipGeometry = NA,
  time = NA_character_,
  bbox = NA,
  ...,
  allow_incomplete_dates = FALSE,
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_meta"),
  limit = getOption("dataRetrieval.limit"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

monitoring_location_id
: A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code` Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

Multiple parameter_codes can be requested as a character vector.

`properties` A vector of requested columns to be returned from the query. Available options are: geometry, time_series_id, monitoring_location_id, parameter_code, unit_of_measure, value, last_modified, time, water_year, year, month, day, time_of_day, peak_since, qualifier. The default (NA) will return all columns of the data.

`time_series_id` A unique identifier representing a single time series. This corresponds to the `id` field in the `time-series-metadata` endpoint.

`unit_of_measure`

A human-readable description of the units of measurement associated with an observation.

`value` The value of the observation. Values are transmitted as strings in the JSON response format in order to preserve precision.

`last_modified` The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

See also Details below for more information.

`water_year` The water year (running from October 1st to September 30th) a peak occurred.

`year` The calendar year a peak occurred.

`month` The calendar month a peak occurred. If null, the month a peak occurred is unknown.

`day` The day of the month a peak occurred. If null, the day a peak occurred is unknown.

`time_of_day` The time of day a peak occurred. If null, the time of day a peak occurred is unknown.

`peak_since` If not null, this record represents the peak value for the parameter code since the year contained in "peak_since".

`qualifier` This field indicates any qualifiers associated with an observation, for instance if a sensor may have been impacted by ice or if values were estimated.

skipGeometry — This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default NA will not specify the argument in the request.

time — The date an observation represents. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a time that intersects the value of datetime are selected. If a feature has multiple temporal properties, it is the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.

See also Details below for more information.

bbox — Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

... — Arguments that can be queried, but are not returned. These are used as alternatives to specifying specific monitoring_location_ids. See ?get_monitoring_location_arguments for available arguments.

allow_incomplete_dates — Specifically in the peaks data, exact peak dates are not always known. Sometimes peaks are known just for the year, sometimes they are known to the year and month, and and sometimes to the exact date. This argument determines if incomplete dates + uncertain month/day values are allowed in the "time" column so that it can be a complete Date object (TRUE), or whether to set those dates to NA (FALSE). Peaks with uncertain days are stored on the first of the month, and those with uncertain month stored on January 1. Default is FALSE.

convertType — logical, defaults to TRUE. If TRUE, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

no_paging — logical, defaults to FALSE. If TRUE, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use TRUE with caution.

chunk_size — Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to NA will eliminate site chunking, giving users full control.

limit — numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable

limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (NA) will set the limit to the maximum allowable limit for the service.

attach_request logical, defaults to TRUE. If set to TRUE, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

See Also

get_monitoring_location_arguments()

Examples

```
wi_peaks <- read_waterdata_combined_meta(
               state_name = "Wisconsin",
               data_type = "Peaks",
               parameter_code = "00060")


dv_data_sf <- read_waterdata_peaks(
               monitoring_location_id = wi_peaks$monitoring_location_id[1],
               parameter_code = "00060")

dane <- read_waterdata_peaks(
  state_name = "Wisconsin",
  county_name = "Dane County",
  parameter_code = "00060")

incomplete_dates_not_allowed <- read_waterdata_peaks(
               monitoring_location_id = "USGS-06334330",
               parameter_code = "00060")
incomplete_dates_not_allowed$time
incomplete_dates_allowed <- read_waterdata_peaks(
               monitoring_location_id = "USGS-06334330",
               parameter_code = "00060",
               allow_incomplete_dates = TRUE)
incomplete_dates_allowed$time
```

`read_waterdata_ratings` *Get USGS Rating Curve Data*

Description

Reads current rating table for an active USGS streamgages. More information can be found at https://api.waterdata.usgs.gov/docs/stac/.

Usage

```
read_waterdata_ratings(
  monitoring_location_id = NA_character_,
  file_type = c("exsa", "base", "corr"),
  file_path = tempdir(),
  bbox = NA,
  datetime = NA_character_,
  ...,
  limit = 10000,
  download_and_parse = TRUE
)
```

Arguments

`monitoring_location_id`
: A unique identifier representing a single monitoring location. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location (e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

`file_type`
: Rating file time. Could be any of "exsa", "corr", or "base". If `file_type` is "base" then the columns are INDEP, typically the gage height, in feet; DEP, typically the streamflow, in cubic feet per second; and STOR, where "*" indicates that the pair are a fixed point of the rating curve. If `file_type` is "exsa" then an additional column, SHIFT, is included that indicates the current shift in the rating for that value of INDEP. If `file_type` is "corr" then the columns are INDEP, typically the gage height, in feet; CORR, the correction for that value; and CORRINDEP, the corrected value for CORR.

`file_path`
: Path to save the rating curve rdb files. The default is `tempdir()`, which will wipe out the files.

`bbox`
: Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric

vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`datetime` Only return items that have a temporal property that intersects this value. Either a date-time or an interval, open or closed. See Details below.

`...` Not used.

`limit` Limits the number of results that are included in each page of the response (capped at the default 10,000).

`download_and_parse`
Logical to define whether or not to download, parse, and return a list of data frames with rating curve data (`TRUE`), or to return just a list of available rating curve files (`FALSE`). Default is `TRUE`.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

Value

List of named lists, one per requested rating file. Each element contains:

ratings Data frame of the rating curve.

metadata Data frame of header/value pairs parsed from the comment attribute of the ratings file.

Examples

```
monitoring_location_id <- c("USGS-01104475", "USGS-01104460")
ratings_exsa <- read_waterdata_ratings(
      monitoring_location_id = monitoring_location_id,
      file_type = "exsa")

head(ratings_exsa[["USGS-01104475.exsa.rdb"]]$ratings)
m1 <- ratings_exsa[["USGS-01104475.exsa.rdb"]]$metadata
m1

ratings_corr <- read_waterdata_ratings(
      monitoring_location_id = monitoring_location_id,
      file_type = "corr")
```

```
head(ratings_corr[["USGS-01104460.corr.rdb"]]$ratings)
m2 <- ratings_corr[["USGS-01104460.corr.rdb"]]$metadata
m2

rating_2 <- read_waterdata_ratings(
      monitoring_location_id = monitoring_location_id,
      file_type = c("corr", "exsa"))
names(rating_2)
m3 <- rating_2$`USGS-01104460.exsa.rdb`$metadata
rat_data <- rating_2$`USGS-01104460.exsa.rdb`$ratings

bbox <- c(-95.00, 40.0, -92.0, 42)

bbox_query <- read_waterdata_ratings(bbox = bbox,
                                     download_and_parse = FALSE)
length(bbox_query)
recent_query <- read_waterdata_ratings(bbox = bbox,
                                       datetime = c(Sys.Date()-7, NA),
                                       download_and_parse = FALSE)
```

`read_waterdata_samples` *USGS Samples Data*

Description

This function creates the call and gets the data for discrete water quality samples data service described at https://waterdata.usgs.gov/download-samples/.

Usage

```
read_waterdata_samples(
  monitoringLocationIdentifier = NA,
  siteTypeCode = NA,
  boundingBox = NA,
  hydrologicUnit = NA,
  activityMediaName = NA,
  characteristicGroup = NA,
  characteristic = NA,
  characteristicUserSupplied = NA,
  activityStartDateLower = NA,
  activityStartDateUpper = NA,
  countryFips = NA,
  stateFips = NA,
  countyFips = NA,
  projectIdentifier = NA,
```

```
  recordIdentifierUserSupplied = NA,
  siteTypeName = NA,
  usgsPCode = NA,
  pointLocationLatitude = NA,
  pointLocationLongitude = NA,
  pointLocationWithinMiles = NA,
  dataType = "results",
  dataProfile = NA,
  tz = "UTC",
  convertType = TRUE
)
```

Arguments

`monitoringLocationIdentifier`
: A monitoring location identifier has two parts: the agency code and the location number, separated by a dash (-). Location identifiers should be separated with commas, for example: AZ014-320821110580701, CAX01-15304600, USGS-040851385. Location numbers without an agency prefix are assumed to have the prefix USGS.

`siteTypeCode`
: Site type code query parameter. See available options by running `check_waterdata_sample_params("s`

`boundingBox`
: North and South are latitude values; East and West are longitude values. A vector of 4 (west, south, east, north) is expected. An example would be: c(-92.8, 44.2, -88.9, 46.0).

`hydrologicUnit`
: Hydrologic Unit Codes (HUCs) identify physical areas within the US that drain to a certain portion of the stream network. This filter accepts values containing 2, 4, 6, 8, 10 or 12 digits.

`activityMediaName`
: Sample media refers to the environmental medium that was sampled or analyzed.

`characteristicGroup`
: Characteristic group is a broad category describing the sample. See available options by running `check_waterdata_sample_params("characteristicgroup")$characteristicGrou`

`characteristic`
: Characteristic is a specific category describing the sample. See available options by running `check_waterdata_sample_params("characteristics")$characteristicName`.

`characteristicUserSupplied`
: Observed property is the USGS term for the constituent sampled and the property name gives a detailed description of what was sampled. Observed property is mapped to characteristicUserSupplied and replaces the parameter name and pcode USGS previously used to describe discrete sample data. Find more information in the Observed Properties and Parameter Codes section of the Code Dictionary found here: https://waterdata.usgs.gov/code-dictionary/.

`activityStartDateLower`
: The service will return records with dates earlier than the value entered for activityStartDateUpper. Can be an R Date object, or a string with format YYYY-MM-DD. The logic is inclusive, i.e. it will also return records that match the date.

activityStartDateUpper
: The service will return records with dates later than the value entered for activityStartDateLower. Can be an R Date object, or a string with format YYYY-MM-DD. The logic is inclusive, i.e. it will also return records that match the date.

countryFips
: Country query parameter. Do not set redundant parameters. If another query parameter contains the country information, leave this parameter set to the default NA. See available options by running `check_waterdata_sample_params("countries")`, where the "id" field contains the value to use in the countryFips input.

stateFips
: State query parameter. To get a list of available state fips, run `check_waterdata_sample_params("state`
The "fips" can be created using the function `stateCdLookup` - for example: `stateCdLookup("WI", "fips")`. FIPs codes for states take the format: CountryAbbrev:StateNumber, like US:55 for Wisconsin.

countyFips
: County query parameter. To get a list of available counties, run `check_waterdata_sample_params("cou`
The "Fips" can be created using the function `countyCdLookup` - for example: `countyCdLookup("WI", "Dane", "fips")` for Dane County, WI. FIPs codes for counties take the format: CountryAbbrev:StateNumber:CountyNumber, like US:55:025 for Dane County, WI.

projectIdentifier
: Project identifier query parameter. This information would be needed from prior project information.

recordIdentifierUserSupplied
: Record identifier, user supplied identifier. This information would be needed from the data supplier.

siteTypeName
: Site type name query parameter. See available options by running `check_waterdata_sample_params("s`

usgsPCode
: USGS parameter code. See available options by running `check_waterdata_sample_params("characte`

pointLocationLatitude
: Latitude for a point/radius query (decimal degrees). Must be used with pointLocationLongitude and pointLocationWithinMiles.

pointLocationLongitude
: Longitude for a point/radius query (decimal degrees). Must be used with pointLocationLatitude and pointLocationWithinMiles.

pointLocationWithinMiles
: Radius for a point/radius query. Must be used with pointLocationLatitude and pointLocationLongitude

dataType
: Options include: "Results", "Monitoring locations", "Activities", "Projects", and "Organizations".

dataProfile
: Profile depends on type. Options for "results" dataType are: "fullphyschem", "basicphyschem", "fullbio", "basicbio", "narrow", "resultdetectionquantitationlimit", "labsampleprep", "count". Options for "locations" are: "site" and "count". Options for "activities" are "sampact", "actmetric", "actgroup", and "count". Options for "projects" are: "project" and "projectmonitoringlocationweight". Options for "organizations" are: "organization" and "count".

tz
: character to set timezone attribute of datetime. Default is UTC (properly accounting for daylight savings times based on the data's provided tz_cd column).

Possible values include "America/New_York","America/Chicago", "America/Denver","America/Los_An
"America/Anchorage","America/Honolulu","America/Jamaica","America/Managua",
"America/Phoenix", and "America/Metlakatla"

convertType logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character.

Examples

```
ph_data <- read_waterdata_samples(
               monitoringLocationIdentifier = "USGS-04074950",
               characteristicUserSupplied = "pH, water, unfiltered, field",
               activityStartDateUpper = "2000-01-01",
               dataProfile = "narrow")

nameToUse <- "pH"
pHData <- read_waterdata_samples(monitoringLocationIdentifier = "USGS-04024315",
                         characteristic = nameToUse)
ncol(pHData)
attr(pHData, "url")
attr(pHData, "queryTime")

summary_data <- read_waterdata_samples(monitoringLocationIdentifier = "USGS-04024315",
                               dataType = "projects")
```

---

read_waterdata_stats_por

Get USGS daily data statistics

Description

This service provides endpoints for access to computations on the historical record regarding water conditions. For more information regarding the calculation of statistics and other details, please visit the Statistics documentation page.

Note: The /statistics API is under active beta development and subject to change. Improved handling of significant figures will be addressed in a future release.

read_waterdata_stats_por Returns day-of-year and month-of-year statistics matching your query.

read_waterdata_stats_daterange Returns monthly and annual statistics matching your query.

Usage

```
read_waterdata_stats_por(
  approval_status = NA,
  computation_type = NA_character_,
  country_code = NA_character_,
  state_code = NA_character_,
  county_code = NA_character_,
  start_date = NA_character_,
  end_date = NA_character_,
  normal_type = NA_character_,
  monitoring_location_id = NA_character_,
  parent_time_series_id = NA_character_,
  site_type_code = NA_character_,
  site_type_name = NA_character_,
  parameter_code = NA_character_,
  page_size = NA
)

read_waterdata_stats_daterange(
  approval_status = NA,
  computation_type = NA_character_,
  country_code = NA_character_,
  state_code = NA_character_,
  county_code = NA_character_,
  start_date = NA_character_,
  end_date = NA_character_,
  interval_type = NA_character_,
  monitoring_location_id = NA_character_,
  parent_time_series_id = NA_character_,
  site_type_code = NA_character_,
  site_type_name = NA_character_,
  parameter_code = NA_character_,
  page_size = NA
)
```

Arguments

approval_status	Whether to include approved and/or provisional observations. At this time, only approved observations are returned.
computation_type	Desired statistical computation method. Available values: "arithmetic_mean", "maximum", "median", "minimum", "percentile".
country_code	Country Query Parameter. Accepts multiple values (see examples). If one of country, county, or state code is supplied then the other two arguments do not need to be specified.
state_code	State Query Parameter. Accepts multiple values in a character vector.

county_code	County Query Parameter. Accepts multiple values in a character vector.
start_date	Start Date Query Parameter. The logic is inclusive i.e., it will also return records that match the date. If an end date is supplied, but no start date is supplied, then statistics will be supplied for the entire period of record ending with the end date. If an end date is not supplied, but a start date is supplied then statistics will be supplied for the period of record following the start date. If no start or end date are supplied then statistics will be supplied for the entire period of record.
end_date	End Date Query Parameter. The logic is inclusive i.e., it will also return records that match the date.
normal_type	Normal Type Query Parameter. If unspecified, all matching data will be returned. Otherwise, it will filter the results to one of the following normals: day-of-year, month-of-year. Available values: "DOY", "MOY".
monitoring_location_id	Each monitoring location has been assigned a unique station number that places them in downstream order. Accepts multiple values in a character vector.
parent_time_series_id	The parent_time_series_id returns statistics tied to a particular database entry. Accepts multiple values in a character vector. If no parent time series identifier is supplied, then all records matching the rest of the provided criteria will be returned.
site_type_code	Site Type Code Query Parameter. Accepts multiple values in a character vector. If no Site Type code is specified, statistics of all site types with the matching Monitoring Location Identifier will be returned.
site_type_name	Site Type Name Query Parameter. If no Site Type name is specified, statistics of all site types with the matching Monitoring Location Identifier will be returned.
parameter_code	USGS Parameter Code Query Parameter. Accepts multiple values in a character vector. If no USGS parameter code is specified, but a Monitoring Location Identifier is supplied, then all statistics and their parameter codes with a matching monitoring location identifier will be returned. All statistics within the period of record will be returned if no parameter code or monitoring location identifier are specified.
page_size	Return a defined number of results (default: 1000).
interval_type	Interval Type Query Parameter. If unspecified, all matching data will be returned. Otherwise, it will filter the results to one or more of the following intervals: month, calendar year, water year. Available values: "M", "CY", "WY".

See Also

https://api.waterdata.usgs.gov/statistics/v0/docs

Examples

```
# All day-of-year and month-of-year statistics for two sites
x1 <- read_waterdata_stats_por(
```

```
  monitoring_location_id = c("USGS-02319394", "USGS-02171500")
)

# Request only month-of-year statistics using normal_type arg
x1 <- read_waterdata_stats_por(
  monitoring_location_id = c("USGS-02319394", "USGS-02171500"),
  normal_type = "MOY"
)

# Request temperature percentiles for specific month-day range
# Returns:
# - Day-of-year temperature percentiles for each day between June 1 through June 15.
# - Month-of-year percentiles for June, computed using
#    all June data (not just June 1 through June 15).
# Note: the month-of-year percentiles are returned only when the month-day range includes
#  the beginning of the month (e.g., "06-01")
x2 <- read_waterdata_stats_por(
  monitoring_location_id = c("USGS-02319394", "USGS-02171500"),
  parameter_code = "00010",
  start_date = "06-01", end_date = "06-15",
  computation_type = "percentile"
)

# All calendar month, calendar year, and water year statistics for two sites
x3 <- read_waterdata_stats_daterange(
  monitoring_location_id = c("USGS-02319394", "USGS-02171500")
)

# Request only calendar year statistics
x3 <- read_waterdata_stats_daterange(
  monitoring_location_id = c("USGS-02319394", "USGS-02171500"),
  interval_type = "CY"
)

# Request specific gage height and discharge summaries for a limited date range
# Returns:
# - calendar month summaries for each month between January, 2010 through December, 2011
# - calendar year summaries for 2010 and 2011
# - water year summaries for WY2010, WY2011, and WY2012
x4 <- read_waterdata_stats_daterange(
  monitoring_location_id = c("USGS-02319394", "USGS-02171500"),
  parameter_code = c("00065", "00060"),
  start_date = "2010-01-01", end_date = "2011-12-31",
  computation_type = c("minimum", "median", "maximum")
)
```

---

read_waterdata_ts_meta

Get USGS Time Series Metadata

Description

Daily data and continuous measurements are grouped into time series, which represent a collection of observations of a single parameter, potentially aggregated using a standard statistic, at a single monitoring location. This endpoint provides metadata about those time series, including their operational thresholds, units of measurement, and when the earliest and most recent observations in a time series occurred.

Usage

```
read_waterdata_ts_meta(
  monitoring_location_id = NA_character_,
  parameter_code = NA_character_,
  parameter_name = NA_character_,
  properties = NA_character_,
  statistic_id = NA_character_,
  last_modified = NA_character_,
  begin_utc = NA_character_,
  end_utc = NA_character_,
  hydrologic_unit_code = NA_character_,
  state_name = NA_character_,
  unit_of_measure = NA_character_,
  computation_period_identifier = NA_character_,
  computation_identifier = NA_character_,
  thresholds = NA,
  sublocation_identifier = NA_character_,
  primary = NA_character_,
  parent_time_series_id = NA_character_,
  time_series_id = NA_character_,
  web_description = NA_character_,
  skipGeometry = NA,
  bbox = NA,
  begin = NA_character_,
  end = NA_character_,
  ...,
  limit = getOption("dataRetrieval.limit"),
  convertType = getOption("dataRetrieval.convertType"),
  no_paging = getOption("dataRetrieval.no_paging"),
  chunk_size = getOption("dataRetrieval.site_chunk_size_meta"),
  attach_request = getOption("dataRetrieval.attach_request")
)
```

Arguments

`monitoring_location_id`

A unique identifier representing a single monitoring location. This corresponds to the `id` field in the `monitoring-locations` endpoint. Monitoring location IDs are created by combining the agency code of the agency responsible for the monitoring location (e.g. USGS) with the ID number of the monitoring location

(e.g. 02238500), separated by a hyphen (e.g. USGS-02238500).

Multiple monitoring_location_ids can be requested as a character vector.

`parameter_code` Parameter codes are 5-digit codes used to identify the constituent measured and the units of measure. A complete list of parameter codes and associated groupings can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/parameter-codes/items.

Multiple parameter_codes can be requested as a character vector.

`parameter_name` A human-understandable name corresponding to `parameter_code`.

`properties` A vector of requested columns to be returned from the query. Available options are: geometry, time_series_id, unit_of_measure, parameter_name, parameter_code, statistic_id, last_modified, begin, end, computation_period_identifier, computation_identifier, thresholds, sublocation_identifier, primary, monitoring_location_id, web_description, parameter_description, parent_time_series_id, data_gap_interval, statistics_begin. The default (`NA`) will return all columns of the data.

`statistic_id` A code corresponding to the statistic an observation represents. Example codes include 00001 (max), 00002 (min), and 00003 (mean). A complete list of codes and their descriptions can be found at https://api.waterdata.usgs.gov/ogcapi/v1/collections/statistic-codes/items.

Multiple statistic_ids can be requested as a character vector.

`last_modified` The last time a record was refreshed in our database. This may happen due to regular operational processes and does not necessarily indicate anything about the measurement has changed. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `last_modified` that intersects the value of datetime are selected.

See also Details below for more information.

`begin_utc` Deprecated in v1. Use "begin" instead.

`end_utc` Deprecated in v1. Use "end" instead.

`hydrologic_unit_code`

Deprecated in v1. Use `read_waterdata_combined_meta` for similar functionality.

`state_name` Deprecated in v1. Use `read_waterdata_combined_meta` for similar functionality.

`unit_of_measure`

A human-readable description of the units of measurement associated with an observation.

`computation_period_identifier`

Indicates the period of data used for any statistical computations. Multiple computation_period_identifiers can be requested as a character vector.

`computation_identifier`
: Indicates the computation performed to calculate this time series. Values of "Instantaneous" reflect point measurements. Multiple computation_identifiers can be requested as a character vector.

`thresholds`
: Thresholds represent known numeric limits for a time series, for example the historic maximum value for a parameter or a level below which a sensor is non-operative. These thresholds are sometimes used to automatically determine if an observation is erroneous due to sensor error, and therefore shouldn't be included in the time series.

`sublocation_identifier`
: An optional human-readable identifier used to specify where measurements are recorded at a monitoring location.

`primary`
: A flag identifying if the time series is a "primary" time series. "Primary" time series (which have this flag) are standard observations which undergo Bureau review and approval processes. Non-primary time series, which will have missing values for "primary", are provisional datasets made available to meet the need for timely best science and to assist with daily operations which need real-time information. Non-primary time series data are only retained by this system for 120 days.

`parent_time_series_id`
: The unique identifier representing the parent or "upchain" time series that a daily values time series is generated from. Daily values time series have one and only one parent time series.

`time_series_id`
: A unique identifier representing a single time series. This corresponds to the "time_series_id" field in other endpoints.

`web_description`
: An optional description of the time series. WDFN and other USGS data dissemination products use this field, in combination with sublocation_identifier, to distinguish the differences between multiple time series for the same parameter code, statistic code, and monitoring location.

`skipGeometry`
: This parameter can be used to skip response geometries for each feature. The returning object will be a data frame with no spatial information. The default `NA` will not specify the argument in the request.

`bbox`
: Only features that have a geometry that intersects the bounding box are selected.The bounding box is provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth). Coordinates are assumed to be in crs 4326. The expected format is a numeric vector structured: c(xmin,ymin,xmax,ymax). Another way to think of it is c(Western-most longitude, Southern-most latitude, Eastern-most longitude, Northern-most longitude).

`begin`
: The datetime of the earliest observation in the time series. Together with `end`, this field represents the period of record of a time series. Note that some time series may have large gaps in their collection record. You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `begin` that intersects the value of datetime are selected.

`end` The datetime of the most recent observation in the time series. Data returned by this endpoint updates at most once per day, and potentially less frequently than that, and as such there may be more recent observations within a time series than the time series `end` value reflects. Together with `begin`, this field represents the period of record of a time series. It is additionally used to determine whether a time series is "active". You can query this field using date-times or intervals, adhering to RFC 3339, or using ISO 8601 duration objects. Intervals may be bounded or half-bounded (double-dots at start or end). Examples:

- A date-time: "2018-02-12T23:20:50Z"
- A bounded interval: "2018-02-12T00:00:00Z/2018-03-18T12:31:12Z"
- Half-bounded intervals: "2018-02-12T00:00:00Z/.." or "../2018-03-18T12:31:12Z"
- Duration objects: "P1M" for data from the past month or "PT36H" for the last 36 hours

Only features that have a `end` that intersects the value of datetime are selected.

`...` Not used. Included to help differentiate official Water Data API arguments from more seldom used, optional dataRetrieval-specific arguments.

`limit` numeric, The optional limit parameter is used to control the subset of the selected features that should be returned in each page. The maximum allowable limit is 50,000. It may be beneficial to set this number lower if your internet connection is spotty. The default (`NA`) will set the limit to the maximum allowable limit for the service.

`convertType` logical, defaults to TRUE. If `TRUE`, the function will convert the data to dates, any qualifiers to string vector and reorder the returned data frame.

`no_paging` logical, defaults to FALSE. If `TRUE`, the data will be requested from a native csv format. This can be dangerous because the data will cut off at 50,000 rows without indication that more data is available. Use `TRUE` with caution.

`chunk_size` Number of monitoring_location_ids to chunk requests into. The default for functions that don't generally return long-term data records is 250, while the default for time series functions is 10. Setting to `NA` will eliminate site chunking, giving users full control.

`attach_request` logical, defaults to TRUE. If set to `TRUE`, the full request sent to the Water Data API is attached as an attribute to the data set.

Details

You can also use a vector of length 2 for any time queries (such as time or last_modified). The first value is the starting date (or datetime), the second value is the ending date(or datetime). NA's within the vector indicate a half-bound date. For example, `time = c("2024-01-01", NA)` will return all

data starting at 2024-01-01. `time = c(NA, "2024-01-01")` will return all data from the beginning of the timeseries until 2024-01-01. By default, time is assumed UTC, although time zone attributes will be accommodated. As an example, setting `time = as.POSIXct(c("2021-01-01 12:00:00","2021-01-01 14:00"), tz = "America/New_York")` will request data that between noon and 2pm eastern time on 2021-01-01. All time values RETURNED from the service are UTC with the exception of daily data, which returns time values in local dates.

Examples

```
site <- "USGS-02238500"
meta_1 <- read_waterdata_ts_meta(monitoring_location_id = site)

meta_multi <- read_waterdata_ts_meta(monitoring_location_id =  c("USGS-01491000",
                                                                 "USGS-01645000"),
                             parameter_code = c("00060", "00010"),
                             properties = c("monitoring_location_id",
                                            "parameter_code",
                                            "begin",
                                            "end",
                                            "time_series_id"),
                             skipGeometry = TRUE)

meta_wi <- read_waterdata_ts_meta(state_name = "Wisconsin")
```

`renameNWISColumns` *renameColumns*

Description

Rename columns coming back from NWIS data retrievals. Daily and unit value columns have names derived from their data descriptor, parameter, and statistic codes. This function reads information from the header and the arguments in the call to to rename those columns.

Usage

```
renameNWISColumns(
  rawData,
  p00010 = "Wtemp",
  p00045 = "Precip",
  p00060 = "Flow",
  p00065 = "GH",
  p00095 = "SpecCond",
  p00300 = "DO",
  p00400 = "pH",
  p62611 = "GWL",
```

```
  p63680 = "Turb",
  p72019 = "WLBLS",
  ...
)
```

Arguments

rawData	the daily- or unit-values datset retrieved from NWISweb.
p00010	the base name for parameter code 00010.
p00045	the base name for parameter code 00045.
p00060	the base name for parameter code 00060.
p00065	the base name for parameter code 00065.
p00095	the base name for parameter code 00095.
p00300	the base name for parameter code 00300.
p00400	the base name for parameter code 00400.
p62611	the base name for parameter code 62611.
p63680	the base name for parameter code 63680.
p72019	the base name for parameter code 72019.
...	named arguments for the base name for any other parameter code. The form of the name must be like pXXXXX, where XXXXX is the parameter code.

Value

A dataset like data with selected columns renamed.

Note

The following statistics codes are converted by renameNWISColumns.

00000 Instantaneous Value, suffix: Inst

00001 Maximum value, suffix: Max

00002 Minimum value, suffix: Min

00003 Mean value, no suffix

00006 Sum of values, suffix: Sum

00007 Modal value, suffix: Mode

00008 Median value, suffix: Median

00012 Equivalent mean value, suffix: EqMean

00021 Tidal high-high value, suffix: HiHiTide

00022 Tidal low-high value, suffix: LoHiTide

00023 Tidal high-low value, suffix: HiLoTide

00024 Tidal low-low value, suffix: LoLoTide

See Also

readNWISdv(), readNWISuv()

setAccess *Set data endpoint*

Description

access Indicate which dataRetrieval access code you want to use options: `c('public','internal')`

Usage

```
setAccess(access = "public")
```

Arguments

access	code for data access. Options are: "public","internal","cooperator", or "USGS". • "internal" represents Access=3 ...for a single water science center • "USGS" represents Access=2 ...for all water science centers • "cooperator" represents Access=1 • "public" represents Access=0, public access

Author(s)

Luke Winslow, Jordan S Read

Examples

```
setAccess("internal")

setAccess("public")
```

stateCd *US State Code Lookup Table*

Description

Classic lookup table for states. Has been replaced in functions with `check_waterdata_sample_params("states")`.

Value

stateCd data frame.

Name	Type	Description
STATE	character	FIPS State Code
STUSAB	character	Official United States Postal Service (USPS) Code
STATE_NAME	character	State Name
STATENS	character	Geographic Names Information System Identifier (GNISID)

Examples

```
head(stateCd)
```

---

stateCdLookup *State code look up*

Description

Function to simplify finding state and state code definitions. Used in `readNWISdata` and `readWQPdata`.

Usage

```
stateCdLookup(input, outputType = "postal", country = "US")
```

Arguments

`input`	could be character (full name, abbreviation, id), or numeric (id)
`outputType`	character can be "postal", "fullName", "tableIndex", or "id".
`country`	description

Examples

```
fullName <- stateCdLookup("wi", "fullName")
abbriev <- stateCdLookup("Wisconsin", "postal")
id <- stateCdLookup("WI", "id")
name <- stateCdLookup(55, "fullName")
fips <- stateCdLookup("WI", "fips")
canada_st <- stateCdLookup(13, "fullName", country = "CA")
mexico_st <- stateCdLookup(13, "fullName", country = "MX")
stateCdLookup(c("West Virginia", "Wisconsin", 200, 55, "MN"))
```

summarize_waterdata_samples *USGS Samples Summary Data*

Description

This function creates the call and gets the data for discrete water quality samples summary data service described at https://api.waterdata.usgs.gov/samples-data/docs.

Usage

```
summarize_waterdata_samples(monitoringLocationIdentifier)

summarize_USGS_samples(monitoringLocationIdentifier)
```

Arguments

monitoringLocationIdentifier	A single monitoring location identifier with two parts, separated by a dash (-): the agency code and the location number. Examples: USGS-040851385, AZ014-320821110580701, CAX01-15304600. The summary service accepts only one site at a time; supplying a vector of length > 1 raises an error. The agency prefix is required: bare location numbers (e.g. "040851385") are accepted by the service but return an empty result.

Value

data frame with summary of data available based on the monitoringLocationIdentifier

Examples

```
monitoringLocationIdentifier <- "USGS-04074950"

what_data <- summarize_waterdata_samples(monitoringLocationIdentifier)
```

whatNWISdata *USGS data availability*

Description

Imports a table of available parameters, period of record, and count. See https://waterservices.usgs.gov/docs/site-service/ for more information.

Usage

```
whatNWISdata(..., convertType = TRUE, override_error = FALSE)
```

Arguments

...	see https://waterservices.usgs.gov/docs/site-service/ for a complete list of options. A list of arguments can also be supplied.
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character
override_error	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to TRUE should only be used as a tool to convert readNWIS to read_waterdata functions.

Details

This function requires users to create their own arguments based on the NWIS web services. It is a more complicated function to use compared to other NWIS functions such as readNWISdv(), readNWISuv(), etc. However, this function adds a lot of flexibility to the possible queries. If the "service" argument is included, the results will be filtered to the proper data_type_cd. This is a great function to use before a large data set, by filtering down the number of sites that have useful data.

Value

A data frame with the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
station_nm	character	Site name
site_tp_cd	character	Site type
dec_lat_va	numeric	Decimal latitude
dec_long_va	numeric	Decimal longitude
coord_acy_cd	character	Latitude-longitude accuracy
dec_coord_datum_cd	character	Decimal Latitude-longitude datum
alt_va	character	Altitude of Gage or land surface
alt_acy_va	character	Altitude accuracy

alt_datum_cd	character	Altitude datum
huc_cd	character	Hydrologic unit code
data_type_cd	character	Data type
parm_cd	character	Parameter code
stat_cd	character	Statistical code
dd_nu	character	Internal database key
loc_web_ds	character	Additional measurement description
medium_grp_cd	character	Medium group code
parm_grp_cd	character	Parameter group code
srs_id	character	SRS ID
access_cd	character	Access code
begin_date	Date	Begin date
end_date	Date	End date
count_nu	integer	Record count
parameter_group_nm	character	Parameter group name
parameter_nm	character	Parameter name
casrn	character	Chemical Abstracts Service (CAS) Registry Number
srsname	character	Substance Registry Services
parameter_units	character	Parameter units

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
comment	character	Header comments from the RDB file
queryTime	POSIXct	The time the data was returned

See Also

`read_waterdata_combined_meta()`

`whatNWISsites` *Site Data Import from NWIS*

Description

Returns a list of sites from the NWIS web service. This function gets the data from: https://waterservices.usgs.gov/docs/site-service/. Mapper format is used

Usage

```
whatNWISsites(..., override_error = FALSE)
```

Arguments

...	see https://waterservices.usgs.gov/docs/site-service/ for a complete list of options. A list (or lists) can also be supplied.
override_error	Logical parameter that allows users to run this function during the final stages of NWIS decommission. NWIS servers will be taken offline February 22nd, 2027. Setting this parameter to TRUE should only be used as a tool to convert readNWIS to read_waterdata functions.

Value

A data frame with at least the following columns:

Name	Type	Description
agency_cd	character	The NWIS code for the agency reporting the data
site_no	character	The USGS site number
station_nm	character	Station name
site_tp_cd	character	Site type code
dec_lat_va	numeric	Decimal latitude
dec_long_va	numeric	Decimal longitude
queryTime	POSIXct	Query time

There are also several useful attributes attached to the data frame:

Name	Type	Description
url	character	The url used to generate the data
queryTime	POSIXct	The time the data was returned

See Also

read_waterdata_monitoring_location()

Examples

```
# see ?read_waterdata_monitoring_location
#siteListPhos <- whatNWISsites(stateCd = "OH", parameterCd = "00665")
#oneSite <- whatNWISsites(sites = "05114000")
```

whatWQPdata *Data Available from Water Quality Portal*

Description

Returns a list of sites from the Water Quality Portal web service. This function gets the data from: https://www.waterqualitydata.us. The information returned from whatWQPdata describes the available data at the WQP sites, and some metadata on the sites themselves. For example, a row is returned for each individual site that fulfills this query. In that we can learn how many sampling activities and results are available for the query. It does not break those results down by any finer grain. For example, if you ask for "Nutrients" (characteristicGroup), you will not learn what specific nutrients are available at that site. For that kind of data discovery see readWQPsummary.

Usage

```
whatWQPdata(..., convertType = TRUE)
```

Arguments

...	A list of named arguments. One way to figure out how to construct a WQP query is to go to the "Advanced" form in the Water Quality Portal. Use the form to discover what parameters are available. Once the query is set in the form, scroll down to the "Query URL". You will see the parameters after "https://www.waterqualitydata.us/#". For example, if you chose "Nutrient" in the Characteristic Group dropdown, you will see characteristicType=Nutrient in the Query URL. The corresponding argument for dataRetrieval is characteristicType = "Nutrient". dataRetrieval users do not need to include mimeType, and providers is optional (these arguments are picked automatically).
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character.

Value

A data frame that returns basic data availability such as sites, number of results, and number of sampling activities from the query parameters for the Water Quality Portal.

See Also

whatWQPsites readWQPsummary readWQPdata

Examples

```
#site1 <- whatWQPdata(siteid = "USGS-01594440")

#type <- "Stream"
#sites <- whatWQPdata(countycode = "US:55:025", siteType = type)
```

```
#lakeSites <- whatWQPdata(siteType = "Lake, Reservoir, Impoundment",
#                         countycode = "US:55:025")
#lakeSites_chars <- whatWQPdata(
#   siteType = "Lake, Reservoir, Impoundment",
#   countycode = "US:55:025", convertType = FALSE)


#bbox <- c(-86.9736, 34.4883, -86.6135, 34.6562)
#what_bb <- whatWQPdata(bBox = bbox)
```

---

whatWQPsamples *Site Data Import from Water Quality Portal*

Description

Returns a list of sites from the Water Quality Portal web service. This function gets the data from: https://www.waterqualitydata.us. The return from this function returns the basic metadata on WQP sites. It is generally faster than the whatWQPdata() function, but does not return information on what data was collected at the site.

Usage

```
whatWQPsamples(..., convertType = TRUE, legacy = TRUE)

whatWQPmetrics(..., convertType = TRUE)

whatWQPsites(..., legacy = TRUE, convertType = TRUE)
```

Arguments

...	A list of named arguments. One way to figure out how to construct a WQP query is to go to the "Advanced" form in the Water Quality Portal. Use the form to discover what parameters are available. Once the query is set in the form, scroll down to the "Query URL". You will see the parameters after "https://www.waterqualitydata.us/#". For example, if you chose "Nutrient" in the Characteristic Group dropdown, you will see characteristicType=Nutrient in the Query URL. The corresponding argument for dataRetrieval is characteristicType = "Nutrient". dataRetrieval users do not need to include mimeType, and providers is optional (these arguments are picked automatically).
convertType	logical, defaults to TRUE. If TRUE, the function will convert the data to dates, datetimes, numerics based on a standard algorithm. If false, everything is returned as a character.
legacy	Logical. If TRUE, uses legacy WQP services. Default is TRUE. Setting legacy = FALSE uses WQX3.0 WQP services, which are in-development, use with caution.

Value

A data frame with information on the sampling activity available from the Water Quality Portal for the query parameters.

data frame that includes information on site metadata.

See Also

whatWQPdata readWQPsummary

whatNWISdata

Examples

```
#site1 <- whatWQPsamples(siteid = "USGS-01594440")

#type <- "Stream"

#sites <- whatWQPsamples(countycode = "US:55:025", siteType = type)

#lakeSites_samples <- whatWQPsamples(siteType = "Lake, Reservoir, Impoundment",
#                                    countycode = "US:55:025")



#type <- "Stream"

#sites <- whatWQPmetrics(countycode = "US:55:025", siteType = type)
#lakeSites_metrics <- whatWQPmetrics(siteType = "Lake, Reservoir, Impoundment",
#                                    countycode = "US:55:025")




#site1 <- whatWQPsites(siteid = "USGS-01594440")

#type <- "Stream"
#sites <- whatWQPsites(
#   countycode = "US:55:025",
#  characteristicName = "Phosphorus",
#   siteType = type
#)
```

---

wqp_check_status *Get WQP service metadata*

Description

The information from this request is only available for a limited time after the original query from the WQP. In the readWQPdata and readWQPqw functions, the results from this function will be attached as an attribute to the data.

Usage

```
wqp_check_status(wqp_request_id)
```

Arguments

wqp_request_id	A character returned from the header of a WQP request.

Value

a list generated from the WQP describing what data was returned.

Examples

```
#rawPcode <- readWQPqw("USGS-01594440", "01075",
#                       ignore_attributes = TRUE, legacy = FALSE)
#  headerInfo <- attr(rawPcode, "headerInfo")
#wqp_request_id <- headerInfo$`wqp-request-id`
#count_info <- wqp_check_status(wqp_request_id)
#count_info[["dataProviders"]]
```

---

zeroPad *Pad string with leading zeros*

Description

Function to pad a string with leading zeros. Useful for parameter codes and USGS site IDs.

Usage

```
zeroPad(x, padTo)
```

Arguments

x	character
padTo	number Final desired length of the character

Value

x character returned with leading zeros

Examples

```
pCode <- "10"
correctPCode <- zeroPad(pCode, 5)
pCodes <- c("100", "1000", "0", "12345", "1565465465465465")
correctPCodes <- zeroPad(pCodes, 5)
pCodeNA <- c(1, 2, NA)
padPCodeNA <- zeroPad(pCodeNA, 4)
```

Index

∗ **IO**
renameNWISColumns, 137
∗ **USGS**
constructNWISURL, 7
countyCd, 9
readNWISpCode, 35
readNWISsite, 39
readNWISuv, 43
readWQPqw, 50
stateCd, 139
whatNWISdata, 142
zeroPad, 148
∗ **WQP**
constructWQPURL, 8
readWQPdata, 45
whatWQPdata, 145
whatWQPsamples, 146
∗ **countyCd**
countyCd, 9
∗ **data**
constructNWISURL, 7
constructWQPURL, 8
readNWISpCode, 35
readNWISsite, 39
readNWISuv, 43
readWQPdata, 45
readWQPqw, 50
whatNWISdata, 142
whatWQPdata, 145
whatWQPsamples, 146
zeroPad, 148
∗ **import**
constructNWISURL, 7
constructWQPURL, 8
readNWISpCode, 35
readNWISsite, 39
readNWISuv, 43
readWQPdata, 45
readWQPqw, 50
whatNWISdata, 142
whatWQPdata, 145
whatWQPsamples, 146
zeroPad, 148
∗ **manip**
renameNWISColumns, 137
∗ **nldi**
findNLDI, 12
get_nldi_sources, 20
∗ **service**
constructNWISURL, 7
constructWQPURL, 8
readNWISpCode, 35
readNWISsite, 39
readNWISuv, 43
readWQPdata, 45
readWQPqw, 50
whatNWISdata, 142
whatWQPdata, 145
whatWQPsamples, 146
zeroPad, 148
∗ **stateCd**
stateCd, 139
∗ **web**
constructNWISURL, 7
constructWQPURL, 8
readNWISpCode, 35
readNWISsite, 39
readNWISuv, 43
readWQPdata, 45
readWQPqw, 50
whatNWISdata, 142
whatWQPdata, 145
whatWQPsamples, 146
zeroPad, 148

addWaterYear, 4

calcWaterYear, 4
check_waterdata_sample_params, 6

checkWQPdates, 5
constructNWISURL, 7
constructNWISURL(), *37*, *39*, *42*
constructWQPURL, 8
countyCd, 9
countyCdLookup, 10
create_NWIS_bib, 11
create_WQP_bib, 11

findNLDI, 12

get_monitoring_location_arguments, 15
get_monitoring_location_arguments(), *83*, *88*, *93*, *101*, *105*, *109*, *123*
get_nldi_sources, 20
get_ogc_params, 21
getQuerySummary, 14
getWebServiceData, 15

importNGWMN, 21
importRDB1, 22
importRDB1(), *35*, *37*, *39*, *42*
importWaterML1, 24
importWaterML1(), *44*
importWaterML2, 27
importWQP, 28
importWQP(), *51*
is_dataRetrieval_user, 29

parameterCdFile, 29
parse_WQP, 30
pcode_to_name, 31

read_ngwmn, 53
read_ngwmn_lithology, 55
read_ngwmn_providers, 57
read_ngwmn_sites, 58
read_ngwmn_water_level, 62
read_ngwmn_well_construction, 64
read_waterdata, 66
read_waterdata(), *33*
read_waterdata_channel, 67
read_waterdata_combined_meta, 71
read_waterdata_combined_meta(), *143*
read_waterdata_continuous, 80
read_waterdata_daily, 85
read_waterdata_daily(), *35*
read_waterdata_field_measurements, 89
read_waterdata_field_meta, 94
read_waterdata_latest_continuous, 98
read_waterdata_latest_daily, 102
read_waterdata_latest_field_measurements, 106
read_waterdata_metadata, 110
read_waterdata_monitoring_location, 111
read_waterdata_monitoring_location(), *41*, *144*
read_waterdata_parameter_codes, 118
read_waterdata_peaks, 120
read_waterdata_ratings, 124
read_waterdata_samples, 126
read_waterdata_stats_daterange *(*read_waterdata_stats_por*)*, 129
read_waterdata_stats_por, 129
read_waterdata_ts_meta, 132
readNWISdata, 31
readNWISdata(), *33*, *43*
readNWISdv, 33
readNWISdv(), *32*, *138*, *142*
readNWISpCode, 35
readNWISpeak, 36
readNWISrating, 38
readNWISsite, 39
readNWISstat, 41
readNWISuv, 43
readNWISuv(), *32*, *138*, *142*
readWQPdata, 45
readWQPdata(), *28*, *51*
readWQPqw, 50
readWQPqw(), *28*
readWQPsummary, 52
renameNWISColumns, 137
renameNWISColumns(), *25*, *44*

setAccess, 139
stateCd, 139
stateCdLookup, 140
summarize_USGS_samples *(*summarize_waterdata_samples*)*, 141
summarize_waterdata_samples, 141

whatNWISdata, 142
whatNWISdata(), *33*, *43*
whatNWISsites, 143
whatWQPdata, 145
whatWQPdata(), *146*

whatWQPmetrics *(*whatWQPsamples*)*, 146
whatWQPsamples, 146
whatWQPsites *(*whatWQPsamples*)*, 146
whatWQPsites(), *28*, *51*
wqp_check_status, 147

zeroPad, 148