

Package ‘dodgr’

April 2, 2022

Title Distances on Directed Graphs

Version 0.2.13

Description Distances on dual-weighted directed graphs using priority-queue shortest paths (Padgham (2019) <doi:10.32866/6945>). Weighted directed graphs have weights from A to B which may differ from those from B to A. Dual-weighted directed graphs have two sets of such weights. A canonical example is a street network to be used for routing in which routes are calculated by weighting distances according to the type of way and mode of transport, yet lengths of routes must be calculated from direct distances.

License GPL-3

URL <https://github.com/ATFutures/dodgr>

BugReports <https://github.com/ATFutures/dodgr/issues>

Depends R (>= 3.5.0)

Imports callr, digest, fs, magrittr, methods, osmdata, Rcpp (>= 0.12.6), RcppParallel

Suggests bench, dplyr, geodist, ggplot2, igraph, igraphdata, jsonlite, knitr, markdown, rmarkdown, roxygen2, sf, testthat, tidygraph

LinkingTo Rcpp, RcppParallel, RcppThread

VignetteBuilder knitr

Encoding UTF-8

LazyData true

NeedsCompilation yes

RoxygenNote 7.1.2

SystemRequirements C++11, GNU make

Author Mark Padgham [aut, cre],
Andreas Petutschnig [aut],
Robin Lovelace [ctb],
Andrew Smith [ctb],
Malcolm Morgan [ctb],
Shane Saunders [cph] (Original author of included code for priority
heaps)

Maintainer Mark Padgham <mark.padgham@email.com>

Repository CRAN

Date/Publication 2022-04-01 23:50:02 UTC

R topics documented:

clear_dodgr_cache	3
compare_heaps	3
dodgr	4
dodgr_cache_off	5
dodgr_cache_on	6
dodgr_centrality	6
dodgr_components	9
dodgr_contract_graph	9
dodgr_distances	10
dodgr_dists	12
dodgr_dists_categorical	14
dodgr_flowmap	16
dodgr_flows_aggregate	17
dodgr_flows_disperse	20
dodgr_flows_si	22
dodgr_full_cycles	24
dodgr_fundamental_cycles	25
dodgr_insert_vertex	26
dodgr_isochrones	27
dodgr_isodists	28
dodgr_isoverts	29
dodgr_load_streetnet	31
dodgr_paths	31
dodgr_sample	33
dodgr_save_streetnet	34
dodgr_sflines_to_poly	35
dodgr_streetnet	35
dodgr_streetnet_sc	37
dodgr_times	38
dodgr_to_igraph	40
dodgr_to_sf	41
dodgr_to_sfc	42
dodgr_to_tidygraph	43
dodgr_uncontract_graph	43
dodgr_vertices	44
estimate_centrality_threshold	45
estimate_centrality_time	46
hampi	47
igraph_to_dodgr	48
match_points_to_graph	48
match_pts_to_graph	49

clear_dodgr_cache 3

<code>merge_directed_graph</code>	50
<code>os_roads_bristol</code>	51
<code>summary.dodgr_dists_categorical</code>	52
<code>weighting_profiles</code>	53
<code>weight_railway</code>	54
<code>weight_streetnet</code>	55
<code>write_dodgr_wt_profile</code>	59

Index 60

`clear_dodgr_cache` *clear_dodgr_cache*

Description

Remove cached versions of `dodgr` graphs. This function should generally *not* be needed, except if graph structure has been directly modified other than through `dodgr` functions; for example by modifying edge weights or distances. Graphs are cached based on the vector of edge IDs, so manual changes to any other attributes will not necessarily be translated into changes in `dodgr` output unless the cached versions are cleared using this function. See <https://github.com/ATFutures/dodgr/wiki/Caching-of-streetnets-and-contracted-graphs> for details of caching process.

Usage

```
clear_dodgr_cache()
```

Value

Nothing; the function silently clears any cached objects

See Also

Other cache: `dodgr_cache_off()`, `dodgr_cache_on()`, `dodgr_load_streetnet()`, `dodgr_save_streetnet()`

`compare_heaps` *compare_heaps*

Description

Perform timing comparison between different kinds of heaps as well as with equivalent `igraph` routine distances. To do this, a random sub-graph containing a defined number of vertices is first selected. Alternatively, this random sub-graph can be pre-generated with the `dodgr_sample` function and passed directly.

Usage

```
compare_heaps(graph, nverts = 100, replications = 2)
```

Arguments

graph	data.frame object representing the network graph (or a sub-sample selected with <code>codedodgr_sample</code>)
nverts	Number of vertices used to generate random sub-graph. If a non-numeric value is given, the whole graph will be used.
replications	Number of replications to be used in comparison

Value

Result of bench: :mark comparison.

Note

igraph caches intermediate results of graph processing, so the **igraph** comparisons will be faster on subsequent runs. To obtain fair comparisons, run only once or re-start the current R session.

See Also

Other misc: [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile](#)

Examples

```
graph <- weight_streetnet (hampi)
## Not run:
compare_heaps (graph, nverts = 1000, replications = 1)

## End(Not run)
```

dodgr

dodgr.

Description

Distances on dual-weighted directed graphs using priority-queue shortest paths. Weighted directed graphs have weights from A to B which may differ from those from B to A. Dual-weighted directed graphs have two sets of such weights. A canonical example is a street network to be used for routing in which routes are calculated by weighting distances according to the type of way and mode of transport, yet lengths of routes must be calculated from direct distances.

The Main Function

- [dodgr_dists\(\)](#): Calculate pair-wise distances between specified pairs of points in a graph.

Functions to Obtain Graphs

- [dodgr_streetnet\(\)](#): Extract a street network in Simple Features (sf) form.
- [weight_streetnet\(\)](#): Convert an sf-formatted street network to a dodgr graph through applying specified weights to all edges.

Functions to Modify Graphs

- [dodgr_components\(\)](#): Number all graph edges according to their presence in distinct connected components.
- [dodgr_contract_graph\(\)](#): Contract a graph by removing redundant edges.

Miscellaneous Functions

- [dodgr_sample\(\)](#): Randomly sample a graph, returning a single connected component of a defined number of vertices.
- [dodgr_vertices\(\)](#): Extract all vertices of a graph.
- [compare_heaps\(\)](#): Compare the performance of different priority queue heap structures for a given type of graph.

dodgr_cache_off

dodgr_cache_off

Description

Turn off all dodgr caching in current session. This is useful if speed is paramount, and if graph contraction is not needed. Caching can be switched back on with [dodgr_cache_on](#).

Usage

```
dodgr_cache_off()
```

Value

Nothing; the function invisibly returns TRUE if successful.

See Also

Other cache: [clear_dodgr_cache\(\)](#), [dodgr_cache_on\(\)](#), [dodgr_load_streetnet\(\)](#), [dodgr_save_streetnet\(\)](#)

dodgr_cache_on	<i>dodgr_cache_on</i>
----------------	-----------------------

Description

Turn on all dodgr caching in current session. This will only have an effect after caching has been turned off with [dodgr_cache_off](#).

Usage

```
dodgr_cache_on()
```

Value

Nothing; the function invisibly returns TRUE if successful.

See Also

Other cache: [clear_dodgr_cache\(\)](#), [dodgr_cache_off\(\)](#), [dodgr_load_streetnet\(\)](#), [dodgr_save_streetnet\(\)](#)

dodgr_centrality	<i>dodgr_centrality</i>
------------------	-------------------------

Description

Calculate betweenness centrality for a 'dodgr' network, in either vertex- or edge-based form.

Usage

```
dodgr_centrality(  
  graph,  
  contract = TRUE,  
  edges = TRUE,  
  column = "d_weighted",  
  vert_wts = NULL,  
  dist_threshold = NULL,  
  heap = "BHeap"  
)
```

Arguments

graph	'data.frame' or equivalent object representing the network graph (see Details)
contract	If 'TRUE', centrality is calculated on contracted graph before mapping back on to the original full graph. Note that for street networks, in particular those obtained from the osmdata package, vertex placement is effectively arbitrary except at junctions; centrality for such graphs should only be calculated between the latter points, and thus 'contract' should always be 'TRUE'.
edges	If 'TRUE', centrality is calculated for graph edges, returning the input 'graph' with an additional 'centrality' column; otherwise centrality is calculated for vertices, returning the equivalent of 'dodgr_vertices(graph)', with an additional vertex-based 'centrality' column.
column	Column of graph defining the edge properties used to calculate centrality (see Note).
vert_wts	Optional vector of length equal to number of vertices (nrow(dodgr_vertices(graph))), to enable centrality to be calculated in weighted form, such that centrality measured from each vertex will be weighted by the specified amount.
dist_threshold	If not 'NULL', only calculate centrality for each point out to specified threshold. Setting values for this will result in approximate estimates for centrality, yet with considerable gains in computational efficiency. For sufficiently large values, approximations will be accurate to within some constant multiplier. Appropriate values can be established via the estimate_centrality_threshold function.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; 'FHeap'), Binary Heap ('BHeap'), Trinomial Heap ('TriHeap'), Extended Trinomial Heap ('TriHeapExt', and 2-3 Heap ('Heap23').

Value

Modified version of graph with additional 'centrality' column added.

Note

The column parameter is by default d_weighted, meaning centrality is calculated by routing according to weighted distances. Other possible values for this parameter are

- d for unweighted distances
- time for unweighted time-based routing
- time_weighted for weighted time-based routing

Centrality is calculated by default using parallel computation with the maximal number of available cores or threads. This number can be reduced by specifying a value via RcppParallel::setThreadOptions (numThreads = <desired number of threads>).

See Also

Other centrality: [estimate_centrality_threshold\(\)](#), [estimate_centrality_time\(\)](#)

Examples

```

graph_full <- weight_streetnet (hampi)
graph <- dodgr_contract_graph (graph_full)
graph <- dodgr_centrality (graph)
# 'graph' is then the contracted graph with an additional 'centrality' column
# Same calculation via 'igraph':
igr <- dodgr_to_igraph (graph)
library (igraph)
cent <- edge_betweenness (igr)
identical (cent, graph$centrality) # TRUE
# Values of centrality between all junctions in the contracted graph can then
# be mapped back onto the original full network by "uncontracting":
graph_full <- dodgr_uncontract_graph (graph)
# For visualisation, it is generally necessary to merge the directed edges to
# form an equivalent undirected graph. Conversion to 'sf' format via
# 'dodgr_to_sf()' is also useful for many visualisation routines.
graph_sf <- merge_directed_graph (graph_full) %>%
  dodgr_to_sf ()

## Not run:
library (mapview)
centrality <- graph_sf$centrality / max (graph_sf$centrality)
ncols <- 30
cols <- c ("lawngreen", "red")
cols <- colorRampPalette (cols) (ncols) [ceiling (ncols * centrality)]
mapview (graph_sf, color = cols, lwd = 10 * centrality)

## End(Not run)

# An example of flow aggregation across a generic (non-OSM) highway,
# represented as the 'routes_fast' object of the \pkg{stplanr} package,
# which is a SpatialLinesDataFrame containing commuter densities along
# components of a street network.
## Not run:
library (stplanr)
# merge all of the 'routes_fast' lines into a single network
r <- overline (routes_fast, attrib = "length", buff_dist = 1)
r <- sf::st_as_sf (r)
# Convert to a 'dodgr' network, for which we need to specify both a 'type'
# and 'id' column.
r$type <- 1
r$id <- seq (nrow (r))
graph_full <- weight_streetnet (r, type_col = "type", id_col = "id",
  wt_profile = 1)
# convert to contracted form, retaining junction vertices only, and append
# 'centrality' column
graph <- dodgr_contract_graph (graph_full) %>%
  dodgr_centrality ()
#' expand back to full graph; merge directed flows; and convert result to
# 'sf'-format for plotting
graph_sf <- dodgr_uncontract_graph (graph) %>%
  merge_directed_graph () %>%

```



```
dodgr_to_sf ()  
plot (graph_sf ["centrality"])  
  
## End(Not run)
```

dodgr_components *dodgr_components*

Description

Identify connected components of graph and add corresponding component column to data.frame.

Usage

```
dodgr_components(graph)
```

Arguments

graph A data.frame of edges

Value

Equivalent graph with additional component column, sequentially numbered from 1 = largest component.

See Also

Other modification: [dodgr_contract_graph\(\)](#), [dodgr_uncontract_graph\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)  
graph <- dodgr_components (graph)
```

dodgr_contract_graph *dodgr_contract_graph*

Description

Removes redundant (straight-line) vertices from graph, leaving only junction vertices.

Usage

```
dodgr_contract_graph(graph, verts = NULL)
```

Arguments

graph	A flat table of graph edges. Must contain columns labelled from and to, or start and stop. May also contain similarly labelled columns of spatial coordinates (for example from_x) or stop_lon).
verts	Optional list of vertices to be retained as routing points. These must match the from and to columns of graph.

Value

A contracted version of the original graph, containing the same number of columns, but with each row representing an edge between two junction vertices (or between the submitted verts, which may or may not be junctions).

See Also

Other modification: [dodgr_components\(\)](#), [dodgr_uncontract_graph\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
nrow (graph) # 5,973
graph <- dodgr_contract_graph (graph)
nrow (graph) # 662
```

dodgr_distances

dodgr_distances

Description

Alias for [dodgr_dists](#)

Usage

```
dodgr_distances(
  graph,
  from = NULL,
  to = NULL,
  shortest = TRUE,
  pairwise = FALSE,
  heap = "BHeap",
  parallel = TRUE,
  quiet = TRUE
)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Notes)
from	Vector or matrix of points from which route distances are to be calculated (see Notes)
to	Vector or matrix of points to which route distances are to be calculated (see Notes)
shortest	If FALSE, calculate distances along the <i>fastest</i> rather than shortest routes (see Notes).
pairwise	If TRUE, calculate distances only between the ordered pairs of from and to.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23').
parallel	If TRUE, perform routing calculation in parallel (see details)
quiet	If FALSE, display progress messages on screen.

Value

square matrix of distances between nodes

See Also

Other distances: [dodgr_dists_categorical\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isodists\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_paths\(\)](#), [dodgr_times\(\)](#)

Examples

```
# A simple graph
graph <- data.frame (from = c ("A", "B", "B", "B", "C", "C", "D", "D"),
                    to = c ("B", "A", "C", "D", "B", "D", "C", "A"),
                    d = c (1, 2, 1, 3, 2, 1, 2, 1))

dodgr_dists (graph)

# A larger example from the included [hampi()] data.
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 100)
to <- sample (graph$to_id, size = 50)
d <- dodgr_dists (graph, from = from, to = to)
# d is a 100-by-50 matrix of distances between `from` and `to`

## Not run:
# a more complex street network example, thanks to @chrijo; see
# https://github.com/ATFutures/dodgr/issues/47

xy <- rbind (c (7.005994, 51.45774), # limbeckerplatz 1 essen germany
            c (7.012874, 51.45041)) # hauptbahnhof essen germany
xy <- data.frame (lon = xy [, 1], lat = xy [, 2])
essen <- dodgr_streetnet (pts = xy, expand = 0.2, quiet = FALSE)
```

```

graph <- weight_streetnet (essen, wt_profile = "foot")
d <- dodgr_dists (graph, from = xy, to = xy)
# First reason why this does not work is because the graph has multiple,
# disconnected components.
table (graph$component)
# reduce to largest connected component, which is always number 1
graph <- graph [which (graph$component == 1), ]
d <- dodgr_dists (graph, from = xy, to = xy)
# should work, but even then note that
table (essen$level)
# There are parts of the network on different building levels (because of
# shopping malls and the like). These may or may not be connected, so it may
# be necessary to filter out particular levels
index <- which (! (essen$level == "-1" | essen$level == "1")) # for example
library (sf) # needed for following sub-select operation
essen <- essen [index, ]
graph <- weight_streetnet (essen, wt_profile = "foot")
graph <- graph [which (graph$component == 1), ]
d <- dodgr_dists (graph, from = xy, to = xy)

## End(Not run)

```

dodgr_dists

dodgr_dists

Description

Calculate matrix of pair-wise distances between points.

Usage

```

dodgr_dists(
  graph,
  from = NULL,
  to = NULL,
  shortest = TRUE,
  pairwise = FALSE,
  heap = "BHeap",
  parallel = TRUE,
  quiet = TRUE
)

```

Arguments

graph	data.frame or equivalent object representing the network graph (see Notes)
from	Vector or matrix of points from which route distances are to be calculated (see Notes)
to	Vector or matrix of points to which route distances are to be calculated (see Notes)

shortest	If FALSE, calculate distances along the <i>fastest</i> rather than shortest routes (see Notes).
pairwise	If TRUE, calculate distances only between the ordered pairs of from and to.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23').
parallel	If TRUE, perform routing calculation in parallel (see details)
quiet	If FALSE, display progress messages on screen.

Value

square matrix of distances between nodes

Note

graph must minimally contain three columns of from, to, dist. If an additional column named weight or wt is present, shortest paths are calculated according to values specified in that column; otherwise according to dist values. Either way, final distances between from and to points are calculated by default according to values of dist. That is, paths between any pair of points will be calculated according to the minimal total sum of weight values (if present), while reported distances will be total sums of dist values.

For street networks produced with [weight_streetnet](#), distances may also be calculated along the *fastest* routes with the shortest = FALSE option. Graphs must in this case have columns of time and time_weighted. Note that the fastest routes will only be approximate when derived from sf-format data generated with the **osmdata** function `osmdata_sf()`, and will be much more accurate when derived from sc-format data generated with `osmdata_sc()`. See [weight_streetnet](#) for details.

The from and to columns of graph may be either single columns of numeric or character values specifying the numbers or names of graph vertices, or combinations to two columns specifying geographical (longitude and latitude) coordinates. In the latter case, almost any sensible combination of names will be accepted (for example, fromx, fromy, from_x, from_y, or fr_lat, fr_lon.)

from and to values can be either two-column matrices of equivalent of longitude and latitude coordinates, or else single columns precisely matching node numbers or names given in graph\$from or graph\$to. If to is NULL, pairwise distances are calculated between all points specified in from. If both from and to are NULL, pairwise distances are calculated between all nodes in graph.

Calculations in parallel (parallel = TRUE) ought very generally be advantageous. For small graphs, calculating distances in parallel is likely to offer relatively little gain in speed, but increases from parallel computation will generally markedly increase with increasing graph sizes. By default, parallel computation uses the maximal number of available cores or threads. This number can be reduced by specifying a value via `RcppParallel::setThreadOptions(numThreads = <desired_number>)`.

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists_categorical\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isodists\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_paths\(\)](#), [dodgr_times\(\)](#)

Examples

```

# A simple graph
graph <- data.frame (from = c ("A", "B", "B", "B", "C", "C", "D", "D"),
                    to = c ("B", "A", "C", "D", "B", "D", "C", "A"),
                    d = c (1, 2, 1, 3, 2, 1, 2, 1))

dodgr_dists (graph)

# A larger example from the included [hampi()] data.
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 100)
to <- sample (graph$to_id, size = 50)
d <- dodgr_dists (graph, from = from, to = to)
# d is a 100-by-50 matrix of distances between `from` and `to`

## Not run:
# a more complex street network example, thanks to @chrijo; see
# https://github.com/ATFutures/dodgr/issues/47

xy <- rbind (c (7.005994, 51.45774), # limbeckerplatz 1 essen germany
            c (7.012874, 51.45041)) # hauptbahnhof essen germany
xy <- data.frame (lon = xy [, 1], lat = xy [, 2])
essen <- dodgr_streetnet (pts = xy, expand = 0.2, quiet = FALSE)
graph <- weight_streetnet (essen, wt_profile = "foot")
d <- dodgr_dists (graph, from = xy, to = xy)
# First reason why this does not work is because the graph has multiple,
# disconnected components.
table (graph$component)
# reduce to largest connected component, which is always number 1
graph <- graph [which (graph$component == 1), ]
d <- dodgr_dists (graph, from = xy, to = xy)
# should work, but even then note that
table (essen$level)
# There are parts of the network on different building levels (because of
# shopping malls and the like). These may or may not be connected, so it may
# be necessary to filter out particular levels
index <- which (! (essen$level == "-1" | essen$level == "1")) # for example
library (sf) # needed for following sub-select operation
essen <- essen [index, ]
graph <- weight_streetnet (essen, wt_profile = "foot")
graph <- graph [which (graph$component == 1), ]
d <- dodgr_dists (graph, from = xy, to = xy)

## End(Not run)

```

dodgr_dists_categorical

Cumulative distances along different edge categories

Description

Cumulative distances along different edge categories

Usage

```
dodgr_dists_categorical(
  graph,
  from = NULL,
  to = NULL,
  proportions_only = FALSE,
  dlimit = NULL,
  heap = "BHeap",
  quiet = TRUE
)
```

Arguments

graph	data.frame or equivalent object representing the network graph which must have a column named "edge_type" which labels categories of edge types along which categorical distances are to be aggregated (see Note).
from	Vector or matrix of points from which route distances are to be calculated (see Notes)
to	Vector or matrix of points to which route distances are to be calculated (see Notes)
proportions_only	If FALSE, return distance matrices for full distances and for each edge category; if TRUE, return single vector of proportional distances, like the summary function applied to full results. See Note.
dlimit	If TRUE, and no value to to is given, distances are aggregated from each from point out to the specified distance limit (in the same units as the edge distances of the input graph). The proportions_only argument has no effect when dlimit = TRUE.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23').
quiet	If FALSE, display progress messages on screen.

Value

If `dlimit = FALSE`, a list of distance matrices of equal dimensions (`length(from)`, `length(to)`), the first of which ("distance") holds the final distances, while the rest are one matrix for each unique value of "edge_type", holding the distances traversed along those types of edges only. If `dlimit = TRUE`, a single matrix of total distances along all ways from each point, along with distances along each of the different kinds of ways specified in the "edge_type" column of the input graph.

Note

The "edge_type" column in the graph can contain any kind of discrete or categorical values, although integer values of 0 are not permissible. NA values are ignored. The function requires one full distance matrix to be stored for each category of "edge_type" (unless `proportions_only = TRUE`). It is wise to keep numbers of discrete types as low as possible, especially for large distance matrices.

Setting the `proportions_only` flag to `TRUE` may be advantageous for large jobs, because this avoids construction of the full matrices. This may speed up calculations, but perhaps more importantly it may make possible calculations which would otherwise require distance matrices too large to be directly stored.

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isodists\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_paths\(\)](#), [dodgr_times\(\)](#)

Examples

```
# Prepare a graph for categorical routing by including an "edge_type" column
graph <- weight_streetnet (hampi, wt_profile = "foot")
graph <- graph [graph$component == 1, ]
graph$edge_type <- graph$highway
# Define start and end points for categorical distances; using all vertices
# here.
length (unique (graph$edge_type)) # Number of categories
v <- dodgr_vertices (graph)
from <- to <- v$id
d <- dodgr_dists_categorical (graph, from, to)
class (d)
length (d)
sapply (d, dim)
# 9 distance matrices, all of same dimensions, first of which is standard
# distance matrix
# s <- summary (d) # print summary as proportions along each "edge_type"
# or directly calculate proportions only
dodgr_dists_categorical (graph, from, to,
                        proportions_only = TRUE)

# The 'dlimit' parameter can be used to calculate total distances along each
# category of edges from a set of points:
dlimit <- 2000 # in metres
d <- dodgr_dists_categorical (graph, from, dlimit = dlimit)
dim (d) # length(from), length(unique(edge_type)) + 1
```

dodgr_flowmap

dodgr_flowmap

Description

Map the output of [dodgr_flows_aggregate](#) or [dodgr_flows_disperse](#)

Usage

```
dodgr_flowmap(net, bbox = NULL, linescale = 1)
```


Arguments

net	A street network with a flow column obtained from dodgr_flows_aggregate or dodgr_flows_disperse
bbox	If given, scale the map to this bbox, otherwise use entire extend of net
linescale	Maximal thickness of plotted lines

Note

net should be first passed through `merge_directed_graph` prior to plotting, otherwise lines for different directions will be overlaid.

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
to <- sample (graph$to_id, size = 5)
to <- to [!to %in% from]
flows <- matrix (10 * runif (length (from) * length (to)),
                 nrow = length (from))
graph <- dodgr_flows_aggregate (graph, from = from, to = to, flows = flows)
# graph then has an additional 'flows` column of aggregate flows along all
# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_graph (graph)
## Not run:
dodgr_flowmap (graph_undir)

## End(Not run)
```

`dodgr_flows_aggregate` *dodgr_flows_aggregate*

Description

Aggregate flows throughout a network based on an input matrix of flows between all pairs of from and to points.

Usage

```
dodgr_flows_aggregate(
  graph,
  from,
  to,
  flows,
  contract = FALSE,
  heap = "BHeap",
  tol = 0.000000000001,
  norm_sums = TRUE,
  quiet = TRUE
)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which aggregate flows are to be calculated (see Details)
to	Vector or matrix of points to which aggregate flows are to be calculated (see Details)
flows	Matrix of flows with <code>nrow(flows)==length(from)</code> and <code>ncol(flows)==length(to)</code> .
contract	If TRUE, calculate flows on contracted graph before mapping them back on to the original full graph (recommended as this will generally be much faster).
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).
tol	Relative tolerance below which flows towards to vertices are not considered. This will generally have no effect, but can provide speed gains when flow matrices represent spatial interaction models, in which case this parameter effectively reduces the radius from each from point over which flows are aggregated. To remove any such effect, set <code>tol = 0</code> .
norm_sums	Standardise sums from all origin points, so sum of flows throughout entire network equals sum of densities from all origins (see Note).
quiet	If FALSE, display progress messages on screen.

Value

Modified version of graph with additional flow column added.

Note

Spatial Interaction models are often fitted through trialling a range of values of 'k'. The specification above allows fitting multiple values of 'k' to be done with a single call, in a way that is far more efficient than making multiple calls. A matrix of 'k' values may be entered, with each column holding a different vector of values, one for each 'from' point. For a matrix of 'k' values having 'n' columns, the return object will be a modified version in the input 'graph', with an additional 'n'

columns, named 'flow1', 'flow2', ... up to 'n'. These columns must be subsequently matched by the user back on to the corresponding columns of the matrix of 'k' values.

The `norm_sums` parameter should be used whenever densities at origins and destinations are absolute values, and ensures that the sum of resultant flow values throughout the entire network equals the sum of densities at all origins. For example, with `norm_sums = TRUE` (the default), a flow from a single origin with density one to a single destination along two edges will allocate flows of one half to each of those edges, such that the sum of flows across the network will equal one, or the sum of densities from all origins. The `norm_sums = TRUE` option is appropriate where densities are relative values, and ensures that each edge maintains relative proportions. In the above example, flows along each of two edges would equal one, for a network sum of two, or greater than the sum of densities.

Flows are calculated by default using parallel computation with the maximal number of available cores or threads. This number can be reduced by specifying a value via `RcppParallel::setThreadOptions(numThreads = <desired number of threads>)`.

See Also

Other distances: `dodgr_distances()`, `dodgr_dists_categorical()`, `dodgr_dists()`, `dodgr_flows_disperse()`, `dodgr_flows_si()`, `dodgr_isochrones()`, `dodgr_isodists()`, `dodgr_isoverts()`, `dodgr_paths()`, `dodgr_times()`

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
to <- sample (graph$to_id, size = 5)
to <- to [!to %in% from]
flows <- matrix (10 * runif (length (from) * length (to)),
                nrow = length (from))
graph <- dodgr_flows_aggregate (graph, from = from, to = to, flows = flows)
# graph then has an additional 'flows' column of aggregate flows along all
# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_graph (graph)
# This graph will only include those edges having non-zero flows, and so:
nrow (graph); nrow (graph_undir) # the latter is much smaller

# The following code can be used to convert the resultant graph to an `sf`
# object suitable for plotting
## Not run:
gsf <- dodgr_to_sf (graph_undir)

# example of plotting with the 'mapview' package
library (mapview)
flow <- gsf$flow / max (gsf$flow)
ncols <- 30
cols <- c ("lawngreen", "red")
colranmp <- colorRampPalette (cols) (ncols) [ceiling (ncols * flow)]
mapview (gsf, color = colranmp, lwd = 10 * flow)

## End(Not run)
```

```

# An example of flow aggregation across a generic (non-OSM) highway,
# represented as the `routes_fast` object of the \pkg{stplanr} package,
# which is a SpatialLinesDataFrame containing commuter densities along
# components of a street network.
## Not run:
library(stplanr)
# merge all of the 'routes_fast' lines into a single network
r <- overline(routes_fast, attrib = "length", buff_dist = 1)
r <- sf::st_as_sf(r)
# then extract the start and end points of each of the original 'routes_fast'
# lines and use these for routing with `dodgr`
l <- lapply(routes_fast@lines, function(i)
  c(sp::coordinates(i)[[1]][1, ],
    tail(sp::coordinates(i)[[1]], 1)))
l <- do.call(rbind, l)
xy_start <- l[, 1:2]
xy_end <- l[, 3:4]
# Then just specify a generic OD matrix with uniform values of 1:
flows <- matrix(1, nrow = nrow(l), ncol = nrow(l))
# We need to specify both a `type` and `id` column for the
# \link{weight_streetnet} function.
r$type <- 1
r$id <- seq(nrow(r))
graph <- weight_streetnet(r, type_col = "type", id_col = "id",
  wt_profile = 1)
f <- dodgr_flows_aggregate(graph, from = xy_start, to = xy_end,
  flows = flows)
# Then merge directed flows and convert to \pkg{sf} for plotting as before:
f <- merge_directed_graph(f)
geoms <- dodgr_to_sfc(f)
gc <- dodgr_contract_graph(f)
gsf <- sf::st_sf(geoms)
gsf$flow <- gc$flow
# sf plot:
plot(gsf["flow"])

## End(Not run)

```

dodgr_flows_disperse *dodgr_flows_disperse*

Description

Disperse flows throughout a network based on a input vectors of origin points and associated densities

Usage

```

dodgr_flows_disperse(
  graph,

```

```

    from,
    dens,
    k = 500,
    contract = FALSE,
    heap = "BHeap",
    tol = 0.000000000001,
    quiet = TRUE
  )

```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which aggregate dispersed flows are to be calculated (see Details)
dens	Vectors of densities corresponding to the from points
k	Width coefficient of exponential diffusion function defined as $\exp(-d/k)$, in units of distance column of graph (metres by default). Can also be a vector with same length as from, giving dispersal coefficients from each point. If value of $k < 0$ is given, a standard logistic polynomial will be used.
contract	If TRUE, calculate flows on contracted graph before mapping them back on to the original full graph (recommended as this will generally be much faster).
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).
tol	Relative tolerance below which dispersal is considered to have finished. This parameter can generally be ignored; if in doubt, its effect can be removed by setting $tol = 0$.
quiet	If FALSE, display progress messages on screen.

Value

Modified version of graph with additional flow column added.

Note

Spatial Interaction models are often fitted through trialling a range of values of 'k'. The specification above allows fitting multiple values of 'k' to be done with a single call, in a way that is far more efficient than making multiple calls. A matrix of 'k' values may be entered, with each column holding a different vector of values, one for each 'from' point. For a matrix of 'k' values having 'n' columns, the return object will be a modified version in the input 'graph', with an additional 'n' columns, named 'flow1', 'flow2', ... up to 'n'. These columns must be subsequently matched by the user back on to the corresponding columns of the matrix of 'k' values.

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists_categorical\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isodists\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_paths\(\)](#), [dodgr_times\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
dens <- rep (1, length (from)) # Uniform densities
graph <- dodgr_flows_disperse (graph, from = from, dens = dens)
# graph then has an additional 'flows` column of aggregate flows along all
# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_graph (graph)
```

dodgr_flows_si

dodgr_flows_si

Description

Aggregate flows throughout a network based using an exponential Spatial Interaction (SI) model between a specified set of origin and destination points, and associated vectors of densities.

Usage

```
dodgr_flows_si(
  graph,
  from,
  to,
  k = 500,
  dens_from = NULL,
  dens_to = NULL,
  contract = FALSE,
  norm_sums = TRUE,
  heap = "BHeap",
  tol = 0.000000000001,
  quiet = TRUE
)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which aggregate flows are to be calculated (see Details)
to	Vector or matrix of points to which aggregate flows are to be calculated (see Details)
k	Width of exponential spatial interaction function ($\exp(-d/k)$), in units of 'd', specified in one of 3 forms: (i) a single value; (ii) a vector of independent values for each origin point (with same length as 'from' points); or (iii) an equivalent matrix with each column holding values for each 'from' point, so 'nrow(k)==length(from)'. See Note.

<code>dens_from</code>	Vector of densities at origin ('from') points
<code>dens_to</code>	Vector of densities at destination ('to') points
<code>contract</code>	If TRUE, calculate flows on contracted graph before mapping them back on to the original full graph (recommended as this will generally be much faster).
<code>norm_sums</code>	Standardise sums from all origin points, so sum of flows throughout entire network equals sum of densities from all origins (see Note).
<code>heap</code>	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).
<code>tol</code>	Relative tolerance below which flows towards to vertices are not considered. This will generally have no effect, but can provide speed gains when flow matrices represent spatial interaction models, in which case this parameter effectively reduces the radius from each from point over which flows are aggregated. To remove any such effect, set <code>tol = 0</code> .
<code>quiet</code>	If FALSE, display progress messages on screen.

Value

Modified version of graph with additional flow column added.

Note

Spatial Interaction models are often fitted through trialling a range of values of 'k'. The specification above allows fitting multiple values of 'k' to be done with a single call, in a way that is far more efficient than making multiple calls. A matrix of 'k' values may be entered, with each column holding a different vector of values, one for each 'from' point. For a matrix of 'k' values having 'n' columns, the return object will be a modified version in the input 'graph', with an additional 'n' columns, named 'flow1', 'flow2', ... up to 'n'. These columns must be subsequently matched by the user back on to the corresponding columns of the matrix of 'k' values.

The `norm_sums` parameter should be used whenever densities at origins and destinations are absolute values, and ensures that the sum of resultant flow values throughout the entire network equals the sum of densities at all origins. For example, with `norm_sums = TRUE` (the default), a flow from a single origin with density one to a single destination along two edges will allocate flows of one half to each of those edges, such that the sum of flows across the network will equal one, or the sum of densities from all origins. The `norm_sums = TRUE` option is appropriate where densities are relative values, and ensures that each edge maintains relative proportions. In the above example, flows along each of two edges would equal one, for a network sum of two, or greater than the sum of densities.

With `norm_sums = TRUE`, the sum of network flows (`sum(output$flow)`) should equal the sum of origin densities (`sum(dens_from)`). This may nevertheless not always be the case, because origin points may simply be too far from any destination (to) points for an exponential model to yield non-zero values anywhere in a network within machine tolerance. Such cases may result in sums of output flows being less than sums of input densities.

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists_categorical\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isodists\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_paths\(\)](#), [dodgr_times\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
to <- sample (graph$to_id, size = 5)
to <- to [!to %in% from]
flows <- matrix (10 * runif (length (from) * length (to)),
                nrow = length (from))
graph <- dodgr_flows_aggregate (graph, from = from, to = to, flows = flows)
# graph then has an additional 'flows' column of aggregate flows along all
# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_graph (graph)
# This graph will only include those edges having non-zero flows, and so:
nrow (graph); nrow (graph_undir) # the latter is much smaller
```

dodgr_full_cycles *dodgr_full_cycles*

Description

Calculate fundamental cycles on a FULL (that is, non-contracted) graph.

Usage

```
dodgr_full_cycles(graph, graph_max_size = 10000, expand = 0.05)
```

Arguments

graph	data.frame or equivalent object representing the contracted network graph (see Details).
graph_max_size	Maximum size submitted to the internal C++ routines as a single chunk. Warning: Increasing this may lead to computer meltdown!
expand	For large graphs which must be broken into chunks, this factor determines the relative overlap between chunks to ensure all cycles are captured. (This value should only need to be modified in special cases.)

Note

This function converts the graph to its contracted form, calculates the fundamental cycles on that version, and then expands these cycles back onto the original graph. This is far more computationally efficient than calculating fundamental cycles on a full (non-contracted) graph.

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile\(\)](#)

Examples

```
## Not run:
net <- weight_streetnet (hampi)
graph <- dodgr_contract_graph (net)
cyc1 <- dodgr_fundamental_cycles (graph)
cyc2 <- dodgr_full_cycles (net)

## End(Not run)
# cyc2 has same number of cycles, but each one is generally longer, through
# including all points intermediate to junctions; cyc1 has cycles composed of
# junction points only.
```

```
dodgr_fundamental_cycles
      dodgr_fundamental_cycles
```

Description

Calculate fundamental cycles in a graph.

Usage

```
dodgr_fundamental_cycles(
  graph,
  vertices = NULL,
  graph_max_size = 10000,
  expand = 0.05
)
```

Arguments

graph	data.frame or equivalent object representing the contracted network graph (see Details).
vertices	data.frame returned from dodgr_vertices (graph). Will be calculated if not provided, but it's quicker to pass this if it has already been calculated.
graph_max_size	Maximum size submitted to the internal C++ routines as a single chunk. Warning: Increasing this may lead to computer meltdown!
expand	For large graphs which must be broken into chunks, this factor determines the relative overlap between chunks to ensure all cycles are captured. (This value should only need to be modified in special cases.)

Value

List of cycle paths, in terms of vertex IDs in graph and, for spatial graphs, the corresponding coordinates.

Note

Calculation of fundamental cycles is VERY computationally demanding, and this function should only be executed on CONTRACTED graphs (that is, graphs returned from [dodgr_contract_graph](#)), and even then may take a long time to execute. Results for full graphs can be obtained with the function [dodgr_full_cycles](#). The computational complexity can also not be calculated in advance, and so the parameter `graph_max_size` will lead to graphs larger than that (measured in numbers of edges) being cut into smaller parts. (Note that that is only possible for spatial graphs, meaning that it is not at all possible to apply this function to large, non-spatial graphs.) Each of these smaller parts will be expanded by the specified amount (`expand`), and cycles found within. The final result is obtained by aggregating all of these cycles and removing any repeated ones arising due to overlap in the expanded portions. Finally, note that this procedure of cutting graphs into smaller, computationally manageable sub-graphs provides only an approximation and may not yield all fundamental cycles.

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile\(\)](#)

Examples

```
net <- weight_streetnet (hampi)
graph <- dodgr_contract_graph (net)
verts <- dodgr_vertices (graph)
cyc <- dodgr_fundamental_cycles (graph, verts)
```

`dodgr_insert_vertex` *dodgr_insert_vertex*

Description

Insert a new node or vertex into a network

Usage

```
dodgr_insert_vertex(graph, v1, v2, x = NULL, y = NULL)
```

Arguments

graph	A flat table of graph edges. Must contain columns labelled from and to, or start and stop. May also contain similarly labelled columns of spatial coordinates (for example from_x) or stop_lon).
v1	Vertex defining start of graph edge along which new vertex is to be inserted
v2	Vertex defining end of graph edge along which new vertex is to be inserted (order of v1 and v2 is not important).
x	The x-coordinate of new vertex. If not specified, vertex is created half-way between v1 and v2.
y	The y-coordinate of new vertex. If not specified, vertex is created half-way between v1 and v2.

Value

A modified graph with specified edge between defined start and end vertices split into two edges either side of new vertex.

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
e1 <- sample (nrow (graph), 1)
v1 <- graph$from_id [e1]
v2 <- graph$to_id [e1]
# insert new vertex in the middle of that randomly-selected edge:
graph2 <- dodgr_insert_vertex (graph, v1, v2)
nrow (graph); nrow (graph2) # new edges added to graph2
```

dodgr_isochrones *dodgr_isochrones*

Description

Calculate isochrone contours from specified points. Function is fully vectorized to calculate accept vectors of central points and vectors defining multiple isochrone thresholds.

Usage

```
dodgr_isochrones(graph, from = NULL, tlim = NULL, heap = "BHeap")
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Notes)
from	Vector or matrix of points from which isochrones are to be calculated.
tlim	Vector of desired limits of isochrones in seconds
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).

Value

A single data.frame of isochrones as points sorted anticlockwise around each origin (from) point, with columns denoting the from points and tlim value(s). The isochrones are given as id values and associated coordinates of the series of points from each from point at the specified isochrone times.

Isochrones are calculated by default using parallel computation with the maximal number of available cores or threads. This number can be reduced by specifying a value via RcppParallel::setThreadOptions (numThreads = <

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists_categorical\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isodists\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_paths\(\)](#), [dodgr_times\(\)](#)

Examples

```
## Not run:
# Use osmdata package to extract 'SC'-format data:
library (osmdata)
dat <- opq ("hampi india") %>%
  add_osm_feature (key = "highway") %>%
  osmdata_sc ()
graph <- weight_streetnet (dat)
from <- sample (graph$.vx0, size = 100)
tlim <- c (5, 10, 20, 30, 60) * 60 # times in seconds
x <- dodgr_isochrones (graph, from = from, tlim)

## End(Not run)
```

dodgr_isodists

dodgr_isodists

Description

Calculate isodistance contours from specified points. Function is fully vectorized to calculate accept vectors of central points and vectors defining multiple isodistances.

Usage

```
dodgr_isodists(graph, from = NULL, dlim = NULL, heap = "BHeap")
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Notes)
from	Vector or matrix of points from which isodistances are to be calculated.
dlim	Vector of desired limits of isodistances in metres.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).

Value

A single data.frame of isodistances as points sorted anticlockwise around each origin (from) point, with columns denoting the from points and dlim value(s). The isodistance contours are given as id values and associated coordinates of the series of points from each from point at the specified isodistances.

Note

Isodists are calculated by default using parallel computation with the maximal number of available cores or threads. This number can be reduced by specifying a value via RcppParallel::setThreadOptions (numThreads = <desired number of threads>).

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists_categorical\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_paths\(\)](#), [dodgr_times\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 100)
dlim <- c (1, 2, 5, 10, 20) * 100
d <- dodgr_isodists (graph, from = from, dlim)
```

dodgr_isoverts

dodgr_isoverts

Description

Calculate isodistance or isochrone contours from specified points, and return lists of all network vertices contained within the contours. Function is fully vectorized to calculate accept vectors of central points and vectors defining multiple isochrone thresholds. Provide one or more dlim values for isodistances, or one or more tlim values for isochrones.

Usage

```
dodgr_isoverts(graph, from = NULL, dlim = NULL, tlim = NULL, heap = "BHeap")
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Notes)
from	Vector or matrix of points from which isodistances or isochrones are to be calculated.
dlim	Vector of desired limits of isodistances in metres.
tlim	Vector of desired limits of isochrones in seconds
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).

Value

A single data.frame of vertex IDs, with columns denoting the from points and tlim value(s). The isochrones are given as id values and associated coordinates of the series of points from each from point at the specified isochrone times.

Isoverts are calculated by default using parallel computation with the maximal number of available cores or threads. This number can be reduced by specifying a value via RcppParallel::setThreadOptions (numThreads = <desired number of threads>).

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists_categorical\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isodists\(\)](#), [dodgr_paths\(\)](#), [dodgr_times\(\)](#)

Examples

```
## Not run:
# Use osmdata package to extract 'SC'-format data:
library(osmdata)
dat <- opq("hampi india") %>%
  add_osm_feature(key = "highway") %>%
  osmdata_sc()
graph <- weight_streetnet(dat)
from <- sample(graph$vx0, size = 100)
tlim <- c(5, 10, 20, 30, 60) * 60 # times in seconds
x <- dodgr_isoverts(graph, from = from, tlim)

## End(Not run)
```

dodgr_load_streetnet *Load a street network previously saved with [dodgr_save_streetnet](#).*

Description

This always returns the full, non-contracted graph. The contracted graph can be generated by passing the result to [dodgr_contract_graph](#).

Usage

```
dodgr_load_streetnet(filename)
```

Arguments

filename Name (with optional full path) of file to be loaded.

See Also

Other cache: [clear_dodgr_cache\(\)](#), [dodgr_cache_off\(\)](#), [dodgr_cache_on\(\)](#), [dodgr_save_streetnet\(\)](#)

Examples

```
net <- weight_streetnet (hampi)
f <- file.path (tempdir (), "streetnet.Rds")
dodgr_save_streetnet (net, f)
clear_dodgr_cache () # rm cached objects from tempdir
# at some later time, or in a new R session:
net <- dodgr_load_streetnet (f)
```

dodgr_paths *dodgr_paths*

Description

Calculate lists of pair-wise shortest paths between points.

Usage

```
dodgr_paths(
  graph,
  from,
  to,
  vertices = TRUE,
  pairwise = FALSE,
  heap = "BHeap",
  quiet = TRUE
)
```

Arguments

graph	data.frame or equivalent object representing the network graph (see Details)
from	Vector or matrix of points from which route paths are to be calculated (see Details)
to	Vector or matrix of points to which route paths are to be calculated (see Details)
vertices	If TRUE, return lists of lists of vertices for each path, otherwise return corresponding lists of edge numbers from graph.
pairwise	If TRUE, calculate paths only between the ordered pairs of from and to. In this case, each of these must be the same length, and the output will contain paths the i-th members of each, and thus also be of that length.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Radix, Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23).
quiet	If FALSE, display progress messages on screen.

Value

List of list of paths tracing all connections between nodes such that if `x <-dodgr_paths (graph, from, to)`, then the path between `from[i]` and `to[j]` is `x [[i]] [[j]]`.

Note

graph must minimally contain four columns of from, to, dist. If an additional column named weight or wt is present, shortest paths are calculated according to values specified in that column; otherwise according to dist values. Either way, final distances between from and to points are calculated according to values of dist. That is, paths between any pair of points will be calculated according to the minimal total sum of weight values (if present), while reported distances will be total sums of dist values.

The from and to columns of graph may be either single columns of numeric or character values specifying the numbers or names of graph vertices, or combinations to two columns specifying geographical (longitude and latitude) coordinates. In the latter case, almost any sensible combination of names will be accepted (for example, fromx, fromy, from_x, from_y, or fr_lat, fr_lon.)

from and to values can be either two-column matrices of equivalent of longitude and latitude coordinates, or else single columns precisely matching node numbers or names given in graph\$from or graph\$to. If to is missing, pairwise distances are calculated between all points specified in from. If neither from nor to are specified, pairwise distances are calculated between all nodes in graph.

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists_categorical\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isodists\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_times\(\)](#)

Examples

```

graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 100)
to <- sample (graph$to_id, size = 50)
dp <- dodgr_paths (graph, from = from, to = to)
# dp is a list with 100 items, and each of those 100 items has 30 items, each
# of which is a single path listing all vertiex IDs as taken from `graph`.

# it is also possible to calculate paths between pairwise start and end
# points
from <- sample (graph$from_id, size = 5)
to <- sample (graph$to_id, size = 5)
dp <- dodgr_paths (graph, from = from, to = to, pairwise = TRUE)
# dp is a list of 5 items, each of which just has a single path between each
# pairwise from and to point.

```

`dodgr_sample`*dodgr_sample*

Description

Sample a random but connected sub-component of a graph

Usage

```
dodgr_sample(graph, nverts = 1000)
```

Arguments

graph	A flat table of graph edges. Must contain columns labelled from and to, or start and stop. May also contain similarly labelled columns of spatial coordinates (for example from_x) or stop_lon).
nverts	Number of vertices to sample

Value

A connected sub-component of graph

Note

Graphs may occasionally have nverts + 1 vertices, rather than the requested nverts.

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
nrow (graph) # 5,742
graph <- dodgr_sample (graph, nverts = 200)
nrow (graph) # generally around 400 edges
nrow (dodgr_vertices (graph)) # 200
```

dodgr_save_streetnet *Save a weighted streetnet to a local file*

Description

The [weight_streetnet](#) function returns a single data.frame object, the processing of which also relies on a couple of cached lookup-tables to match edges in the data.frame to objects in the original input data. It automatically calculates and caches a contracted version of the same graph, to enable rapid conversion between contracted and uncontracted forms. This function saves all of these items in a single .Rds file, so that the result of a linkweight_streetnet call can be rapidly loaded into a workspace in subsequent sessions, rather than re-calculating the entire weighted network.

Usage

```
dodgr_save_streetnet(net, filename = NULL)
```

Arguments

net	data.frame or equivalent object representing the weighted network graph.
filename	Name with optional full path of file in which to save the input net. The extension .Rds will be automatically appended, unless specified otherwise.

Note

This may take some time if [dodgr_cache_off](#) has been called. The contracted version of the graph is also saved, and so must be calculated if it has not previously been automatically cached.

See Also

Other cache: [clear_dodgr_cache\(\)](#), [dodgr_cache_off\(\)](#), [dodgr_cache_on\(\)](#), [dodgr_load_streetnet\(\)](#)

Examples

```
net <- weight_streetnet (hampi)
f <- file.path (tempdir (), "streetnet.Rds")
dodgr_save_streetnet (net, f)
clear_dodgr_cache () # rm cached objects from tempdir
# at some later time, or in a new R session:
net <- dodgr_load_streetnet (f)
```

dodgr_sfines_to_poly *dodgr_sfines_to_poly*

Description

Convert **sf** LINESTRING objects to POLYGON objects representing all fundamental cycles within the LINESTRING objects.

Usage

```
dodgr_sfines_to_poly(sfines, graph_max_size = 10000, expand = 0.05)
```

Arguments

sfines	An sf LINESTRING object representing a network.
graph_max_size	Maximum size submitted to the internal C++ routines as a single chunk. Warning: Increasing this may lead to computer meltdown!
expand	For large graphs which must be broken into chunks, this factor determines the relative overlap between chunks to ensure all cycles are captured. (This value should only need to be modified in special cases.)

Value

An `sf::sfc` collection of POLYGON objects.

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile\(\)](#)

dodgr_streetnet *dodgr_streetnet*

Description

Use the `osmdata` package to extract the street network for a given location. For routing between a given set of points (passed as `pts`), the `bbox` argument may be omitted, in which case a bounding box will be constructed by expanding the range of `pts` by the relative amount of `expand`.

Usage

```
dodgr_streetnet(bbox, pts = NULL, expand = 0.05, quiet = TRUE)
```

Arguments

bbox	Bounding box as vector or matrix of coordinates, or location name. Passed to <code>osmdata::getbb</code> .
pts	List of points presumably containing spatial coordinates
expand	Relative factor by which street network should extend beyond limits defined by pts (only if bbox not given).
quiet	If FALSE, display progress messages

Value

A Simple Features (sf) object with coordinates of all lines in the street network.

Note

Calls to this function may return "General overpass server error" with a note that "Query timed out." The overpass served used to access the data has a sophisticated queueing system which prioritises requests that are likely to require little time. These timeout errors can thus generally *not* be circumvented by changing "timeout" options on the HTTP requests, and should rather be interpreted to indicate that a request is too large, and may need to be refined, or somehow broken up into smaller queries.

See Also

Other extraction: [dodgr_streetnet_sc\(\)](#), [weight_railway\(\)](#), [weight_streetnet\(\)](#)

Examples

```
## Not run:
streetnet <- dodgr_streetnet ("hampi india", expand = 0)
# convert to form needed for `dodgr` functions:
graph <- weight_streetnet (streetnet)
nrow (graph) # around 5,900 edges
# Alternative ways of extracting street networks by using a small selection
# of graph vertices to define bounding box:
verts <- dodgr_vertices (graph)
verts <- verts [sample (nrow (verts), size = 200), ]
streetnet <- dodgr_streetnet (pts = verts, expand = 0)
graph <- weight_streetnet (streetnet)
nrow (graph)
# This will generally have many more rows because most street networks
# include streets that extend considerably beyond the specified bounding box.

# bbox can also be a polygon:
bb <- osmdata::getbb ("gent belgium") # rectangular bbox
nrow (dodgr_streetnet (bbox = bb)) # around 30,000
bb <- osmdata::getbb ("gent belgium", format_out = "polygon")
nrow (dodgr_streetnet (bbox = bb)) # around 17,000
# The latter has fewer rows because only edges within polygon are returned

# Example with access restrictions
```

```

bbox <- c (-122.2935, 47.62663, -122.28, 47.63289)
x <- dodgr_streetnet_sc (bbox)
net <- weight_streetnet (x, keep_cols = "access, turn_penalty = TRUE)
# has many streets with "access" = "private; these can be removed like this:
net2 <- net [which (!net$access != "private"), ]
# or modified in some other way such as strongly penalizing use of those
# streets:
index <- which (net$access == "private")
net$time_weighted [index] <- net$time_weighted [index] * 100

## End(Not run)

```

dodgr_streetnet_sc *dodgr_streetnet_sc*

Description

Use the `osmdata` package to extract the street network for a given location and return it in SC-format. For routing between a given set of points (passed as `pts`), the `bbox` argument may be omitted, in which case a bounding box will be constructed by expanding the range of `pts` by the relative amount of `expand`.

Usage

```
dodgr_streetnet_sc(bbox, pts = NULL, expand = 0.05, quiet = TRUE)
```

Arguments

<code>bbox</code>	Bounding box as vector or matrix of coordinates, or location name. Passed to <code>osmdata::getbb</code> .
<code>pts</code>	List of points presumably containing spatial coordinates
<code>expand</code>	Relative factor by which street network should extend beyond limits defined by <code>pts</code> (only if <code>bbox</code> not given).
<code>quiet</code>	If <code>FALSE</code> , display progress messages

Value

A Simple Features (`sf`) object with coordinates of all lines in the street network.

See Also

Other extraction: [dodgr_streetnet\(\)](#), [weight_railway\(\)](#), [weight_streetnet\(\)](#)

Examples

```

## Not run:
streetnet <- dodgr_streetnet ("hampi india", expand = 0)
# convert to form needed for `dodgr` functions:
graph <- weight_streetnet (streetnet)
nrow (graph) # around 5,900 edges
# Alternative ways of extracting street networks by using a small selection
# of graph vertices to define bounding box:
verts <- dodgr_vertices (graph)
verts <- verts [sample (nrow (verts), size = 200), ]
streetnet <- dodgr_streetnet (pts = verts, expand = 0)
graph <- weight_streetnet (streetnet)
nrow (graph)
# This will generally have many more rows because most street networks
# include streets that extend considerably beyond the specified bounding box.

# bbox can also be a polygon:
bb <- osmdata::getbb ("gent belgium") # rectangular bbox
nrow (dodgr_streetnet (bbox = bb)) # around 30,000
bb <- osmdata::getbb ("gent belgium", format_out = "polygon")
nrow (dodgr_streetnet (bbox = bb)) # around 17,000
# The latter has fewer rows because only edges within polygon are returned

# Example with access restrictions
bbox <- c (-122.2935, 47.62663, -122.28, 47.63289)
x <- dodgr_streetnet_sc (bbox)
net <- weight_streetnet (x, keep_cols = "access, turn_penalty = TRUE)
# has many streets with "access" = "private; these can be removed like this:
net2 <- net [which (!net$access != "private"), ]
# or modified in some other way such as strongly penalizing use of those
# streets:
index <- which (net$access == "private")
net$time_weighted [index] <- net$time_weighted [index] * 100

## End(Not run)

```

dodgr_times

dodgr_times

Description

Calculate matrix of pair-wise travel times between points.

Usage

```
dodgr_times(graph, from = NULL, to = NULL, shortest = FALSE, heap = "BHeap")
```

Arguments

graph	A dodgr network returned from the weight_streetnet function using a network obtained with the <code>osmdata</code> <code>osmdata_sc</code> function, possibly contracted with dodgr_contract_graph .
from	Vector or matrix of points from which route distances are to be calculated (see Notes)
to	Vector or matrix of points to which route distances are to be calculated (see Notes)
shortest	If TRUE, calculate times along the <i>shortest</i> rather than fastest paths.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; FHeap), Binary Heap (BHeap), Trinomial Heap (TriHeap), Extended Trinomial Heap (TriHeapExt, and 2-3 Heap (Heap23').

Value

square matrix of distances between nodes

See Also

Other distances: [dodgr_distances\(\)](#), [dodgr_dists_categorical\(\)](#), [dodgr_dists\(\)](#), [dodgr_flows_aggregate\(\)](#), [dodgr_flows_disperse\(\)](#), [dodgr_flows_si\(\)](#), [dodgr_isochrones\(\)](#), [dodgr_isodists\(\)](#), [dodgr_isoverts\(\)](#), [dodgr_paths\(\)](#)

Examples

```
# A simple graph
graph <- data.frame (from = c ("A", "B", "B", "B", "C", "C", "D", "D"),
                    to = c ("B", "A", "C", "D", "B", "D", "C", "A"),
                    d = c (1, 2, 1, 3, 2, 1, 2, 1))

dodgr_dists (graph)

# A larger example from the included [hampi()] data.
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 100)
to <- sample (graph$to_id, size = 50)
d <- dodgr_dists (graph, from = from, to = to)
# d is a 100-by-50 matrix of distances between `from` and `to`

## Not run:
# a more complex street network example, thanks to @chrijo; see
# https://github.com/ATFutures/dodgr/issues/47

xy <- rbind (c (7.005994, 51.45774), # limbeckerplatz 1 essen germany
            c (7.012874, 51.45041)) # hauptbahnhof essen germany
xy <- data.frame (lon = xy [, 1], lat = xy [, 2])
essen <- dodgr_streetnet (pts = xy, expand = 0.2, quiet = FALSE)
graph <- weight_streetnet (essen, wt_profile = "foot")
d <- dodgr_dists (graph, from = xy, to = xy)
# First reason why this does not work is because the graph has multiple,
# disconnected components.
table (graph$component)
```

```

# reduce to largest connected component, which is always number 1
graph <- graph [which (graph$component == 1), ]
d <- dodgr_dists (graph, from = xy, to = xy)
# should work, but even then note that
table (essen$level)
# There are parts of the network on different building levels (because of
# shopping malls and the like). These may or may not be connected, so it may
# be necessary to filter out particular levels
index <- which (! (essen$level == "-1" | essen$level == "1")) # for example
library (sf) # needed for following sub-select operation
essen <- essen [index, ]
graph <- weight_streetnet (essen, wt_profile = "foot")
graph <- graph [which (graph$component == 1), ]
d <- dodgr_dists (graph, from = xy, to = xy)

## End(Not run)

```

dodgr_to_igraph

dodgr_to_igraph

Description

Convert a dodgr graph to an **igraph**.

Usage

```
dodgr_to_igraph(graph, weight_column = "d")
```

Arguments

graph	A dodgr graph
weight_column	The column of the dodgr network to use as the edge weights in the igraph representation.

Value

The igraph equivalent of the input. Note that this will *not* be a dual-weighted graph.

See Also

[igraph_to_dodgr](#)

Other conversion: [dodgr_to_sfc\(\)](#), [dodgr_to_sf\(\)](#), [dodgr_to_tidygraph\(\)](#), [igraph_to_dodgr\(\)](#)

Examples

```

graph <- weight_streetnet (hampi)
graphi <- dodgr_to_igraph (graph)

```

dodgr_to_sf	<i>dodgr_to_sf</i>
-------------	--------------------

Description

Convert a `dodgr` graph into an equivalent `sf` object. Works by aggregating edges into `LINESTRING` objects representing longest sequences between all junction nodes. The resultant objects will generally contain more `LINESTRING` objects than the original `sf` object, because the former will be bisected at every junction point.

Usage

```
dodgr_to_sf(graph)
```

Arguments

graph	A <code>dodgr</code> graph
-------	----------------------------

Value

Equivalent object of class `sf`.

Note

Requires the `sf` package to be installed.

See Also

Other conversion: [dodgr_to_igraph\(\)](#), [dodgr_to_sfc\(\)](#), [dodgr_to_tidygraph\(\)](#), [igraph_to_dodgr\(\)](#)

Examples

```
hw <- weight_streetnet (hampi)
nrow(hw) # 5,729 edges
xy <- dodgr_to_sf (hw)
dim (xy) # 764 edges; 14 attributes
```

dodgr_to_sfc

dodgr_to_sfc

Description

Convert a `dodgr` graph into a `list` composed of two objects: `dat`, a `data.frame`; and `geometry`, an `sfc` object from the (`sf`) package. Works by aggregating edges into `LINESTRING` objects representing longest sequences between all junction nodes. The resultant objects will generally contain more `LINESTRING` objects than the original `sf` object, because the former will be bisected at every junction point.

Usage

```
dodgr_to_sfc(graph)
```

Arguments

`graph` A `dodgr` graph

Value

A `list` containing (1) A `data.frame` of data associated with the `sf` geometries; and (ii) A Simple Features Collection (`sfc`) list of `LINESTRING` objects.

Note

The output of this function corresponds to the edges obtained from `dodgr_contract_graph`. This function does not require the `sf` package to be installed; the corresponding function that creates a full `sf` object - [dodgr_to_sf](#) does requires `sf` to be installed.

See Also

Other conversion: [dodgr_to_igraph\(\)](#), [dodgr_to_sf\(\)](#), [dodgr_to_tidygraph\(\)](#), [igraph_to_dodgr\(\)](#)

Examples

```
hw <- weight_streetnet (hampi)
nrow(hw)
xy <- dodgr_to_sfc (hw)
dim (hw) # 5.845 edges
length (xy$geometry) # more linestrings aggregated from those edges
nrow (hampi) # than the 191 linestrings in original sf object
dim (xy$dat) # same number of rows as there are geometries
# The dodgr_to_sf function then just implements this final conversion:
# sf::st_sf (xy$dat, geometry = xy$geometry, crs = 4326)
```

dodgr_to_tidygraph *dodgr_to_tidygraph*

Description

Convert a dodgr graph to an **tidygraph**.

Usage

```
dodgr_to_tidygraph(graph)
```

Arguments

graph A dodgr graph

Value

The tidygraph equivalent of the input

See Also

Other conversion: [dodgr_to_igraph\(\)](#), [dodgr_to_sfc\(\)](#), [dodgr_to_sf\(\)](#), [igraph_to_dodgr\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
graph_t <- dodgr_to_tidygraph (graph)
```

dodgr_uncontract_graph *dodgr_uncontract_graph*

Description

Revert a contracted graph created with [dodgr_contract_graph](#) back to the full, uncontracted version. This function is mostly used for the side effect of mapping any new columns inserted on to the contracted graph back on to the original graph, as demonstrated in the example.

Usage

```
dodgr_uncontract_graph(graph)
```

Arguments

graph A contracted graph created from [dodgr_contract_graph](#).

Value

A single data.frame representing the equivalent original, uncontracted graph.

See Also

Other modification: [dodgr_components\(\)](#), [dodgr_contract_graph\(\)](#)

Examples

```
graph0 <- weight_streetnet (hampi)
nrow (graph0) # 5,845
graph1 <- dodgr_contract_graph (graph0)
nrow (graph1) # 686
graph2 <- dodgr_uncontract_graph (graph1)
nrow (graph2) # 5,845

# Insert new data on to the contracted graph and uncontract it:
graph1$new_col <- runif (nrow (graph1))
graph3 <- dodgr_uncontract_graph (graph1)
# graph3 is then the uncontracted graph which includes "new_col" as well
dim (graph0); dim (graph3)
```

dodgr_vertices

dodgr_vertices

Description

Extract vertices of graph, including spatial coordinates if included

Usage

```
dodgr_vertices(graph)
```

Arguments

graph	A flat table of graph edges. Must contain columns labelled from and to, or start and stop. May also contain similarly labelled columns of spatial coordinates (for example from_x) or stop_lon).
-------	--

Value

A data.frame of vertices with unique numbers (n).

Note

Values of n are 0-indexed

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
v <- dodgr_vertices (graph)
```

estimate_centrality_threshold
estimate_centrality_threshold

Description

Estimate a value for the 'dist_threshold' parameter of the [dodgr_centrality](#) function. Providing distance thresholds to this function generally provides considerably speed gains, and results in approximations of centrality. This function enables the determination of values of 'dist_threshold' corresponding to specific degrees of accuracy.

Usage

```
estimate_centrality_threshold(graph, tolerance = 0.001)
```

Arguments

graph	'data.frame' or equivalent object representing the network graph (see Details)
tolerance	Desired maximal degree of inaccuracy in centrality estimates <ul style="list-style-type: none">values will be accurate to within this amount, subject to a constant scaling factor. Note that threshold values increase non-linearly with decreasing values of 'tolerance'

Value

A single value for 'dist_threshold' giving the required tolerance.

Note

This function may take some time to execute. While running, it displays ongoing information on screen of estimated values of 'dist_threshold' and associated errors. Thresholds are progressively increased until the error is reduced below the specified tolerance.

See Also

Other centrality: [dodgr_centrality\(\)](#), [estimate_centrality_time\(\)](#)

```
estimate_centrality_time
      estimate_centrality_time
```

Description

The 'dodgr' centrality functions are designed to be applied to potentially very large graphs, and may take considerable time to execute. This helper function estimates how long a centrality function may take for a given graph and given value of 'dist_threshold' estimated via the [estimate_centrality_threshold](#) function.

Usage

```
estimate_centrality_time(
  graph,
  contract = TRUE,
  edges = TRUE,
  dist_threshold = NULL,
  heap = "BHeap"
)
```

Arguments

graph	'data.frame' or equivalent object representing the network graph (see Details)
contract	If 'TRUE', centrality is calculated on contracted graph before mapping back on to the original full graph. Note that for street networks, in particular those obtained from the osmdata package, vertex placement is effectively arbitrary except at junctions; centrality for such graphs should only be calculated between the latter points, and thus 'contract' should always be 'TRUE'.
edges	If 'TRUE', centrality is calculated for graph edges, returning the input 'graph' with an additional 'centrality' column; otherwise centrality is calculated for vertices, returning the equivalent of 'dodgr_vertices(graph)', with an additional vertex-based 'centrality' column.
dist_threshold	If not 'NULL', only calculate centrality for each point out to specified threshold. Setting values for this will result in approximate estimates for centrality, yet with considerable gains in computational efficiency. For sufficiently large values, approximations will be accurate to within some constant multiplier. Appropriate values can be established via the estimate_centrality_threshold function.
heap	Type of heap to use in priority queue. Options include Fibonacci Heap (default; 'FHeap'), Binary Heap ('BHeap'), Trinomial Heap ('TriHeap'), Extended Trinomial Heap ('TriHeapExt', and 2-3 Heap ('Heap23').

Value

An estimated calculation time for calculating centrality for the given value of 'dist_threshold'

Note

This function may take some time to execute. While running, it displays ongoing information on screen of estimated values of 'dist_threshold' and associated errors. Thresholds are progressively increased until the error is reduced below the specified tolerance.

See Also

Other centrality: [dodgr_centrality\(\)](#), [estimate_centrality_threshold\(\)](#)

hampi

hampi

Description

A sample street network from the township of Hampi, Karnataka, India.

Format

A Simple Features sf data.frame containing the street network of Hampi.

Note

Can be re-created with the following command, which also removes extraneous columns to reduce size:

See Also

Other data: [os_roads_bristol](#), [weighting_profiles](#)

Examples

```
## Not run:
hampi <- dodgr_streetnet("hampi india")
cols <- c("osm_id", "highway", "oneway", "geometry")
hampi <- hampi[, which(names(hampi) %in% cols)]

## End(Not run)
# this 'sf data.frame' can be converted to a 'dodgr' network with
net <- weight_streetnet(hampi, wt_profile = 'foot')
```

igraph_to_dodgr *igraph_to_dodgr*

Description

Convert a **igraph** network to an equivalent dodgr representation.

Usage

```
igraph_to_dodgr(graph)
```

Arguments

graph An **igraph** network

Value

The dodgr equivalent of the input.

See Also

[dodgr_to_igraph](#)

Other conversion: [dodgr_to_igraph\(\)](#), [dodgr_to_sfc\(\)](#), [dodgr_to_sf\(\)](#), [dodgr_to_tidygraph\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
graphi <- dodgr_to_igraph (graph)
graph2 <- igraph_to_dodgr (graphi)
identical (graph2, graph) # FALSE
```

match_points_to_graph *match_points_to_graph*

Description

Alias for [match_points_to_graph](#)

Usage

```
match_points_to_graph(verts, xy, connected = FALSE)
```


Arguments

verts	A data.frame of vertices obtained from <code>dodgr_vertices(graph)</code> .
xy	coordinates of points to be matched to the vertices, either as matrix or sf -formatted data.frame.
connected	Should points be matched to the same (largest) connected component of graph? If FALSE and these points are to be used for a <code>dodgr</code> routing routine (<code>dodgr_dists</code> , <code>dodgr_paths</code> , or <code>dodgr_flows_aggregate</code>), then results may not be returned if points are not part of the same connected component. On the other hand, forcing them to be part of the same connected component may decrease the spatial accuracy of matching.

Value

A vector index into `verts`

See Also

Other misc: `compare_heaps()`, `dodgr_flowmap()`, `dodgr_full_cycles()`, `dodgr_fundamental_cycles()`, `dodgr_insert_vertex()`, `dodgr_sample()`, `dodgr_sflines_to_poly()`, `dodgr_vertices()`, `match_pts_to_graph()`, `merge_directed_graph()`, `summary.dodgr_dists_categorical()`, `write_dodgr_wt_profile()`

Examples

```
net <- weight_streetnet (hampi, wt_profile = "foot")
verts <- dodgr_vertices (net)
# Then generate some random points to match to graph
npts <- 10
xy <- data.frame (
  x = min (verts$x) + runif (npts) * diff (range (verts$x)),
  y = min (verts$y) + runif (npts) * diff (range (verts$y))
)
pts <- match_pts_to_graph (verts, xy)
pts # an index into verts
pts <- verts$id [pts]
pts # names of those vertices
```

match_pts_to_graph *match_pts_to_graph*

Description

Match spatial points to a spatial graph which contains vertex coordinates

Usage

```
match_pts_to_graph(verts, xy, connected = FALSE)
```

Arguments

verts	A data.frame of vertices obtained from <code>dodgr_vertices(graph)</code> .
xy	coordinates of points to be matched to the vertices, either as matrix or sf -formatted data.frame.
connected	Should points be matched to the same (largest) connected component of graph? If FALSE and these points are to be used for a <code>dodgr</code> routing routine (<code>dodgr_dists</code> , <code>dodgr_paths</code> , or <code>dodgr_flows_aggregate</code>), then results may not be returned if points are not part of the same connected component. On the other hand, forcing them to be part of the same connected component may decrease the spatial accuracy of matching.

Value

A vector index into `verts`

See Also

Other misc: `compare_heaps()`, `dodgr_flowmap()`, `dodgr_full_cycles()`, `dodgr_fundamental_cycles()`, `dodgr_insert_vertex()`, `dodgr_sample()`, `dodgr_sflines_to_poly()`, `dodgr_vertices()`, `match_points_to_graph()`, `merge_directed_graph()`, `summary.dodgr_dists_categorical()`, `write_dodgr_wt_profile()`

Examples

```
net <- weight_streetnet (hampi, wt_profile = "foot")
verts <- dodgr_vertices (net)
# Then generate some random points to match to graph
npts <- 10
xy <- data.frame (
  x = min (verts$x) + runif (npts) * diff (range (verts$x)),
  y = min (verts$y) + runif (npts) * diff (range (verts$y))
)
pts <- match_pts_to_graph (verts, xy)
pts # an index into verts
pts <- verts$id [pts]
pts # names of those vertices
```

merge_directed_graph *merge_directed_graph*

Description

Merge directed edges into equivalent undirected values by aggregating across directions. This function is primarily intended to aid visualisation of directed graphs, particularly visualising the results of the `dodgr_flows_aggregate` and `dodgr_flows_disperse` functions, which return columns of aggregated flows directed along each edge of a graph.

Usage

```
merge_directed_graph(graph, col_names = c("flow"))
```

Arguments

graph	A undirected graph in which directed edges of the input graph have been merged through aggregation to yield a single, undirected edge between each pair of vertices.
col_names	Names of columns to be merged through aggregation. Values for these columns in resultant undirected graph will be aggregated from directed values.

Value

An equivalent graph in which all directed edges have been reduced to single, undirected edges, and all values of the specified column(s) have been aggregated across directions to undirected values.

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#), [write_dodgr_wt_profile\(\)](#)

Examples

```
graph <- weight_streetnet (hampi)
from <- sample (graph$from_id, size = 10)
to <- sample (graph$to_id, size = 5)
to <- to [!to %in% from]
flows <- matrix (10 * runif (length (from) * length (to)),
                 nrow = length (from))
graph <- dodgr_flows_aggregate (graph, from = from, to = to, flows = flows)
# graph then has an additional 'flows` column of aggregate flows along all
# edges. These flows are directed, and can be aggregated to equivalent
# undirected flows on an equivalent undirected graph with:
graph_undir <- merge_directed_graph (graph)
# This graph will only include those edges having non-zero flows, and so:
nrow (graph); nrow (graph_undir) # the latter is much smaller
```

os_roads_bristol

os_roads_bristol

Description

A sample street network for Bristol, U.K., from the Ordnance Survey.

Format

A Simple Features sf data.frame representing motorways in Bristol, UK.

Note

Input data downloaded from <https://osdatahub.os.uk/downloads/open>, To download the data from that page click on the tick box next to 'OS Open Roads', scroll to the bottom, click 'Continue' and complete the form on the subsequent page. This dataset is open access and can be used under the [Open Government License](#) and must be cited as follows: Contains OS data © Crown copyright and database right (2017)

See Also

Other data: [hampi](#), [weighting_profiles](#)

Examples

```
## Not run:
library(sf)
library(dplyr)
# data must be unzipped here
# os_roads <- sf::read_sf("~/data/ST_RoadLink.shp")
# u <- "https://opendata.arcgis.com/datasets/686603e943f948acaa13fb5d2b0f1275_4.kml"
# lads <- sf::read_sf(u)
# mapview::mapview(lads)
# bristol_pol <- dplyr::filter(lads, grepl("Bristol", lad16nm))
# os_roads <- st_transform(os_roads, st_crs(lads))
# os_roads_bristol <- os_roads[bristol_pol, ] %>%
#   dplyr::filter(class == "Motorway" &
#                 roadNumber != "M32") %>%
#   st_zm(drop = TRUE)
# mapview::mapview(os_roads_bristol)

## End(Not run)
# Converting this 'sf data.frame' to a 'dodgr' network requires manual
# specification of weighting profile:
colnm <- "formOfWay" # name of column used to determine weights
wts <- data.frame (name = "custom",
                  way = unique (os_roads_bristol [[colnm]]),
                  value = c (0.1, 0.2, 0.8, 1))
net <- weight_streetnet (os_roads_bristol, wt_profile = wts,
                       type_col = colnm, id_col = "identifier")
# 'id_col' tells the function which column to use to attribute IDs of ways
```

summary.dodgr_dists_categorical

Transform a result from 'dodgr_dists_categorical' to summary statistics

Description

Transform a result from 'dodgr_dists_categorical' to summary statistics

Usage

```
## S3 method for class 'dodgr_dists_categorical'  
summary(object, ...)
```

Arguments

object	A 'dodgr_dists_categorical' object
...	Extra parameters currently not used

Value

The summary statistics (invisibly)

See Also

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [write_dodgr_wt_profile\(\)](#)

weighting_profiles *weighting_profiles*

Description

Collection of weighting profiles used to adjust the routing process to different means of transport. Modified from data taken from the Routino project, with additional tables for average speeds, dependence of speed on type of surface, and waiting times in seconds at traffic lights. The latter table (called "penalties") includes waiting times at traffic lights (in seconds), additional time penalties for turning across oncoming traffic ("turn"), and a binary flag indicating whether turn restrictions should be obeyed or not.

Format

List of `data.frame` objects with profile names, means of transport and weights.

References

<https://www.routino.org/xml/routino-profiles.xml>

See Also

Other data: [hampi](#), [os_roads_bristol](#)

weight_railway	<i>weight_railway</i>
----------------	-----------------------

Description

Weight (or re-weight) an sf-formatted OSM street network for routing along railways.

Usage

```
weight_railway(
  sf_lines,
  type_col = "railway",
  id_col = "osm_id",
  keep_cols = c("maxspeed"),
  excluded = c("abandoned", "disused", "proposed", "razed")
)
```

Arguments

<code>sf_lines</code>	A street network represented as sf LINESTRING objects, typically extracted with <code>dodgr_streetnet</code>
<code>type_col</code>	Specify column of the sf data.frame object which designates different types of railways to be used for weighting (default works with osmdata objects).
<code>id_col</code>	Specify column of the codesf data.frame object which provides unique identifiers for each railway (default works with osmdata objects).
<code>keep_cols</code>	Vectors of columns from <code>sf_lines</code> to be kept in the resultant dodgr network; vector can be either names or indices of desired columns.
<code>excluded</code>	Types of railways to exclude from routing.

Value

A data.frame of edges representing the rail network, along with a column of graph component numbers.

Note

Default railway weighting is by distance. Other weighting schemes, such as by maximum speed, can be implemented simply by modifying the `d_weighted` column returned by this function accordingly.

See Also

Other extraction: [dodgr_streetnet_sc\(\)](#), [dodgr_streetnet\(\)](#), [weight_streetnet\(\)](#)

Examples

```
## Not run:
# sample railway extraction with the 'osmdata' package
library (osmdata)
dat <- opq ("shinjuku") %>%
  add_osm_feature (key = "railway") %>%
  osmdata_sf (quiet = FALSE)
graph <- weight_railway (dat$osm_lines)

## End(Not run)
```

```
weight_streetnet      weight_streetnet
```

Description

Weight (or re-weight) an **sf** or SC (silicate)-formatted OSM street network according to a named profile, selected from (foot, horse, wheelchair, bicycle, moped, motorcycle, motorcar, goods, hgv, psv), or a customized version derived from those.

Usage

```
weight_streetnet(
  x,
  wt_profile = "bicycle",
  wt_profile_file = NULL,
  turn_penalty = FALSE,
  type_col = "highway",
  id_col = "osm_id",
  keep_cols = NULL,
  left_side = FALSE
)

## Default S3 method:
weight_streetnet(
  x,
  wt_profile = "bicycle",
  wt_profile_file = NULL,
  turn_penalty = FALSE,
  type_col = "highway",
  id_col = "osm_id",
  keep_cols = NULL,
  left_side = FALSE
)

## S3 method for class 'sf'
weight_streetnet(
```

```

x,
wt_profile = "bicycle",
wt_profile_file = NULL,
turn_penalty = FALSE,
type_col = "highway",
id_col = "osm_id",
keep_cols = NULL,
left_side = FALSE
)

## S3 method for class 'sc'
weight_streetnet(
  x,
  wt_profile = "bicycle",
  wt_profile_file = NULL,
  turn_penalty = FALSE,
  type_col = "highway",
  id_col = "osm_id",
  keep_cols = NULL,
  left_side = FALSE
)

```

Arguments

<code>x</code>	A street network represented either as <code>sf</code> <code>LINestring</code> objects, typically extracted with <code>dodgr_streetnet</code> , or as an <code>SC</code> (silicate) object typically extracted with the <code>dodgr_streetnet_sc</code> .
<code>wt_profile</code>	Name of weighting profile, or <code>data.frame</code> specifying custom values (see Details)
<code>wt_profile_file</code>	Name of locally-stored, <code>.json</code> -formatted version of <code>dodgr::weighting_profiles</code> , created with <code>write_dodgr_wt_profile</code> , and modified as desired.
<code>turn_penalty</code>	Including time penalty on edges for turning across oncoming traffic at intersections (see Note).
<code>type_col</code>	Specify column of the <code>sf data.frame</code> object which designates different types of highways to be used for weighting (default works with <code>osmdata</code> objects).
<code>id_col</code>	For <code>sf</code> -formatted data only: Specify column of the <code>codesf data.frame</code> object which provides unique identifiers for each highway (default works with <code>osmdata</code> objects).
<code>keep_cols</code>	Vectors of columns from <code>x</code> to be kept in the resultant <code>dodgr</code> network; vector can be either names or indices of desired columns (see notes).
<code>left_side</code>	Does traffic travel on the left side of the road (<code>TRUE</code>) or the right side (<code>FALSE</code>)? - only has effect on turn angle calculations for edge times.

Value

A `data.frame` of edges representing the street network, with distances in metres and times in seconds, along with a column of graph component numbers. Times for `sf`-formatted street net-

works are only approximate, and do not take into account traffic lights, turn angles, or elevation changes. Times for `sc`-formatted street networks take into account all of these factors, with elevation changes automatically taken into account for networks generated with the `osmdata` function `osm_elevation()`.

Note

Names for the `wt_profile` parameter are taken from `weighting_profiles`, which is a list including a `data.frame` also called `weighting_profiles` of weights for different modes of transport. Values for `wt_profile` are taken from current modes included there, which are "bicycle", "foot", "goods", "hgv", "horse", "moped", "motorcar", "motorcycle", "psv", and "wheelchair". Railway routing can be implemented with the separate function `weight_railway`. Alternatively, the entire `weighting_profile` structures can be written to a local `.json`-formatted file with `write_dodgr_wt_profile`, the values edited as desired, and the name of this file passed as the `wt_profile_file` parameter.

Realistic routing include factors such as access restrictions, turn penalties, and effects of incline, can only be implemented when the objects passed to `weight_streetnet` are of `sc` ("silicate") format, generated with `dodgr_streetnet_sc`. Restrictions applies to ways (in Open Streetmap Terminology) may be controlled by ensuring specific columns are retained in the `dodgr` network with the `keep_cols` argument. For example, restrictions on access are generally specified by specifying a value for the key of "access". Include "access" in `keep_cols` will ensure these values are retained in the `dodgr` version, from which ways with specified values can easily be removed or modified, as demonstrated in the examples.

The additional Open Street Map (OSM) keys which can be used to specify restrictions are which are automatically extracted with `dodgr_streetnet_sc`, and so may be added to the `keep_cols` argument, include:

- "highway"
- "restriction"
- "access"
- "bicycle"
- "motorcar"
- "motor_vehicle"
- "vehicle"
- "toll"

Restrictions and time-penalties on turns can be implemented from such objects by setting `turn_penalty = TRUE`. Resultant graphs are fundamentally different from the default for distance-based routing. The result of `weight_streetnet(..., turn_penalty = TRUE)` should thus *only* be used to submit to the `dodgr_times` function, and not for any other `dodgr` functions nor forms of network analysis. Setting `turn_penalty = TRUE` will honour turn restrictions specified in Open Street Map (unless the "penalties" table of `weighting_profiles` has `restrictions = FALSE` for a specified `wt_profile`).

The resultant graph includes only those edges for which the given weighting profile specifies finite edge weights. Any edges of types not present in a given weighting profile are automatically removed from the weighted streetnet.

If the resultant graph is to be contracted via `dodgr_contract_graph`, **and** if the columns of the graph have been, or will be, modified, then automatic caching must be switched off with `dodgr_cache_off`.

```
write_dodgr_wt_profile  
write_dodgr_wt_profile
```

Description

Write the dodgr street network weighting profiles to a local .json-formatted file for manual editing and subsequent re-reading.

Usage

```
write_dodgr_wt_profile(file = NULL)
```

Arguments

file	Full name (including path) of file to which to write. The .json suffix will be automatically appended.
------	--

Value

TRUE if writing successful.

See Also

[weight_streetnet](#)

Other misc: [compare_heaps\(\)](#), [dodgr_flowmap\(\)](#), [dodgr_full_cycles\(\)](#), [dodgr_fundamental_cycles\(\)](#), [dodgr_insert_vertex\(\)](#), [dodgr_sample\(\)](#), [dodgr_sflines_to_poly\(\)](#), [dodgr_vertices\(\)](#), [match_points_to_graph\(\)](#), [match_pts_to_graph\(\)](#), [merge_directed_graph\(\)](#), [summary.dodgr_dists_categorical\(\)](#)

Index

- * **cache**
 - clear_dodgr_cache, 3
 - dodgr_cache_off, 5
 - dodgr_cache_on, 6
 - dodgr_load_streetnet, 31
 - dodgr_save_streetnet, 34
 - * **centrality**
 - dodgr_centrality, 6
 - estimate_centrality_threshold, 45
 - estimate_centrality_time, 46
 - * **conversion**
 - dodgr_to_igraph, 40
 - dodgr_to_sf, 41
 - dodgr_to_sfc, 42
 - dodgr_to_tidygraph, 43
 - igraph_to_dodgr, 48
 - * **datasets**
 - hampi, 47
 - os_roads_bristol, 51
 - weighting_profiles, 53
 - * **data**
 - hampi, 47
 - os_roads_bristol, 51
 - weighting_profiles, 53
 - * **distances**
 - dodgr_distances, 10
 - dodgr_dists, 12
 - dodgr_dists_categorical, 14
 - dodgr_flows_aggregate, 17
 - dodgr_flows_disperse, 20
 - dodgr_flows_si, 22
 - dodgr_isochrones, 27
 - dodgr_isodists, 28
 - dodgr_isoverts, 29
 - dodgr_paths, 31
 - dodgr_times, 38
 - * **extraction**
 - dodgr_streetnet, 35
 - dodgr_streetnet_sc, 37
 - weight_railway, 54
 - weight_streetnet, 55
 - * **misc**
 - compare_heaps, 3
 - dodgr_flowmap, 16
 - dodgr_full_cycles, 24
 - dodgr_fundamental_cycles, 25
 - dodgr_insert_vertex, 26
 - dodgr_sample, 33
 - dodgr_sflines_to_poly, 35
 - dodgr_vertices, 44
 - match_points_to_graph, 48
 - match_pts_to_graph, 49
 - merge_directed_graph, 50
 - summary.dodgr_dists_categorical, 52
 - write_dodgr_wt_profile, 59
 - * **modification**
 - dodgr_components, 9
 - dodgr_contract_graph, 9
 - dodgr_uncontract_graph, 43
 - * **package**
 - dodgr, 4
- clear_dodgr_cache, 3, 5, 6, 31, 34
- compare_heaps, 3, 17, 25–27, 33, 35, 45, 49–51, 53, 59
- compare_heaps(), 5
- dodgr, 4
- dodgr_cache_off, 3, 5, 6, 31, 34, 57
- dodgr_cache_on, 3, 5, 6, 31, 34
- dodgr_centrality, 6, 45, 47
- dodgr_components, 9, 10, 44
- dodgr_components(), 5
- dodgr_contract_graph, 9, 9, 26, 31, 39, 43, 44, 57, 58
- dodgr_contract_graph(), 5
- dodgr_distances, 10, 13, 16, 19, 21, 24, 28–30, 32, 39

- dodgr_dists, *10, 11, 12, 16, 19, 21, 24, 28–30, 32, 39, 49, 50*
- dodgr_dists(), *4*
- dodgr_dists_categorical, *11, 13, 14, 19, 21, 24, 28–30, 32, 39*
- dodgr_flowmap, *4, 16, 25–27, 33, 35, 45, 49–51, 53, 59*
- dodgr_flows_aggregate, *11, 13, 16, 17, 17, 21, 24, 28–30, 32, 39, 49, 50*
- dodgr_flows_disperse, *11, 13, 16, 17, 19, 20, 24, 28–30, 32, 39, 50*
- dodgr_flows_si, *11, 13, 16, 19, 21, 22, 28–30, 32, 39*
- dodgr_full_cycles, *4, 17, 24, 26, 27, 33, 35, 45, 49–51, 53, 59*
- dodgr_fundamental_cycles, *4, 17, 25, 25, 27, 33, 35, 45, 49–51, 53, 59*
- dodgr_insert_vertex, *4, 17, 25, 26, 26, 33, 35, 45, 49–51, 53, 59*
- dodgr_isochrones, *11, 13, 16, 19, 21, 24, 27, 29, 30, 32, 39*
- dodgr_isodists, *11, 13, 16, 19, 21, 24, 28, 28, 30, 32, 39*
- dodgr_isoverts, *11, 13, 16, 19, 21, 24, 28, 29, 29, 32, 39*
- dodgr_load_streetnet, *3, 5, 6, 31, 34*
- dodgr_paths, *11, 13, 16, 19, 21, 24, 28–30, 31, 39, 49, 50*
- dodgr_sample, *4, 17, 25–27, 33, 35, 45, 49–51, 53, 59*
- dodgr_sample(), *5*
- dodgr_save_streetnet, *3, 5, 6, 31, 34*
- dodgr_sflines_to_poly, *4, 17, 25–27, 33, 35, 45, 49–51, 53, 59*
- dodgr_streetnet, *35, 37, 54, 56, 58*
- dodgr_streetnet(), *5*
- dodgr_streetnet_sc, *36, 37, 54, 56–58*
- dodgr_times, *11, 13, 16, 19, 21, 24, 28–30, 32, 38, 57, 58*
- dodgr_to_igraph, *40, 41–43, 48*
- dodgr_to_sf, *40, 41, 42, 43, 48*
- dodgr_to_sfc, *40, 41, 42, 43, 48*
- dodgr_to_tidygraph, *40–42, 43, 48*
- dodgr_uncontract_graph, *9, 10, 43*
- dodgr_vertices, *4, 17, 25–27, 33, 35, 44, 49–51, 53, 59*
- dodgr_vertices(), *5*
- estimate centrality_threshold, *7, 45, 46, 47*
- estimate centrality_time, *7, 45, 46*
- hampi, *47, 52, 53*
- igraph_to_dodgr, *40–43, 48*
- match_points_to_graph, *4, 17, 25–27, 33, 35, 45, 48, 48, 50, 51, 53, 59*
- match_pts_to_graph, *4, 17, 25–27, 33, 35, 45, 49, 49, 51, 53, 59*
- merge_directed_graph, *4, 17, 25–27, 33, 35, 45, 49, 50, 50, 53, 59*
- os_roads_bristol, *47, 51, 53*
- summary.dodgr_dists_categorical, *4, 17, 25–27, 33, 35, 45, 49–51, 52, 59*
- weight_railway, *36, 37, 54, 57, 58*
- weight_streetnet, *13, 34, 36, 37, 39, 54, 55, 59*
- weight_streetnet(), *5*
- weighting_profiles, *47, 52, 53, 57*
- write_dodgr_wt_profile, *4, 17, 25–27, 33, 35, 45, 49–51, 53, 56–58, 59*