

Package ‘r.proxy’

May 9, 2026

Type Package

Title Set Proxy in R Console

Version 0.1.3

Maintainer Yonghe Xia <xiayh17@gmail.com>

Description The use of proxies is required in certain network environments. Despite the power of system level software, it is still inconvenient to switch proxy networks at random in R's console. This package is designed to provide one-click switching between proxy and non-proxy states.

License MIT + file LICENSE

URL <https://github.com/xiayh17/r.proxy>

BugReports <https://github.com/xiayh17/r.proxy/issues>

Imports curl, httr, jsonlite

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Yonghe Xia [aut, ctb, cre]

Repository CRAN

Date/Publication 2023-08-15 13:30:02 UTC

Contents

check_ip	2
init_proxy	2
noproxy	3
proxy	3

Index	4
--------------	----------

check_ip	<i>Check IP</i>
----------	-----------------

Description

check what your IP is

Usage

```
check_ip()
```

Details

Use [curl_fetch_memory](#) to get information about the web page <https://api-ipv4.ip.sb/ip> & <https://api.ip.sb/geoip>

Value

IP information

Examples

```
## Not run:  
check_ip()  
  
## End(Not run)
```

init_proxy	<i>Initialization proxy settings</i>
------------	--------------------------------------

Description

When user use it in the first time or reset proxy, this will run and store setting in home directory.

Usage

```
init_proxy()
```

Value

a file in home directory

Examples

```
## Not run:  
init_proxy()  
  
## End(Not run)
```

noproxy

Reset proxy

Description

unset proxy http https and socks5

Usage

noproxy()

Value

unset proxy http https and socks5

Examples

```
## Not run:  
noproxy()  
  
## End(Not run)
```

proxy

Set proxy

Description

set proxy for http https and socks5

Usage

proxy()

Value

set proxy for http https and socks5

Examples

```
## Not run:  
proxy()  
  
## End(Not run)
```

Index

check_ip, [2](#)
curl_fetch_memory, [2](#)

init_proxy, [2](#)

noproxy, [3](#)

proxy, [3](#)